

Package ‘dynamite’

May 30, 2023

Title Bayesian Modeling and Causal Inference for Multivariate Longitudinal Data

Version 1.4.3

Description Easy-to-use and efficient interface for Bayesian inference of complex panel (time series) data using dynamic multivariate panel models by Helske and Tikka (2022) <[doi:10.31235/osf.io/mdwu5](https://doi.org/10.31235/osf.io/mdwu5)>. The package supports joint modeling of multiple measurements per individual, time-varying and time-invariant effects, and a wide range of discrete and continuous distributions. Estimation of these dynamic multivariate panel models is carried out via 'Stan'. For an in-depth tutorial of the package, see (Tikka and Helske, 2023) <[arxiv:2302.01607](https://arxiv.org/abs/2302.01607)>.

License GPL (>= 3)

URL <https://docs.ropensci.org/dynamite/>,
<https://github.com/ropensci/dynamite/>

BugReports <https://github.com/ropensci/dynamite/issues/>

Depends R (>= 3.6.0)

Imports checkmate, cli, data.table, glue, ggplot2, loo, methods, patchwork, posterior, rlang, rstan, stats, tibble (>= 2.0.0), utils

Suggests bookdown, cmdstanr, covr, dplyr, knitr, mockthat, rmarkdown, testthat (>= 3.0.0), tidyr

VignetteBuilder knitr

Config/testthat/edition 3

Encoding UTF-8

RoxygenNote 7.2.3

LazyData true

LazyDataCompression xz

Additional_repositories <https://mc-stan.org/r-packages/>

NeedsCompilation no

Author Santtu Tikka [aut, cre] (<<https://orcid.org/0000-0003-4039-4342>>),
 Jouni Helske [aut] (<<https://orcid.org/0000-0001-7130-793X>>),
 Nicholas Clark [rev],
 Lucy D'Agostino McGowan [rev]

Maintainer Santtu Tikka <santtuth@gmail.com>

Repository CRAN

Date/Publication 2023-05-30 09:20:06 UTC

R topics documented:

dynamite-package	3
as.data.frame.dynamitefit	3
as.data.table.dynamitefit	7
as_draws_df.dynamitefit	8
categorical_example	10
categorical_example_fit	11
coef.dynamitefit	12
confint.dynamitefit	13
dynamite	14
dynamiteformula	18
fitted.dynamitefit	21
gaussian_example	23
gaussian_example_fit	24
gaussian_simulation_fit	25
get_code	26
get_data	27
get_parameter_dims	28
get_parameter_names	29
get_parameter_types	30
get_priors	31
lags	33
lfactor	34
lfo	35
loo.dynamitefit	37
mcmc_diagnostics	38
multichannel_example	39
multichannel_example_fit	39
ndraws.dynamitefit	41
nobs.dynamitefit	41
plot.dynamitefit	42
plot.lfo	43
plot_betas	44
plot_deltas	45
plot_lambdas	46
plot_nus	46
plot_psis	47
predict.dynamitefit	48

`as.data.frame.dynamitefit` 3

<code>print.lfo</code>	51
<code>random_spec</code>	52
<code>splines</code>	53
<code>update.dynamitefit</code>	55

Index 57

`dynamite-package` *The dynamite package.*

Description

Easy-to-use and efficient interface for Bayesian inference of complex panel data consisting of multiple individuals with multiple measurements over time. Supports several observational distributions, time-varying effects and realistic counterfactual predictions which take into account the dynamic structure of the model.

See Also

- The package vignette.
- `dynamiteformula()` for information on defining models.
- `dynamite()` for information on fitting models.
- <https://github.com/ropensci/dynamite/issues/> to submit a bug report or a feature request.

Authors

Santtu Tikka (author) santtuth@gmail.com
Jouni Helske (author) jouni.helske@iki.fi

`as.data.frame.dynamitefit`
Extract Samples From a dynamitefit Object as a Data Frame

Description

Provides a `data.frame` representation of the posterior samples of the model parameters.

Usage

```
## S3 method for class 'dynamitefit'
```

```

as.data.frame(
  x,
  row.names = NULL,
  optional = FALSE,
  parameters = NULL,
  responses = NULL,
  types = NULL,
  summary = FALSE,
  probs = c(0.05, 0.95),
  include_fixed = TRUE,
  ...
)

```

Arguments

x	[dynamitefit] The model fit object.
row.names	Ignored.
optional	Ignored.
parameters	[character()] Parameter(s) for which the samples should be extracted. Possible options can be found with function <code>get_parameter_names()</code> . Default is all parameters of specific type for all responses.
responses	[character()] Response(s) for which the samples should be extracted. Possible options are elements of <code>unique(x\$priors\$response)</code> , and the default is this entire vector. Ignored if the argument <code>parameters</code> is supplied.
types	[character()] Type(s) of the parameters for which the samples should be extracted. See details of possible values. Default is all values listed in details except spline coefficients <code>omega</code> , <code>omega_alpha</code> , and <code>omega_psi</code> . See also get_parameter_types() . Ignored if the argument <code>parameters</code> is supplied.
summary	[logical(1)] If TRUE, returns posterior mean, standard deviation, and posterior quantiles (as defined by the <code>probs</code> argument) for all parameters. If FALSE (default), returns the posterior samples instead.
probs	[numeric()] Quantiles of interest. Default is <code>c(0.05, 0.95)</code> .
include_fixed	[logical(1)] If TRUE (default), time-varying parameters for 1:fixed time points are included in the output as NA values. If FALSE, fixed time points are omitted completely from the output.
...	Ignored.

Details

The arguments `responses` and `types` can be used to extract only a subset of the model parameters (i.e., only certain types of parameters related to a certain response variable).

Potential values for the `types` argument are:

- `alpha`
Intercept terms (time-invariant or time-varying).
- `beta`
Time-invariant regression coefficients.
- `delta`
Time-varying regression coefficients.
- `nu`
Group-level random effects.
- `lambda`
Factor loadings.
- `psi`
Latent factors.
- `tau`
Standard deviations of the spline coefficients of `delta`.
- `tau_alpha`
Standard deviations of the spline coefficients of time-varying `alpha`.
- `sigma_nu`
Standard deviations of the random effects `nu`.
- `corr_nu`
Pairwise within-group correlations of random effects `nu`. Samples of the full correlation matrix can be extracted manually as `rstan::extract(fit$stanfit, pars = "corr_matrix_nu")` if necessary.
- `sigma_lambda`
Standard deviations of the latent factor loadings `lambda`.
- `tau_psi`
Standard deviations of the the spline coefficients of `psi`.
- `corr_psi`
Pairwise correlations of the latent factors. Samples of the full correlation matrix can be extracted manually as `rstan::extract(fit$stanfit, pars = "corr_matrix_psi")` if necessary.
- `sigma`
Standard deviations of gaussian responses.
- `corr`
Pairwise correlations of multivariate gaussian responses.
- `phi`
Describes various distributional parameters, such as:
 - Dispersion parameter of the Negative Binomial distribution.
 - Shape parameter of the Gamma distribution.

- Precision parameter of the Beta distribution.
- Degrees of freedom of the Student t-distribution.
- omega
Spline coefficients of the regression coefficients delta.
- omega_alpha
Spline coefficients of time-varying alpha.
- omega_psi
Spline coefficients of the latent factors psi.

Value

A tibble containing either samples or summary statistics of the model parameters in a long format. For a wide format, see [as_draws\(\)](#).

See Also

Model outputs [as.data.table.dynamitefit\(\)](#), [as_draws_df.dynamitefit\(\)](#), [coef.dynamitefit\(\)](#), [confint.dynamitefit\(\)](#), [dynamite\(\)](#), [get_code\(\)](#), [get_data\(\)](#), [get_parameter_dims\(\)](#), [get_parameter_names\(\)](#), [get_parameter_types\(\)](#), [ndraws.dynamitefit\(\)](#), [nobs.dynamitefit\(\)](#)

Examples

```
as.data.frame(
  gaussian_example_fit,
  responses = "y",
  types = "beta"
)

# Basic summaries can be obtained automatically with summary = TRUE
as.data.frame(
  gaussian_example_fit,
  responses = "y",
  types = "beta",
  summary = TRUE
)

# Time-varying coefficients "delta"
as.data.frame(
  gaussian_example_fit,
  responses = "y",
  types = "delta",
  summary = TRUE
)

# Obtain summaries for a specific parameters
as.data.frame(
  gaussian_example_fit,
  parameters = c("tau_y_x", "sigma_y"),
  summary = TRUE
)
```

 as.data.table.dynamitefit

Extract Samples From a dynamitefit Object as a Data Table

Description

Provides a `data.table` representation of the posterior samples of the model parameters. See [as.data.frame.dynamitefit\(\)](#) for details.

Usage

```
## S3 method for class 'dynamitefit'
as.data.table(
  x,
  keep.rownames = FALSE,
  row.names = NULL,
  optional = FALSE,
  parameters = NULL,
  responses = NULL,
  types = NULL,
  summary = FALSE,
  probs = c(0.05, 0.95),
  include_fixed = TRUE,
  ...
)
```

Arguments

<code>x</code>	[<code>dynamitefit</code>] The model fit object.
<code>keep.rownames</code>	[<code>logical(1)</code>] Not used.
<code>row.names</code>	Ignored.
<code>optional</code>	Ignored.
<code>parameters</code>	[<code>character()</code>] Parameter(s) for which the samples should be extracted. Possible options can be found with function <code>get_parameter_names()</code> . Default is all parameters of specific type for all responses.
<code>responses</code>	[<code>character()</code>] Response(s) for which the samples should be extracted. Possible options are elements of <code>unique(x\$priors\$response)</code> , and the default is this entire vector. Ignored if the argument <code>parameters</code> is supplied.
<code>types</code>	[<code>character()</code>] Type(s) of the parameters for which the samples should be extracted. See details of possible values. Default is all values listed in details except spline coefficients

	omega, omega_alpha, and omega_psi. See also get_parameter_types() . Ignored if the argument parameters is supplied.
summary	[logical(1)] If TRUE, returns posterior mean, standard deviation, and posterior quantiles (as defined by the probs argument) for all parameters. If FALSE (default), returns the posterior samples instead.
probs	[numeric()] Quantiles of interest. Default is <code>c(0.05, 0.95)</code> .
include_fixed	[logical(1)] If TRUE (default), time-varying parameters for 1:fixed time points are included in the output as NA values. If FALSE, fixed time points are omitted completely from the output.
...	Ignored.

Value

A `data.table` containing either samples or summary statistics of the model parameters.

See Also

Model outputs [as.data.frame.dynamitefit\(\)](#), [as_draws_df.dynamitefit\(\)](#), [coef.dynamitefit\(\)](#), [confint.dynamitefit\(\)](#), [dynamite\(\)](#), [get_code\(\)](#), [get_data\(\)](#), [get_parameter_dims\(\)](#), [get_parameter_names\(\)](#), [get_parameter_types\(\)](#), [ndraws.dynamitefit\(\)](#), [nobs.dynamitefit\(\)](#)

Examples

```
as.data.table(
  gaussian_example_fit,
  responses = "y",
  types = "beta",
  summary = FALSE
)
```

as_draws_df.dynamitefit

Convert dynamite Output to draws_df Format

Description

Converts the output from a [dynamite\(\)](#) call to a `draws_df` format of the **posterior** package, enabling the use of diagnostics and plotting methods of **posterior** and **bayesplot** packages. Note that this function returns variables in a wide format, whereas [as.data.frame\(\)](#) uses the long format.

Usage

```
## S3 method for class 'dynamitefit'
as_draws_df(x, parameters = NULL, responses = NULL, types = NULL, ...)

## S3 method for class 'dynamitefit'
as_draws(x, parameters = NULL, responses = NULL, types = NULL, ...)
```

Arguments

x	[dynamitefit] The model fit object.
parameters	[character()] Parameter(s) for which the samples should be extracted. Possible options can be found with function <code>get_parameter_names()</code> . Default is all parameters of specific type for all responses.
responses	[character()] Response(s) for which the samples should be extracted. Possible options are elements of <code>unique(x\$priors\$response)</code> , and the default is this entire vector. Ignored if the argument <code>parameters</code> is supplied.
types	[character()] Type(s) of the parameters for which the samples should be extracted. See details of possible values. Default is all values listed in details except spline coefficients <code>omega</code> , <code>omega_alpha</code> , and <code>omega_psi</code> . See also <code>get_parameter_types()</code> . Ignored if the argument <code>parameters</code> is supplied.
...	Ignored.

Details

You can use the arguments `parameters`, `responses` and `types` to extract only a subset of the model parameters (i.e., only certain types of parameters related to a certain response variable).

See potential values for the `types` argument in `as.data.frame.dynamitefit()` and `get_parameter_names()` for potential values for `parameters` argument.

Value

A `draws_df` object.

A `draws_df` object.

See Also

Model outputs `as.data.frame.dynamitefit()`, `as.data.table.dynamitefit()`, `coef.dynamitefit()`, `confint.dynamitefit()`, `dynamite()`, `get_code()`, `get_data()`, `get_parameter_dims()`, `get_parameter_names()`, `get_parameter_types()`, `ndraws.dynamitefit()`, `nobs.dynamitefit()`

Examples

```
as_draws(gaussian_example_fit, types = c("sigma", "beta"))

# Compute MCMC diagnostics using the posterior package
posterior::summarise_draws(as_draws(gaussian_example_fit))
```

categorical_example *Simulated Categorical Multivariate Panel Data*

Description

A simulated data containing multiple individuals with two categorical response variables.

Usage

```
categorical_example
```

Format

A data frame with 2000 rows and 5 variables:

id Variable defining individuals (1 to 100).

time Variable defining the time point of the measurement (1 to 20).

x Categorical variable with three levels, A, B, and C.

y Categorical variable with three levels, a, b, and c.

z A continuous covariate.

Source

The data was generated according to a script in https://github.com/ropensci/dynamite/blob/main/data-raw/categorical_example.R

See Also

Example models [categorical_example_fit](#), [gaussian_example_fit](#), [gaussian_example](#), [gaussian_simulation_fit](#), [multichannel_example_fit](#), [multichannel_example](#)

`categorical_example_fit`*Model Fit for the Simulated Categorical Multivariate Panel Data*

Description

A dynamitefit object obtained by running dynamite on the categorical_example dataset as

```
set.seed(1)
library(dynamite)
f <- obs(x ~ z + lag(x) + lag(y), family = "categorical") +
  obs(y ~ z + lag(x) + lag(y), family = "categorical")
categorical_example_fit <- dynamite(
  f,
  data = categorical_example,
  time = "time",
  group = "id",
  chains = 1,
  refresh = 0,
  thin = 5,
  save_warmup = FALSE
)
```

Note the small number of samples due to size restrictions on CRAN.

Usage

```
categorical_example_fit
```

Format

A dynamitefit object.

Source

Script in https://github.com/ropensci/dynamite/blob/main/data-raw/categorical_example_fit.R

See Also

Example models [categorical_example](#), [gaussian_example_fit](#), [gaussian_example](#), [gaussian_simulation_fit](#), [multichannel_example_fit](#), [multichannel_example](#)

 coef.dynamitefit *Extract Regression Coefficients of a Dynamite Model*

Description

Extracts either time-varying or time-invariant parameters of the model.

Usage

```
## S3 method for class 'dynamitefit'
coef(
  object,
  parameters = NULL,
  type = c("beta", "delta", "nu", "lambda", "psi"),
  responses = NULL,
  summary = TRUE,
  probs = c(0.05, 0.95),
  include_alpha = TRUE,
  ...
)
```

Arguments

object	[dynamitefit] The model fit object.
parameters	[character()] Parameter(s) for which the samples should be extracted. Possible options can be found with function <code>get_parameter_names()</code> . Default is all parameters of specific type for all responses.
type	[character(1)] Either <code>beta</code> (the default) for time-invariant coefficients, <code>delta</code> for time-varying coefficients, <code>nu</code> for random effects, <code>lambda</code> for factor loadings, or <code>psi</code> for latent factor. Ignored if the argument <code>parameters</code> is supplied.
responses	[character()] Response(s) for which the samples should be extracted. Possible options are elements of <code>unique(x\$priors\$response)</code> , and the default is this entire vector. Ignored if the argument <code>parameters</code> is supplied.
summary	[logical(1)] If <code>TRUE</code> , returns posterior mean, standard deviation, and posterior quantiles (as defined by the <code>probs</code> argument) for all parameters. If <code>FALSE</code> (default), returns the posterior samples instead.
probs	[numeric()] Quantiles of interest. Default is <code>c(0.05, 0.95)</code> .

include_alpha	[logical(1)] If TRUE (default), extracts also time-invariant intercept term alpha if time-invariant parameters beta are extracted, and time-varying alpha if time-varying delta are extracted. Ignored if the argument parameters is supplied. @param summary [logical(1)] If TRUE (default), returns posterior mean, standard deviation, and posterior quantiles (as defined by the probs argument) for all parameters. If FALSE, returns the posterior samples instead.
...	Ignored.

Value

A tibble containing either samples or summary statistics of the model parameters in a long format.

See Also

Model outputs [as.data.frame.dynamitefit\(\)](#), [as.data.table.dynamitefit\(\)](#), [as_draws_df.dynamitefit\(\)](#), [confint.dynamitefit\(\)](#), [dynamite\(\)](#), [get_code\(\)](#), [get_data\(\)](#), [get_parameter_dims\(\)](#), [get_parameter_names\(\)](#), [get_parameter_types\(\)](#), [ndraws.dynamitefit\(\)](#), [nobs.dynamitefit\(\)](#)

Examples

```
betas <- coef(gaussian_example_fit, type = "beta")
deltas <- coef(gaussian_example_fit, type = "delta")
```

confint.dynamitefit *Credible Intervals for Dynamite Model Parameters*

Description

Extracts credible intervals from dynamitefit object.

Usage

```
## S3 method for class 'dynamitefit'
confint(object, parm, level = 0.95, ...)
```

Arguments

object	[dynamitefit] The model fit object.
parm	Ignored.
level	[numeric(1)] Credible interval width.
...	Ignored.

Value

The rows of the resulting matrix will be named using the following logic: {parameter}_{time}_{category}_{group} where parameter is the name of the parameter, time is the time index of the parameter, category specifies the level of the response the parameter is related to if the response is categorical, and group determines which group of observations the parameter is related to in the case of random effects and loadings. Non-applicable fields in the this syntax are set to NA.

See Also

Model outputs `as.data.frame.dynamitefit()`, `as.data.table.dynamitefit()`, `as_draws_df.dynamitefit()`, `coef.dynamitefit()`, `dynamite()`, `get_code()`, `get_data()`, `get_parameter_dims()`, `get_parameter_names()`, `get_parameter_types()`, `ndraws.dynamitefit()`, `nobs.dynamitefit()`

Examples

```
confint(gaussian_example_fit, level = 0.9)
```

dynamite

Estimate a Bayesian Dynamic Multivariate Panel Model

Description

Fit a Bayesian dynamic multivariate panel model (DMPM) using Stan for Bayesian inference. The **dynamite** package supports a wide range of distributions and allows the user to flexibly customize the priors for the model parameters. The dynamite model is specified using standard R formula syntax via `dynamiteformula()`. For more information and examples, see 'Details' and the package vignettes.

The `formula` method returns the model definition as a quoted expression.

Information on the estimated dynamite model can be obtained via `print` including the following: The model formula, the data, the smallest effective sample sizes, largest Rhat and summary statistics of the time-invariant model parameters.

The `summary` method provides statistics of the posterior samples of the model; this is an alias of `as.data.frame.dynamitefit()` with `summary = TRUE`.

Usage

```
dynamite(
  dformula,
  data,
  time,
  group = NULL,
  priors = NULL,
  backend = "rstan",
  verbose = TRUE,
  verbose_stan = FALSE,
```

```

    stanc_options = list("01"),
    threads_per_chain = 1L,
    grainsize = NULL,
    debug = NULL,
    ...
)

## S3 method for class 'dynamitefit'
formula(x, ...)

## S3 method for class 'dynamitefit'
print(x, ...)

## S3 method for class 'dynamitefit'
summary(object, ...)

```

Arguments

dformula	[dynamiteformula] The model formula. See dynamiteformula() and 'Details'.
data	[data.frame , tibble::tibble , or data.table::data.table] The data that contains the variables in the model in long format. Supported column types are integer, logical, double, and factor. Columns of type character will be converted to factors. Unused factor levels will be dropped. The data can contain missing values which will simply be ignored in the estimation in a case-wise fashion (per time-point and per channel). Input data is converted to channel specific matrix representations via stats::model.matrix.lm() .
time	[character(1)] A column name of data that denotes the time index of observations. If this variable is a factor, the integer representation of its levels are used internally for defining the time indexing.
group	[character(1)] A column name of data that denotes the unique groups or NULL corresponding to a scenario without any groups. If group is NULL, a new column <code>.group</code> is created with constant value 1L indicating that all observations belong to the same group. In case of name conflicts with data, see the <code>group_var</code> element of the return object to get the column name of the new variable.
priors	[data.frame] An optional data frame with prior definitions. See get_priors() and 'Details'.
backend	[character(1)] Defines the backend interface to Stan, should be either "rstan" (the default) or "cmdstanr". Note that cmdstanr needs to be installed separately as it is not on CRAN. It also needs the actual CmdStan software. See https://mc-stan.org/cmdstanr/ for details.
verbose	[logical(1)] All warnings and messages are suppressed if set to FALSE. Defaults to TRUE.

verbose_stan	[logical(1)] This is the verbose argument for <code>rstan::sampling()</code> . Defaults to FALSE.
stanc_options	[list()] This is the stanc_options argument passed to the compile method of a <code>CmdStanModel</code> object via <code>cmdstanr::cmdstan_model()</code> when backend = "cmdstanr". Defaults to <code>list("01")</code> to enable level one compiler optimizations.
threads_per_chain	[integer(1)] A Positive integer defining the number of parallel threads to use within each chain. Default is 1. See <code>rstan::rstan_options()</code> and <code>cmdstanr::sample()</code> for details.
grainsize	[integer(1)] A Positive integer defining the suggested size of the partial sums when using within-chain parallelization. Default is number of time points divided by <code>threads_per_chain</code> . Setting this to 1 leads the workload division entirely to the internal scheduler. The performance of the within-chain parallelization can be sensitive to the choice of <code>grainsize</code> , see Stan manual on reduce-sum for details.
debug	[list()] A named list of form <code>name = TRUE</code> indicating additional objects in the environment of the <code>dynamite</code> function which are added to the return object. Additionally, values <code>no_compile = TRUE</code> and <code>no_sampling = TRUE</code> can be used to skip the compilation of the Stan code and sampling steps respectively. This can be useful for debugging when combined with <code>model_code = TRUE</code> , which adds the Stan model code to the return object.
...	For <code>dynamite()</code> , additional arguments to <code>rstan::sampling()</code> or <code>cmdstanr::sample()</code> , such as <code>chains</code> and <code>cores</code> (<code>chains</code> and <code>parallel_chains</code> in <code>cmdstanr</code>). For <code>summary()</code> , additional arguments to <code>as.data.frame.dynamitefit()</code> . For <code>print()</code> , further arguments to the print method for tibbles (see <code>tibble::formatting</code>). Not used for <code>formula()</code> .
x	[dynamitefit] The model fit object.
object	[dynamitefit] The model fit object.

Details

The best-case scalability of `dynamite` in terms of data size should be approximately linear in terms of number of time points and number of groups, but as wall-clock time of the MCMC algorithms provided by Stan can depend on the discrepancy of the data and the model (and the subsequent shape of the posterior), this can vary greatly.

Value

`dynamite` returns a `dynamitefit` object which is a list containing the following components:

- `stanfit`
A `stanfit` object, see `rstan::sampling()` for details.

- `dformulas`
A list of `dynamiteformula` objects for internal use.
- `data`
A processed version of the input data.
- `data_name`
Name of the input data object.
- `stan`
A list containing various elements related to Stan model construction and sampling.
- `group_var`
Name of the variable defining the groups.
- `time_var`
Name of the variable defining the time index.
- `priors`
Data frame containing the used priors.
- `backend`
Either `"rstan"` or `"cmdstanr"` indicating which package was used in sampling.
- `call`
Original function call as an object of class `call`.

`formula` returns a quoted expression.

`print` returns `x` invisibly.

`summary` returns a `data.frame`.

References

Santtu Tikka and Jouni Helske (2023). `dynamite`: An R Package for Dynamic Multivariate Panel Models. arXiv preprint, <https://arxiv.org/abs/2302.01607>.

Jouni Helske and Santtu Tikka (2022). Estimating Causal Effects from Panel Data with Dynamic Multivariate Panel Models. SocArxiv preprint, <https://osf.io/preprints/socarxiv/mdwu5/>.

See Also

Model fitting `get_priors()`, `update.dynamitefit()`

Model formula construction `dynamiteformula()`, `lags()`, `lfactor()`, `random_spec()`, `splines()`

Model outputs `as.data.frame.dynamitefit()`, `as.data.table.dynamitefit()`, `as_draws_df.dynamitefit()`, `coef.dynamitefit()`, `confint.dynamitefit()`, `get_code()`, `get_data()`, `get_parameter_dims()`, `get_parameter_names()`, `get_parameter_types()`, `ndraws.dynamitefit()`, `nobs.dynamitefit()`

Examples

```
# Please update your rstan and StanHeaders installation before running
# on Windows
if (!identical(.Platform$OS.type, "windows")) {
  fit <- dynamite(
    dformula = obs(y ~ -1 + varying(~x), family = "gaussian") +
```

```

      lags(type = "varying") +
      splines(df = 20),
    gaussian_example,
    "time",
    "id",
    chains = 1,
    refresh = 0
  )
}

formula(gaussian_example_fit)

print(gaussian_example_fit)

summary(gaussian_example_fit,
  types = "beta",
  probs = c(0.05, 0.1, 0.9, 0.95)
)
```

dynamiteformula

Model formula for dynamite

Description

Defines a new observational or a new auxiliary channel for the model using standard R formula syntax. Formulas of individual response variables can be joined together via +. See 'Details' and the package vignette for more information. The function `obs` is a shorthand alias for `dynamiteformula`, and `aux` is a shorthand alias for `dynamiteformula(formula, family = "deterministic")`.

Usage

```

dynamiteformula(formula, family)

obs(formula, family)

aux(formula)

## S3 method for class 'dynamiteformula'
e1 + e2

## S3 method for class 'dynamiteformula'
print(x, ...)
```

Arguments

```

formula      [formula]
              An R formula describing the model.
```

family	[character(1)] The family name. See 'Details' for the supported families.
e1	[dynamiteformula] A model formula specification.
e2	[dynamiteformula] A model formula specification.
x	[dynamiteformula] The model formula.
...	Ignored.

Details

Currently the **dynamite** package supports the following distributions for the observations:

- Categorical: `categorical` (with a softmax link using the first category as reference). See the documentation of the `categorical_logit_glm` in the Stan function reference manual (<https://mc-stan.org/users/documentation/>).
- Multinomial: `multinomial` (softmax link, first category is reference).
- Gaussian: `gaussian` (identity link, parameterized using mean and standard deviation).
- Multivariate Gaussian: `mvgaussian` (identity link, parameterized using mean vector, standard deviation vector and the Cholesky decomposition of the correlation matrix).
- Poisson: `poisson` (log-link, with an optional known offset variable).
- Negative-binomial: `negbin` (log-link, using mean and dispersion parameterization, with an optional known offset variable). See the documentation on `NegBinomial2` in the Stan function reference manual.
- Bernoulli: `bernoulli` (logit-link).
- Binomial: `binomial` (logit-link).
- Exponential: `exponential` (log-link).
- Gamma: `gamma` (log-link, using mean and shape parameterization).
- Beta: `beta` (logit-link, using mean and precision parameterization).
- Student t: `student` (identity link, parametrized using degrees of freedom, location and scale)

The models in the **dynamite** package are defined by combining the channel-specific formulas defined via R formula syntax. Each channel is defined via the `obs` function, and the channels are combined with `+`. For example a formula `obs(y ~ lag(x), family = "gaussian") + obs(x ~ z, family = "poisson")` defines a model with two channels; first we declare that `y` is a gaussian variable depending on a previous value of `x` (`lag(x)`), and then we add a second channel declaring `x` as Poisson distributed depending on some exogenous variable `z` (for which we do not define any distribution).

Number of trials for binomial channels should be defined via a `trials` model component, e.g., `obs(y ~ x + trials(n), family = "binomial")`, where `n` is a data variable defining the number of trials. For multinomial channels, the number of trials is automatically defined to be the sum of the observations over the categories, but can also be defined using the `trials` component, for example for prediction.

Multivariate channels are defined by providing a single formula for all components or by providing component-specific formulas separated by a `|`. The response variables that correspond to the components should be joined by `c()`. For instance, the following would define `c(y1, y2)` as multivariate gaussian with `x` as a predictor for the mean of the first component and `x` and `z` as predictors for the mean of the second component: `obs(c(y1, y2) ~ x | x + z, family = "mvgaussian")`. A multinomial channel should only have a single formula.

In addition to declaring response variables via `obs`, we can also use the function `aux` to define auxiliary channels which are deterministic functions of other variables. The values of auxiliary variables are computed dynamically during prediction, making the use of lagged values and other transformations possible. The function `aux` also does not use the `family` argument, which is automatically set to `deterministic` and is a special channel type of `obs`. Note that lagged values of deterministic `aux` channels do not imply fixed time points. Instead they must be given starting values using a special function `init` that directly initializes the lags to specified values, or by `past` which computes the initial values based on an R expression. Both `init` and `past` should appear on the right hand side of the model formula, separated from the primary defining expression via `|`.

The formula within `obs` can also contain an additional special function `varying`, which defines the time-varying part of the model equation, in which case we could write for example `obs(x ~ z + varying(~ -1 + w), family = "poisson")`, which defines a model equation with a constant intercept and time-invariant effect of `z`, and a time-varying effect of `w`. We also remove the duplicate intercept with `-1` in order to avoid identifiability issues in the model estimation (we could also define a time varying intercept, in which case we would write `obs(x ~ -1 + z + varying(~ w), family = "poisson")`). The part of the formula not wrapped with `varying` is assumed to correspond to the fixed part of the model, so `obs(x ~ z + varying(~ -1 + w), family = "poisson")` is actually identical to `obs(x ~ -1 + fixed(~ z) + varying(~ -1 + w), family = "poisson")` and `obs(x ~ fixed(~ z) + varying(~ -1 + w), family = "poisson")`.

When defining `varying` effects, we also need to define how these time-varying regression coefficients behave. For this, a `splines` component should be added to the model, e.g., `obs(x ~ varying(~ -1 + w), family = "poisson", splines = ~10)` defines a cubic B-spline with 10 degrees of freedom for the time-varying coefficient corresponding to the `w`. If the model contains multiple time-varying coefficients, same spline basis is used for all coefficients, with unique spline coefficients and their standard deviation.

If the desired model contains lagged predictors of each response in each channel, these can be quickly added to the model as either time-invariant or time-varying predictors via `lags()` instead of writing them manually for each channel.

It is also possible to define group-specific (random) effects term using the special syntax `random()` similarly as `varying()`. For example, `random(~1)` leads to a model where in addition to the common intercept, each individual/group has their own intercept with zero-mean normal prior and unknown standard deviation analogously with the typical mixed models. An additional model component `random_spec()` can be used to define whether the random effects are allowed to correlate within and across channels and whether to use centered or noncentered parameterization for the random effects.

Value

A `dynamiteformula` object.

See Also

Model formula construction `dynamite()`, `lags()`, `lfactor()`, `random_spec()`, `splines()`

Examples

```
# A single gaussian response channel with a time-varying effect of 'x',
# and a time-varying effect of the lag of 'y' using B-splines with
# 20 degrees of freedom for the coefficients of the time-varying terms.
obs(y ~ -1 + varying(~x), family = "gaussian") +
  lags(type = "varying") +
  splines(df = 20)

# A two-channel categorical model with time-invariant predictors
# here, lag terms are specified manually
obs(x ~ z + lag(x) + lag(y), family = "categorical") +
  obs(y ~ z + lag(x) + lag(y), family = "categorical")

# The same categorical model as above, but with the lag terms
# added using 'lags'
obs(x ~ z, family = "categorical") +
  obs(y ~ z, family = "categorical") +
  lags(type = "fixed")

# A multichannel model with a gaussian, Poisson and a Bernoulli response and
# an auxiliary channel for the logarithm of 'p' plus one
obs(g ~ lag(g) + lag(logp), family = "gaussian") +
  obs(p ~ lag(g) + lag(logp) + lag(b), family = "poisson") +
  obs(b ~ lag(b) * lag(logp) + lag(b) * lag(g), family = "bernoulli") +
  aux(numeric(logp) ~ log(p + 1))

obs(y ~ x, family = "gaussian") + obs(z ~ w, family = "exponential")

x <- obs(y ~ x + random(~ 1 + lag(d)), family = "gaussian") +
  obs(z ~ varying(~w), family = "exponential") +
  aux(numeric(d) ~ log(y) | init(c(0, 1))) +
  lags(k = 2) +
  splines(df = 5) +
  random_spec(correlated = FALSE)
print(x)
```

fitted.dynamitefit *Extract Fitted Values of a Dynamite Model*

Description

Fitted values for a dynamitefit object, i.e., $E(y_t | \text{newdata}, \theta)$ where θ contains all the model parameters. See also `predict.dynamitefit()` for multi-step predictions.

Usage

```
## S3 method for class 'dynamitefit'
fitted(object, newdata = NULL, n_draws = NULL, expand = TRUE, df = TRUE, ...)
```

Arguments

object	[dynamitefit] The model fit object.
newdata	[data.frame] Data used in predictions. If NULL (default), the data used in model estimation is used for predictions as well. There should be no new time points that were not present in the data that were used to fit the model, and no new group levels can be included.
n_draws	[integer(1)] Number of posterior samples to use, default is NULL which uses all samples.
expand	[logical(1)] If TRUE (the default), the output is a single data.frame containing the original newdata and the predicted values. Otherwise, a list is returned with two components, simulated and observed, where the first contains only the predicted values, and the second contains the original newdata. Setting expand to FALSE can help conserve memory because newdata is not replicated n_draws times in the output. This argument is ignored if funs are provided.
df	[logical(1)] If TRUE (default) the output consists of data.frame objects, and data.table objects otherwise.
...	Ignored.

Value

A data.frame containing the fitted values.

See Also

Obtaining predictions [predict.dynamitefit\(\)](#)

Examples

```
fitted(gaussian_example_fit, n_draws = 2L)

set.seed(1)
# Please update your rstan and StanHeaders installation before running
# on Windows
if (!identical(.Platform$OS.type, "windows")) {
  fit <- dynamite(
    dformula = obs(LakeHuron ~ 1, "gaussian") + lags(),
    data = data.frame(LakeHuron, time = seq_len(length(LakeHuron)), id = 1),
    time = "time",
    group = "id",
    chains = 1,
    refresh = 0
  )
  if (requireNamespace("dplyr") &&
```

```

requireNamespace("tidyr") &&
base::getRversion() >= "4.1.0") {

# One-step ahead samples (fitted values) from the posterior
# (first time point is fixed due to lag in the model):
fitted(fit) |>
  dplyr::filter(time > 2) |>
  ggplot2::ggplot(ggplot2::aes(time, LakeHuron_fitted, group = .draw)) +
  ggplot2::geom_line(alpha = 0.5) +
  # observed values
  ggplot2::geom_line(ggplot2::aes(y = LakeHuron), colour = "tomato") +
  ggplot2::theme_bw()

# Posterior predictive distribution given the first time point:
predict(fit, type = "mean") |>
  dplyr::filter(time > 2) |>
  ggplot2::ggplot(ggplot2::aes(time, LakeHuron_mean, group = .draw)) +
  ggplot2::geom_line(alpha = 0.5) +
  # observed values
  ggplot2::geom_line(ggplot2::aes(y = LakeHuron), colour = "tomato") +
  ggplot2::theme_bw()
}
}

```

gaussian_example

Simulated Data of Gaussian Responses

Description

Simulated data containing gaussian response variables with two covariates. The dataset was generated from a model with time-varying effects of covariate *x* and the lagged value of the response variable, time-varying intercept, and time-invariant effect of covariate *z*. The time-varying coefficients vary according to a spline with 20 degrees of freedom.

Usage

```
gaussian_example
```

Format

A data frame with 3000 rows and 5 variables:

y The response variable.

x A continuous covariate.

z A binary covariate.

id Variable defining individuals (1 to 50).

time Variable defining the time point of the measurement (1 to 30).

Source

The data was generated according to a script in https://github.com/ropensci/dynamite/blob/main/data-raw/gaussian_example.R

See Also

Example models [categorical_example_fit](#), [categorical_example](#), [gaussian_example_fit](#), [gaussian_simulation_fit](#), [multichannel_example_fit](#), [multichannel_example](#)

gaussian_example_fit *Model Fit for the Simulated Data of Gaussian Responses*

Description

A dynamitefit object obtained by running dynamite on the gaussian_example dataset as

```
set.seed(1)
library(dynamite)
gaussian_example_fit <- dynamite(
  obs(y ~ -1 + z + varying(~ x + lag(y)) + random(~1), family = "gaussian") +
  random_spec() + splines(df = 20),
  data = gaussian_example,
  time = "time",
  group = "id",
  iter = 2000,
  warmup = 1000,
  thin = 10,
  chains = 2,
  cores = 2,
  refresh = 0,
  save_warmup = FALSE,
  pars = c("omega_alpha_1_y", "omega_raw_alpha_y", "nu_raw", "nu", "L",
    "sigma_nu", "a_y"),
  include = FALSE
)
```

Note the very small number of samples due to size restrictions on CRAN.

Usage

```
gaussian_example_fit
```

Format

A dynamitefit object.

Source

The data was generated according to a script in https://github.com/ropensci/dynamite/blob/main/data-raw/gaussian_example_fit.R

See Also

Example models [categorical_example_fit](#), [categorical_example](#), [gaussian_example](#), [gaussian_simulation_fit](#), [multichannel_example_fit](#), [multichannel_example](#)

gaussian_simulation_fit

Model Fit for the time-varying example in the dynamite_simulation Vignette

Description

A dynamitefit object obtained by running dynamite with the "Fixed_param" algorithm on the specified inits in the example.

```
set.seed(1)
library(dynamite)
gaussian_simulation_fit <- dynamite(
  dformula = f,
  data = d,
  time = "time",
  group = "id",
  chains = 1,
  iter = 1,
  algorithm = "Fixed_param",
  init = list(init),
)
```

Usage

```
gaussian_simulation_fit
```

Format

A dynamitefit object.

Source

The data was generated according to a script in https://github.com/ropensci/dynamite/blob/main/data-raw/gaussian_simulation_fit.R

See Also

Example models [categorical_example_fit](#), [categorical_example](#), [gaussian_example_fit](#), [gaussian_example](#), [multichannel_example_fit](#), [multichannel_example](#)

get_code

*Extract the Stan Code of the Dynamite Model***Description**

Returns the Stan code of the model. Mostly useful for debugging or for building a customized version of the model.

Usage

```
get_code(x, ...)

## S3 method for class 'dynamiteformula'
get_code(x, data, time, group = NULL, blocks = NULL, ...)

## S3 method for class 'dynamitefit'
get_code(x, blocks = NULL, ...)
```

Arguments

x	[dynamiteformula or dynamitefit] The model formula or an existing dynamitefit object. See dynamiteformula() and dynamite() .
...	Ignored.
data	[data.frame, tibble::tibble, or data.table::data.table] The data that contains the variables in the model in long format. Supported column types are integer, logical, double, and factor. Columns of type character will be converted to factors. Unused factor levels will be dropped. The data can contain missing values which will simply be ignored in the estimation in a case-wise fashion (per time-point and per channel). Input data is converted to channel specific matrix representations via stats::model.matrix.lm() .
time	[character(1)] A column name of data that denotes the time index of observations. If this variable is a factor, the integer representation of its levels are used internally for defining the time indexing.
group	[character(1)] A column name of data that denotes the unique groups or NULL corresponding to a scenario without any groups. If group is NULL, a new column .group is created with constant value 1L is created indicating that all observations belong to the same group. In case of name conflicts with data, see the group_var element of the return object to get the column name of the new variable.
blocks	[character()] Stan block names to extract. If NULL, extracts the full model code.

Value

The Stan model blocks as a character string.

See Also

Model outputs [as.data.frame.dynamitefit\(\)](#), [as.data.table.dynamitefit\(\)](#), [as_draws_df.dynamitefit\(\)](#), [coef.dynamitefit\(\)](#), [confint.dynamitefit\(\)](#), [dynamite\(\)](#), [get_data\(\)](#), [get_parameter_dims\(\)](#), [get_parameter_names\(\)](#), [get_parameter_types\(\)](#), [ndraws.dynamitefit\(\)](#), [nobs.dynamitefit\(\)](#)

Examples

```
d <- data.frame(y = rnorm(10), x = 1:10, time = 1:10, id = 1)
cat(get_code(obs(y ~ x, family = "gaussian"),
  data = d, time = "time", group = "id"
))
# same as
cat(dynamite(obs(y ~ x, family = "gaussian"),
  data = d, time = "time", group = "id",
  debug = list(model_code = TRUE, no_compile = TRUE)
)$model_code)
```

get_data

Extract the Model Data of the Dynamite Model

Description

Returns the input data to the Stan model. Mostly useful for debugging.

Usage

```
get_data(x, ...)

## S3 method for class 'dynamiteformula'
get_data(x, data, time, group = NULL, ...)

## S3 method for class 'dynamitefit'
get_data(x, ...)
```

Arguments

x	[dynamiteformula or dynamitefit] The model formula or an existing dynamitefit object. See dynamiteformula() and dynamite() .
...	Ignored.
data	[data.frame, tibble::tibble, or data.table::data.table] The data that contains the variables in the model in long format. Supported column types are integer, logical, double, and factor. Columns of type character will be converted to factors. Unused factor levels will be dropped. The data can contain missing values which will simply be ignored in the estimation in a case-wise fashion (per time-point and per channel). Input data is converted to channel specific matrix representations via stats::model.matrix.lm() .

time	[character(1)] A column name of data that denotes the time index of observations. If this variable is a factor, the integer representation of its levels are used internally for defining the time indexing.
group	[character(1)] A column name of data that denotes the unique groups or NULL corresponding to a scenario without any groups. If group is NULL, a new column <code>.group</code> is created with constant value 1L is created indicating that all observations belong to the same group. In case of name conflicts with data, see the <code>group_var</code> element of the return object to get the column name of the new variable.

Value

A list containing the input data to Stan.

See Also

Model outputs `as.data.frame.dynamitefit()`, `as.data.table.dynamitefit()`, `as_draws_df.dynamitefit()`, `coef.dynamitefit()`, `confint.dynamitefit()`, `dynamite()`, `get_code()`, `get_parameter_dims()`, `get_parameter_names()`, `get_parameter_types()`, `ndraws.dynamitefit()`, `nobs.dynamitefit()`

Examples

```
d <- data.frame(y = rnorm(10), x = 1:10, time = 1:10, id = 1)
str(get_data(obs(y ~ x, family = "gaussian"),
  data = d, time = "time", group = "id"
))
```

get_parameter_dims *Get Parameter Dimensions of the Dynamite Model*

Description

Extracts the names and dimensions of all parameters used in the dynamite model. See also `get_parameter_types()` and `get_parameter_names()`. The returned dimensions match those of the `stanfit` element of the `dynamitefit` object. When applied to `dynamiteformula` objects, the model is compiled and sampled for 1 iteration to get the parameter dimensions.

Usage

```
get_parameter_dims(x, ...)

## S3 method for class 'dynamiteformula'
get_parameter_dims(x, data, time, group = NULL, ...)

## S3 method for class 'dynamitefit'
get_parameter_dims(x, ...)
```

Arguments

x	[dynamiteformula or dynamitefit] The model formula or an existing dynamitefit object. See dynamiteformula() and dynamite() .
...	Ignored.
data	[data.frame, tibble::tibble, or data.table::data.table] The data that contains the variables in the model in long format. Supported column types are integer, logical, double, and factor. Columns of type character will be converted to factors. Unused factor levels will be dropped. The data can contain missing values which will simply be ignored in the estimation in a case-wise fashion (per time-point and per channel). Input data is converted to channel specific matrix representations via stats::model.matrix.lm() .
time	[character(1)] A column name of data that denotes the time index of observations. If this variable is a factor, the integer representation of its levels are used internally for defining the time indexing.
group	[character(1)] A column name of data that denotes the unique groups or NULL corresponding to a scenario without any groups. If group is NULL, a new column .group is created with constant value 1L is created indicating that all observations belong to the same group. In case of name conflicts with data, see the group_var element of the return object to get the column name of the new variable.

Value

A named list with all parameter dimensions of the input model.

See Also

Model outputs [as.data.frame.dynamitefit\(\)](#), [as.data.table.dynamitefit\(\)](#), [as_draws_df.dynamitefit\(\)](#), [coef.dynamitefit\(\)](#), [confint.dynamitefit\(\)](#), [dynamite\(\)](#), [get_code\(\)](#), [get_data\(\)](#), [get_parameter_names\(\)](#), [get_parameter_types\(\)](#), [ndraws.dynamitefit\(\)](#), [nobs.dynamitefit\(\)](#)

Examples

```
get_parameter_dims(multichannel_example_fit)
```

get_parameter_names *Get Parameter Names of the Dynamite Model*

Description

Extracts all parameter names of used in the dynamitefit object.

Usage

```
get_parameter_names(x, types = NULL, ...)

## S3 method for class 'dynamitefit'
get_parameter_names(x, types = NULL, ...)
```

Arguments

x	[dynamitefit] The model fit object.
types	[character()] Extract only names of parameter of a certain type. See get_parameter_types() .
...	Ignored.

Details

The naming of parameters generally follows style where the name starts with the parameter type (e.g. beta for time-invariant regression coefficient), followed by underscore and the name of the response variable, and in case of time-invariant, time-varying or random effect, the name of the predictor. An exception to this is spline coefficients omega, which also contain the number denoting the knot number.

Value

A character vector with parameter names of the input model.

See Also

Model outputs [as.data.frame.dynamitefit\(\)](#), [as.data.table.dynamitefit\(\)](#), [as_draws_df.dynamitefit\(\)](#), [coef.dynamitefit\(\)](#), [confint.dynamitefit\(\)](#), [dynamite\(\)](#), [get_code\(\)](#), [get_data\(\)](#), [get_parameter_dims\(\)](#), [get_parameter_types\(\)](#), [ndraws.dynamitefit\(\)](#), [nobs.dynamitefit\(\)](#)

Examples

```
get_parameter_names(multichannel_example_fit)
```

get_parameter_types *Get Parameter Types of the Dynamite Model*

Description

Extracts all parameter types of used in the dynamitefit object. See [as.data.frame.dynamitefit\(\)](#) for explanations of different types.

Usage

```
get_parameter_types(x, ...)

## S3 method for class 'dynamitefit'
get_parameter_types(x, ...)
```

Arguments

x	[dynamitefit] The model fit object.
...	Ignored.

Value

A character vector with all parameter types of the input model.

See Also

Model outputs [as.data.frame.dynamitefit\(\)](#), [as.data.table.dynamitefit\(\)](#), [as_draws_df.dynamitefit\(\)](#), [coef.dynamitefit\(\)](#), [confint.dynamitefit\(\)](#), [dynamite\(\)](#), [get_code\(\)](#), [get_data\(\)](#), [get_parameter_dims\(\)](#), [get_parameter_names\(\)](#), [ndraws.dynamitefit\(\)](#), [nobs.dynamitefit\(\)](#)

Examples

```
get_parameter_types(multichannel_example_fit)
```

get_priors

Get Prior Definitions of a Dynamite Model

Description

Extracts the priors used in the dynamite model as a data frame. You can then alter the priors by changing the contents of the prior column and supplying this data frame to dynamite function using the argument priors. See vignettes for details.

Usage

```
get_priors(x, ...)

## S3 method for class 'dynamiteformula'
get_priors(x, data, time, group = NULL, ...)

## S3 method for class 'dynamitefit'
get_priors(x, ...)
```

Arguments

x	[<code>dynamiteformula</code> or <code>dynamitefit</code>] The model formula or an existing <code>dynamitefit</code> object. See <code>dynamiteformula()</code> and <code>dynamite()</code> .
...	Ignored.
data	[<code>data.frame</code> , <code>tibble::tibble</code> , or <code>data.table::data.table</code>] The data that contains the variables in the model in long format. Supported column types are <code>integer</code> , <code>logical</code> , <code>double</code> , and <code>factor</code> . Columns of type <code>character</code> will be converted to factors. Unused factor levels will be dropped. The data can contain missing values which will simply be ignored in the estimation in a case-wise fashion (per time-point and per channel). Input data is converted to channel specific matrix representations via <code>stats::model.matrix.lm()</code> .
time	[<code>character(1)</code>] A column name of data that denotes the time index of observations. If this variable is a factor, the integer representation of its levels are used internally for defining the time indexing.
group	[<code>character(1)</code>] A column name of data that denotes the unique groups or <code>NULL</code> corresponding to a scenario without any groups. If <code>group</code> is <code>NULL</code> , a new column <code>.group</code> is created with constant value <code>1L</code> is created indicating that all observations belong to the same group. In case of name conflicts with <code>data</code> , see the <code>group_var</code> element of the return object to get the column name of the new variable.

Value

A `data.frame` containing the prior definitions.

Note

Only the prior column of the output should be altered when defining the user-defined priors for the `dynamite`.

See Also

Model fitting `dynamite()`, `update.dynamitefit()`

Examples

```
d <- data.frame(y = rnorm(10), x = 1:10, time = 1:10, id = 1)
get_priors(obs(y ~ x, family = "gaussian"),
  data = d, time = "time", group = "id"
)
```

lags	<i>Add Lagged Responses as Predictors to Each Channel of a Dynamite Model</i>
------	---

Description

Adds the lagged value of the response of each channel specified via `dynamiteformula()` as a predictor to each channel. The added predictors can be either time-varying or time-invariant.

Usage

```
lags(k = 1L, type = c("fixed", "varying", "random"))
```

Arguments

k	[integer()] Values lagged by k units of time of each observed response variable will be added as a predictor for each channel. Should be a positive (unrestricted) integer.
type	[integer(1)] Either "fixed" or "varying" which indicates whether the coefficients of the added lag terms should vary in time or not.

Value

An object of class lags.

See Also

Model formula construction [dynamiteformula\(\)](#), [dynamite\(\)](#), [lfactor\(\)](#), [random_spec\(\)](#), [splines\(\)](#)

Examples

```
obs(y ~ -1 + varying(~x), family = "gaussian") +
  lags(type = "varying") + splines(df = 20)

# A two-channel categorical model with time-invariant predictors
# here, lag terms are specified manually
obs(x ~ z + lag(x) + lag(y), family = "categorical") +
  obs(y ~ z + lag(x) + lag(y), family = "categorical")

# The same categorical model as above, but with the lag terms
# added using 'lags'
obs(x ~ z, family = "categorical") +
  obs(y ~ z, family = "categorical") +
  lags(type = "fixed")
```

 Ifactor

Define a Common Latent Factor for the Dynamite Model.

Description

This function can be used as part of `dynamiteformula()` to define a common latent factor component. The latent factor is modeled as a spline similarly as a time-varying intercept, but instead of having equal effect on each group, there is an additional loading variable for each group so that in the linear predictor we have a term $\lambda_i \psi_t$ for each group i . In order to keep the full factor loadings λ , the latent factor ψ and the full model identifiable, some restrictions are added to the model. Details will be available in an upcoming paper. This component should be treated as experimental feature.

Usage

```
Ifactor(
  responses = NULL,
  nonzero_lambda = TRUE,
  correlated = TRUE,
  noncentered_psi = FALSE
)
```

Arguments

<code>responses</code>	[character()] Names of the responses that the factor should affect. Default is all responses defined with <code>obs</code> except categorical responses, which do not (yet) support the factor component.
<code>nonzero_lambda</code>	[logical()] If TRUE (the default), assumes that the mean of factor loadings is nonzero or not. Should be a logical vector matching the length of <code>responses</code> or a single logical value in case <code>responses</code> is NULL. See details.
<code>correlated</code>	[logical()] If TRUE (the default), the latent factors are assumed to be correlated between channels.
<code>noncentered_psi</code>	[logical(1)] If TRUE, uses a noncentered parametrization for spline coefficients of all the factors. The number of knots is based <code>splines()</code> call.

Value

An object of class `latent_factor`.

See Also

Model formula construction `dynamiteformula()`, `dynamite()`, `lags()`, `random_spec()`, `splines()`

Examples

```
# three channel model with common factor affecting for responses x and y
obs(y ~ 1, family = "gaussian") +
  obs(x ~ 1, family = "poisson") +
  obs(z ~ 1, family = "gaussian") +
  lfactor(
    responses = c("y", "x"), nonzero_lambda = c(TRUE, FALSE),
    correlated = TRUE, noncentered_psi = FALSE
  )
```

lfo

Approximate Leave-Future-Out (LFO) Cross-validation

Description

Estimates the leave-future-out (LFO) information criterion for dynamic models using Pareto smoothed importance sampling.

Usage

```
lfo(x, L, verbose = TRUE, k_threshold = 0.7, ...)
```

Arguments

x	[dynamitefit] The model fit object.
L	[integer(1)] Positive integer defining how many time points should be used for the initial fit.
verbose	[logical(1)] If TRUE (default), print the progress of the LFO computations to the console.
k_threshold	[numeric(1)] Threshold for the Pareto k estimate triggering refit. Default is 0.7.
...	Additional arguments passed to <code>rstan::sampling()</code> or <code>cmdstanr::sample()</code> , such as <code>chains</code> and <code>cores</code> (<code>parallel_chains</code> in <code>cmdstanr</code>).

Details

For multichannel models, the log-likelihoods of all channels are combined. For models with groups, expected log predictive densities (ELPDs) are computed independently for each group, but the re-estimation of the model is triggered if pareto k values of any group exceeds the threshold.

Value

An lfo object which is a list with the following components:

- `ELPD`
Expected log predictive density estimate.
- `ELPD_SE`
Standard error of ELPD. This is a crude approximation which does not take into account potential serial correlations.
- `pareto_k`
Pareto k values.
- `refits`
Time points where model was re-estimated.
- `L`
L value used in the LFO estimation.
- `k_threshold`
Threshold used in the LFO estimation.

References

Paul-Christian Bürkner, Jonah Gabry, and Aki Vehtari (2020). Approximate leave-future-out cross-validation for Bayesian time series models, *Journal of Statistical Computation and Simulation*, 90:14, 2499-2523.

See Also

Model diagnostics `loo.dynamitefit()`, `mcmc_diagnostics()`

Examples

```
# Please update your rstan and StanHeaders installation before running
# on Windows
if (!identical(.Platform$OS.type, "windows")) {
  # this gives warnings due to the small number of iterations
  out <- suppressWarnings(lfo(gaussian_example_fit, L = 20))
  out$ELPD
  out$ELPD_SE
}
```

loo.dynamitefit	<i>Approximate Leave-One-Out (LOO) Cross-validation</i>
-----------------	---

Description

Estimates the leave-one-out (LOO) information criterion for dynamite models using Pareto smoothed importance sampling with the loo package.

Usage

```
## S3 method for class 'dynamitefit'
loo(x, separate_channels = FALSE, ...)
```

Arguments

x	[dynamitefit] The model fit object.
separate_channels	[logical(1)] If TRUE, computes LOO separately for each channel. This can be useful in diagnosing where the model fails. Default is FALSE, in which case the likelihoods of different channels are combined, i.e., all channels of are left out.
...	Ignored.

Value

An output from `loo::loo()` or a list of such outputs (if `separate_channels` was TRUE).

References

Aki Vehtari, Andrew Gelman, and Johah Gabry (2017). Practical Bayesian model evaluation using leave-one-out cross-validation and WAIC. *Statistics and Computing*. 27(5), 1413–1432.

See Also

Model diagnostics `lfo()`, `mcmc_diagnostics()`

Examples

```
# Please update your rstan and StanHeaders installation before running
# on Windows
if (!identical(.Platform$OS.type, "windows")) {
  # this gives warnings due to the small number of iterations
  suppressWarnings(loo(gaussian_example_fit))
  suppressWarnings(loo(gaussian_example_fit, separate_channels = TRUE))
}
```

mcmc_diagnostics *Diagnostic Values of a Dynamite Model*

Description

Prints HMC diagnostics, and lists parameters with smallest effective sample sizes and largest Rhat values. See [rstan::check_hmc_diagnostics\(\)](#) and [posterior::default_convergence_measures\(\)](#) for details.

Usage

```
mcmc_diagnostics(x, n)

## S3 method for class 'dynamitefit'
mcmc_diagnostics(x, n = 3L)
```

Arguments

x	[dynamitefit] The model fit object.
n	[integer(1)] How many rows to print in parameter-specific convergence measures. The default is 3. Should be a positive (unrestricted) integer.

Value

Returns x (invisibly).

See Also

Model diagnostics [lfo\(\)](#), [loo.dynamitefit\(\)](#)

Examples

```
mcmc_diagnostics(gaussian_example_fit)
```

multichannel_example *Simulated Multivariate Panel Data*

Description

A simulated multichannel data containing multiple individuals with multiple response variables of different distributions.

Usage

```
multichannel_example
```

Format

A data frame with 3000 rows and 5 variables:

id Variable defining individuals (1 to 50).

time Variable defining the time point of the measurement (1 to 20).

g Response variable following gaussian distribution.

p Response variable following Poisson distribution.

b Response variable following Bernoulli distribution.

Source

The data was generated according to a script in https://github.com/ropensci/dynamite/blob/main/data-raw/multichannel_example.R

See Also

Example models [categorical_example_fit](#), [categorical_example](#), [gaussian_example_fit](#), [gaussian_example](#), [gaussian_simulation_fit](#), [multichannel_example_fit](#)

multichannel_example_fit

Model Fit for the Simulated Multivariate Panel Data

Description

A dynamitefit object obtained by running dynamite on the multichannel_example dataset as

```
set.seed(1)
library(dynamite)
f <- obs(g ~ lag(g) + lag(logp), family = "gaussian") +
  obs(p ~ lag(g) + lag(logp) + lag(b), family = "poisson") +
  obs(b ~ lag(b) * lag(logp) + lag(b) * lag(g), family = "bernoulli") +
  aux(numeric(logp) ~ log(p + 1))
multichannel_example_fit <- dynamite(
  f,
  data = multichannel_example,
  time = "time",
  group = "id",
  chains = 1,
  cores = 1,
  iter = 2000,
  warmup = 1000,
  init = 0,
  refresh = 0,
  thin = 5,
  save_warmup = FALSE
)
```

Note the small number of samples due to size restrictions on CRAN.

Usage

```
multichannel_example_fit
```

Format

A dynamitefit object.

Source

Script in https://github.com/ropensci/dynamite/blob/main/data-raw/multichannel_example_fit.R

See Also

Example models [categorical_example_fit](#), [categorical_example](#), [gaussian_example_fit](#), [gaussian_example](#), [gaussian_simulation_fit](#), [multichannel_example](#)

ndraws.dynamitefit *Return the Number of Posterior Draws of a dynamitefit Object*

Description

Return the Number of Posterior Draws of a dynamitefit Object

Usage

```
## S3 method for class 'dynamitefit'  
ndraws(x)
```

Arguments

x [dynamitefit]
The model fit object.

Value

Number of posterior draws as a single integer value.

See Also

Model outputs [as.data.frame.dynamitefit\(\)](#), [as.data.table.dynamitefit\(\)](#), [as_draws_df.dynamitefit\(\)](#), [coef.dynamitefit\(\)](#), [confint.dynamitefit\(\)](#), [dynamite\(\)](#), [get_code\(\)](#), [get_data\(\)](#), [get_parameter_dims\(\)](#), [get_parameter_names\(\)](#), [get_parameter_types\(\)](#), [nobs.dynamitefit\(\)](#)

Examples

```
ndraws(gaussian_example_fit)
```

nobs.dynamitefit *Extract the Number of Observations Used to Fit a Dynamite Model*

Description

Extract the Number of Observations Used to Fit a Dynamite Model

Usage

```
## S3 method for class 'dynamitefit'  
nobs(object, ...)
```

Arguments

object	[dynamitefit] The model fit object.
...	Not used.

Value

Total number of non-missing observations as an integer.

See Also

Model outputs `as.data.frame.dynamitefit()`, `as.data.table.dynamitefit()`, `as_draws_df.dynamitefit()`, `coef.dynamitefit()`, `confint.dynamitefit()`, `dynamite()`, `get_code()`, `get_data()`, `get_parameter_dims()`, `get_parameter_names()`, `get_parameter_types()`, `ndraws.dynamitefit()`

Examples

```
nobs(gaussian_example_fit)
```

plot.dynamitefit	<i>Traceplots and Density Plots for a dynamitefit Object</i>
------------------	--

Description

Produces the traceplots and the density plots of the model parameters.

Usage

```
## S3 method for class 'dynamitefit'
plot(x, parameters = NULL, type = NULL, responses = NULL, ...)
```

Arguments

x	[dynamitefit] The model fit object.
parameters	[character()]\ Parameter name(s) for which the plots should be drawn. Possible options can be found with the function <code>get_parameter_names()</code> . The default is all parameters of a specific type for all responses, which can lead to too crowded a plot.
type	[character(1)] Type of the parameter for which the plots should be drawn. Possible options can be found with the function <code>get_parameter_types()</code> . Ignored if the argument parameters is supplied.
responses	[character()] Response(s) for which the plots should be drawn. Possible options are <code>unique(x\$priors\$response)</code> . Default is all responses. Ignored if the argument parameters is supplied.
...	Not used..

Value

A ggplot object.

See Also

Drawing plots `plot_betas()`, `plot_deltas()`, `plot_lambdas()`, `plot_nus()`, `plot_psis()`

Examples

```
plot(gaussian_example_fit, type = "beta")
```

plot.lfo

Diagnostic Plot for Pareto k Values from LFO

Description

Plots Pareto k values per each time point (with one point per group), together with a horizontal line representing the used threshold.

Usage

```
## S3 method for class 'lfo'
plot(x, ...)
```

Arguments

x	[lfo] Output from the lfo function.
...	Ignored.

Value

A ggplot object.

Examples

```
# Please update your rstan and StanHeaders installation before running
# on Windows
if (!identical(.Platform$OS.type, "windows")) {
  # This gives warnings due to the small number of iterations
  plot(suppressWarnings(lfo(gaussian_example_fit, L = 20)))
}
```

plot_betas

Plot Time-invariant Regression Coefficients of a Dynamite Model

Description

Plot Time-invariant Regression Coefficients of a Dynamite Model

Usage

```
plot_betas(
  x,
  parameters = NULL,
  responses = NULL,
  level = 0.05,
  include_alpha = TRUE
)
```

Arguments

x	[dynamitefit] The model fit object
parameters	[character()]\ Parameter name(s) for which the plots should be drawn. Possible options can be found with function <code>get_parameter_names(types = "beta")</code> .
responses	[character()] Response(s) for which the coefficients should be drawn. Possible options are elements of <code>unique(x\$priors\$response)</code> , and the default is this whole vector.
level	[numeric(1)] Level for posterior intervals. Default is 0.05, leading to 90% intervals.
include_alpha	[logical(1)] If TRUE (default), plots also the time-invariant alphas if such parameters exists in the model.

Value

A ggplot object.

See Also

Drawing plots `plot.dynamitefit()`, `plot_deltas()`, `plot_lambdas()`, `plot_nus()`, `plot_psis()`

Examples

```
plot_betas(gaussian_example_fit, level = 0.1)
```

plot_deltas

*Plot Time-varying Regression Coefficients of a Dynamite Model***Description**

Plot Time-varying Regression Coefficients of a Dynamite Model

Usage

```
plot_deltas(
  x,
  parameters = NULL,
  responses = NULL,
  level = 0.05,
  alpha = 0.5,
  scales = c("fixed", "free"),
  include_alpha = TRUE
)
```

Arguments

x	[dynamitefit] The model fit object
parameters	[character()]\ Parameter name(s) for which the plots should be drawn. Possible options can be found with function <code>get_parameter_names(types = "delta")</code> .
responses	[character()] Response(s) for which the coefficients should be drawn. Possible options are elements of <code>unique(x\$priors\$response)</code> , and the default is this whole vector.
level	[numeric(1)] Level for posterior intervals. Default is 0.05, leading to 90% intervals.
alpha	[numeric(1)] Opacity level for <code>geom_ribbon</code> . Default is 0.5.
scales	[character(1)] Should y-axis of the panels be "fixed" (the default) or "free"? See <code>ggplot2::facet_wrap()</code> .
include_alpha	[logical(1)] If TRUE (default), plots also the time-varying alphas if such parameters exists in the model.

Value

A ggplot object.

See AlsoDrawing plots `plot.dynamitefit()`, `plot_betas()`, `plot_lambdas()`, `plot_nus()`, `plot_psis()`

Examples

```
plot_deltas(gaussian_example_fit, level = 0.025, scales = "free") +
  ggplot2::theme_minimal()
```

 plot_lambdas

Plot Factor Loadings of a Dynamite Model

Description

Plot Factor Loadings of a Dynamite Model

Usage

```
plot_lambdas(x, responses = NULL, level = 0.05)
```

Arguments

x	[dynamitefit] The model fit object
responses	[character()] Response(s) for which the coefficients should be drawn. Possible options are elements of <code>unique(x\$priors\$response)</code> , and the default is this whole vector.
level	[numeric(1)] Level for posterior intervals. Default is 0.05, leading to 90% intervals.

Value

A ggplot object.

See Also

Drawing plots [plot.dynamitefit\(\)](#), [plot.betas\(\)](#), [plot.deltas\(\)](#), [plot.nus\(\)](#), [plot.psis\(\)](#)

 plot_nus

Plot Random effects of a Dynamite Model

Description

Note that as this function tries to draw a plot containing effects of all groups, the plot will become messy with large number of groups.

Usage

```
plot_nus(x, parameters = NULL, responses = NULL, level = 0.05, groups = NULL)
```

Arguments

x	[dynamitefit] The model fit object
parameters	[character()]\ Parameter name(s) for which the plots should be drawn. Possible options can be found with function <code>get_parameter_names(types = "delta")</code> .
responses	[character()] Response(s) for which the coefficients should be drawn. Possible options are elements of <code>unique(x\$priors\$response)</code> , and the default is this whole vector.
level	[numeric(1)] Level for posterior intervals. Default is 0.05, leading to 90% intervals.
groups	Group name(s) for which the plots should be drawn. Default is all groups.

Value

A ggplot object.

See Also

Drawing plots `plot.dynamitefit()`, `plot_betas()`, `plot_deltas()`, `plot_lambdas()`, `plot_psis()`

Examples

```
plot_nus(gaussian_example_fit)
```

plot_psis

Plot Latent Factors of a Dynamite Model

Description

Plot Latent Factors of a Dynamite Model

Usage

```
plot_psis(
  x,
  responses = NULL,
  level = 0.05,
  alpha = 0.5,
  scales = c("fixed", "free")
)
```

Arguments

x	[dynamitefit] The model fit object
responses	[character()] Response(s) for which the coefficients should be drawn. Possible options are elements of <code>unique(x\$priors\$response)</code> , and the default is this whole vector.
level	[numeric(1)] Level for posterior intervals. Default is 0.05, leading to 90% intervals.
alpha	[numeric(1)] Opacity level for <code>geom_ribbon</code> . Default is 0.5.
scales	[character(1)] Should y-axis of the panels be "fixed" (the default) or "free"? See ggplot2::facet_wrap() .

Value

A ggplot object.

See Also

Drawing plots [plot.dynamitefit\(\)](#), [plot_betas\(\)](#), [plot_deltas\(\)](#), [plot_lambdas\(\)](#), [plot_nus\(\)](#)

predict.dynamitefit *Predict Method for a Dynamite Model*

Description

Obtain counterfactual predictions for a dynamitefit object.

Usage

```
## S3 method for class 'dynamitefit'
predict(
  object,
  newdata = NULL,
  type = c("response", "mean", "link"),
  funs = list(),
  impute = c("none", "locf", "nocb"),
  new_levels = c("none", "bootstrap", "gaussian", "original"),
  global_fixed = FALSE,
  n_draws = NULL,
  expand = TRUE,
  df = TRUE,
  ...
)
```


Arguments

object	[dynamitefit] The model fit object.
newdata	[data.frame] Data used in predictions. Predictions are computed for missing (NA) values in the response variable columns, and non-missing values are assumed fixed. If NULL (default), the data used in model estimation is used for predictions as well, after all values in the response variable columns after the first fixed time point are converted to NA values. Missing values in predictor columns can be imputed (argument impute). There should be no new time points that were not present in the data that were used to fit the model. New group levels can be included, but if the model contains random effects, an option for the random effects for the new levels must be chosen (argument new_levels). If the grouping variable of the original data is missing, it is assumed that all observations in newdata belong to the first group in the original data. New group levels are not allowed for models using latent factors.
type	[character(1)] Type of prediction, "response" (default), "mean", or "link".
funcs	[list()] A named list whose names should correspond to the response variables of the model. Each element of funcs should be a named list of functions that will be applied to the corresponding predicted type of the channel over the individuals for each combination of the posterior draws and time points. In other words, the resulting predictions will be averages over the individuals. The functions should take the corresponding type variable values as their only argument. If funcs is empty, the full individual level values are returned instead. Note that this argument can only be used if there are multiple individuals (i.e., group was not NULL in the dynamite call).
impute	[character(1)] Which imputation scheme to use for missing exogenous predictor values. Currently supported options are no imputation: "none" (default), last observation carried forward: "locf", and next observation carried backward: "nocb".
new_levels	[character(1)] Defines if and how to sample the random effects for observations whose group level was not present in the original data. The options are: <ul style="list-style-type: none"> • "none" (the default) which will signal an error if new levels are encountered. • "bootstrap" which will randomly draw from the posterior samples of the random effects across all original levels. • "gaussian" which will randomly draw from a gaussian distribution using the posterior samples of the random effects standard deviation (and correlation matrix if applicable). • "original" which will randomly match each new level to one of the original levels. The posterior samples of the random effects of the matched levels will then be used for the new levels.

This argument is ignored if the model does not contain random effects.

global_fixed	[logical(1)] If FALSE (the default), the first non-fixed time point is counted from the the first non-NA observation for each group member separately. Otherwise, the first non-fixed time point is counted from the first time point globally. If there are no groups, then the options are equivalent.
n_draws	[integer(1)] Number of posterior samples to use, default is NULL which uses all samples.
expand	[logical(1)] If TRUE (the default), the output is a single data.frame containing the original newdata and the predicted values. Otherwise, a list is returned with two components, simulated and observed, where the first contains only the predicted values, and the second contains the original newdata. Setting expand to FALSE can help conserve memory because newdata is not replicated n_draws times in the output. This argument is ignored if funs are provided.
df	[logical(1)] If TRUE (default) the output consists of data.frame objects, and data.table objects otherwise.
...	Ignored.

Details

Note that forecasting (i.e., predictions for time indices beyond the last time index in the original data) is not supported by the **dynamite** package. However, such predictions can be obtained by augmenting the original data with NA values before model estimation.

Value

A data.frame containing the predicted values or a list of two data.frames. See the expand argument for details. Note that the .draw column is not the same as .draw from as.data.frame and as_draws methods as predict uses permuted samples. A mapping between these variables can be done using information in object\$stanfit@sim\$permutation.

See Also

Obtaining predictions [fitted.dynamitefit\(\)](#)

Examples

```
out <- predict(gaussian_example_fit, type = "response", n_draws = 2L)
head(out)

# using summary functions
sumr <- predict(multichannel_example_fit, type = "mean",
  funs = list(g = list(m = mean, s = sd), b = list(sum = sum)),
  n_draws = 2L)
head(sumr$simulated)

# Please update your rstan and StanHeaders installation before running
# on Windows
```

```

if (!identical(.Platform$OS.type, "windows")) {
  # Simulate from the prior predictive distribution

  f <- obs(y ~ lag(y) + varying(~ -1 + x), "gaussian") +
    splines(df = 10, noncentered = TRUE)

  # Create data with missing observations
  # Note that due to the lagged term in the model,
  # we need to fix the first time point
  d <- data.frame(y = c(0, rep(NA, 49)), x = rnorm(50), time = 1:50)

  # Suppress warnings due to the lack of data
  suppressWarnings(
    priors <- get_priors(f, data = d, time = "time")
  )

  # Modify default priors which can produce exploding behavior when used
  # without data
  priors$prior <- c(
    "normal(0, 1)",
    "normal(0.6, 0.1)",
    "normal(-0.2, 0.5)",
    "normal(0.2, 0.1)",
    "normal(0.5, 0.1)"
  )

  # Samples from the prior conditional on the first time point and x
  fit <- dynamite(
    dformula = f,
    data = d,
    time = "time",
    verbose = FALSE,
    priors = priors,
    chains = 1
  )

  # Simulate new data
  pp <- predict(fit)

  ggplot2::ggplot(pp, ggplot2::aes(time, y_new, group = .draw)) +
    ggplot2::geom_line(alpha = 0.1) +
    ggplot2::theme_bw()
}

```

print.lfo

Print the results from the LFO

Description

Prints the summary of the leave-future-out cross-validation.

Usage

```
## S3 method for class 'lfo'
print(x, ...)
```

Arguments

x	x [lfo] Output of the lfo method.
...	Ignored.

Value

Returns x invisibly.

Examples

```
# Please update your rstan and StanHeaders installation before running
# on Windows
if (!identical(.Platform$OS.type, "windows")) {
  # This gives warnings due to the small number of iterations
  suppressWarnings(lfo(gaussian_example_fit, L = 20))
}
```

random_spec	<i>Additional Specifications for the Group-level Random Effects of the DMPM</i>
-------------	---

Description

This function can be used as part of [dynamiteformula\(\)](#) to define whether the group-level random effects should be modeled as correlated or not.

Usage

```
random_spec(correlated = TRUE, noncentered = TRUE)
```

Arguments

correlated	[logical(1)] If TRUE (the default), correlations of random effects are modeled as multivariate normal.
noncentered	[logical(1)] If TRUE (the default), use a noncentered parameterization for random effects. Try changing this if you encounter divergences or other problems in sampling.

Details

With a large number of time points random intercepts can become challenging sample with default priors. This is because with large group sizes the group-level intercepts tend to behave similarly to fixed group-factor variable so the model becomes overparameterized given these and the common intercept term. Another potential cause for sampling problems is relatively large variation in the intercepts (large σ_{ν}) compared to the sampling variation (σ) in the Gaussian case.

Value

An object of class `random_spec`.

See Also

Model formula construction `dynamiteformula()`, `dynamite()`, `lags()`, `lfactor()`, `splines()`

Examples

```
# two channel model with correlated random effects for responses x and y
obs(y ~ 1 + random(~1), family = "gaussian") +
  obs(x ~ 1 + random(~1 + z), family = "poisson") +
  random_spec(correlated = TRUE)
```

splines	<i>Define the B-splines Used for the Time-varying Coefficients of the Model.</i>
---------	--

Description

This function can be used as part of `dynamiteformula()` to define the splines used for the time-varying coefficients δ .

Usage

```
splines(
  df = NULL,
  degree = 3L,
  lb_tau = 0,
  noncentered = FALSE,
  override = FALSE
)
```

Arguments

df	[integer(1)] Degrees of freedom, i.e., the total number of spline coefficients. See splines::bs() . Note that the knots are always defined as an equidistant sequence on the interval starting from the first non-fixed time point to the last time point in the data. See dynamiteformula() for more information on fixed time points. Should be an (unrestricted) positive integer.
degree	[integer(1)] See splines::bs() . Should be an (unrestricted) positive integer.
lb_tau	[numeric()] Hard constraint(s) on the lower bound of the standard deviation parameters τ of the random walk priors. Can be useful in avoiding divergences in some cases. See also the noncentered argument. Can be a single positive value, or vector defining the lower bound separately for each channel, even for channels without varying effects. The ordering is based on the order of channel definitions in the dynamiteformula object.
noncentered	[logical()] If TRUE, use a noncentered parameterization for the spline coefficients. Default is FALSE. Try changing this if you encounter divergences or other problems in sampling for example when simulating from prior predictive distribution. Can be a single logical value, or vector of logical values, defining the parameterization separately for each channel, even for channels without varying effects.
override	[logical(1)] If FALSE (the default), an existing definition for the splines will not be overridden by another call to splines() . If TRUE, any existing definitions will be replaced.

Value

An object of class `splines`.

See Also

Model formula construction [dynamiteformula\(\)](#), [dynamite\(\)](#), [lags\(\)](#), [lfactor\(\)](#), [random_spec\(\)](#)

Examples

```
# Two channel model with varying effects, with explicit lower bounds for the
# random walk prior standard deviations, with noncentered parameterization
# for the first channel and centered for the second channel.
obs(y ~ 1, family = "gaussian") + obs(x ~ 1, family = "gaussian") +
  lags(type = "varying") +
  splines(
    df = 20, degree = 3, lb_tau = c(0, 0.1),
    noncentered = c(TRUE, FALSE)
  )
```

 update.dynamitefit *Update a Dynamite Model*

Description

Note that using a different backend for the original model fit and when updating can lead to an error due to different naming in cmdstanr and rstan sampling arguments.

Usage

```
## S3 method for class 'dynamitefit'
update(
  object,
  dformula = NULL,
  data = NULL,
  priors = NULL,
  recompile = NULL,
  ...
)
```

Arguments

object	[dynamitefit] The model fit object.
dformula	[dynamiteformula] Updated model formula. By default the original formula is used.
data	[data.frame, tibble::tibble, or data.table::data.table] Data for the updated model. By default original data is used.
priors	[data.frame] Updated priors. By default the priors of the original model are used.
recompile	[logical(1)] Should the model be recompiled? If NULL (default), tries to avoid recompilation. Recompilation is forced when the model formula or the priors are changed, or if the new data contains missing values in a channel which did not contain missing values in the original data. Recompilation is also forced in case the backend previous or new backend is cmdstanr.
...	Additional parameters to dynamite.

Value

An updated dynamitefit object.

See Also

Model fitting [dynamite\(\)](#), [get_priors\(\)](#)

Examples

```
## Not run:  
# re-estimate the example fit without thinning:  
# As the model is compiled on Windows, this will fail on other platforms  
if (identical(.Platform$OS.type, "windows")) {  
  fit <- update(gaussian_example_fit, thin = 1)  
}  
  
## End(Not run)
```


Index

- * **datasets**
 - categorical_example, 10
 - categorical_example_fit, 11
 - gaussian_example, 23
 - gaussian_example_fit, 24
 - gaussian_simulation_fit, 25
 - multichannel_example, 39
 - multichannel_example_fit, 39
- * **diagnostics**
 - lfo, 35
 - loo.dynamitefit, 37
 - mcmc_diagnostics, 38
- * **examples**
 - categorical_example, 10
 - categorical_example_fit, 11
 - gaussian_example, 23
 - gaussian_example_fit, 24
 - gaussian_simulation_fit, 25
 - multichannel_example, 39
 - multichannel_example_fit, 39
- * **fitting**
 - dynamite, 14
 - get_priors, 31
 - update.dynamitefit, 55
- * **formulas**
 - dynamite, 14
 - dynamiteformula, 18
 - lags, 33
 - lfactor, 34
 - random_spec, 52
 - splines, 53
- * **output**
 - as.data.frame.dynamitefit, 3
 - as.data.table.dynamitefit, 7
 - as_draws_df.dynamitefit, 8
 - coef.dynamitefit, 12
 - confint.dynamitefit, 13
 - dynamite, 14
 - get_code, 26
 - get_data, 27
 - get_parameter_dims, 28
 - get_parameter_names, 29
 - get_parameter_types, 30
 - ndraws.dynamitefit, 41
 - nobs.dynamitefit, 41
- * **plotting**
 - plot.dynamitefit, 42
 - plot_betas, 44
 - plot_deltas, 45
 - plot_lambdas, 46
 - plot_nus, 46
 - plot_psis, 47
- * **prediction**
 - fitted.dynamitefit, 21
 - predict.dynamitefit, 48
- + .dynamiteformula (dynamiteformula), 18
- as.data.frame(), 8
- as.data.frame.dynamitefit, 3, 8, 9, 13, 14, 17, 27–31, 41, 42
- as.data.frame.dynamitefit(), 7, 9, 14, 16, 30
- as.data.table
 - (as.data.table.dynamitefit), 7
- as.data.table.dynamitefit, 6, 7, 9, 13, 14, 17, 27–31, 41, 42
- as_draws (as_draws_df.dynamitefit), 8
- as_draws(), 6
- as_draws_df (as_draws_df.dynamitefit), 8
- as_draws_df.dynamitefit, 6, 8, 8, 13, 14, 17, 27–31, 41, 42
- aux (dynamiteformula), 18
- categorical_example, 10, 11, 24, 25, 39, 40
- categorical_example_fit, 10, 11, 24, 25, 39, 40
- cmdstanr::cmdstan_model(), 16
- cmdstanr::sample(), 16, 35

- coef.dynamitefit, [6](#), [8](#), [9](#), [12](#), [14](#), [17](#), [27–31](#), [41](#), [42](#)
- confint.dynamitefit, [6](#), [8](#), [9](#), [13](#), [13](#), [17](#), [27–31](#), [41](#), [42](#)
- dynamite, [6](#), [8](#), [9](#), [13](#), [14](#), [14](#), [20](#), [27–34](#), [41](#), [42](#), [53–55](#)
- dynamite(), [3](#), [8](#), [26](#), [27](#), [29](#), [32](#)
- dynamite-package, [3](#)
- dynamiteformula, [17](#), [18](#), [33](#), [34](#), [53](#), [54](#)
- dynamiteformula(), [3](#), [14](#), [15](#), [26](#), [27](#), [29](#), [32–34](#), [52–54](#)
- fitted.dynamitefit, [21](#), [50](#)
- formula.dynamitefit (dynamite), [14](#)
- gaussian_example, [10](#), [11](#), [23](#), [25](#), [39](#), [40](#)
- gaussian_example_fit, [10](#), [11](#), [24](#), [24](#), [25](#), [39](#), [40](#)
- gaussian_simulation_fit, [10](#), [11](#), [24](#), [25](#), [25](#), [39](#), [40](#)
- get_code, [6](#), [8](#), [9](#), [13](#), [14](#), [17](#), [26](#), [28–31](#), [41](#), [42](#)
- get_data, [6](#), [8](#), [9](#), [13](#), [14](#), [17](#), [27](#), [27](#), [29–31](#), [41](#), [42](#)
- get_parameter_dims, [6](#), [8](#), [9](#), [13](#), [14](#), [17](#), [27](#), [28](#), [28](#), [30](#), [31](#), [41](#), [42](#)
- get_parameter_names, [6](#), [8](#), [9](#), [13](#), [14](#), [17](#), [27–29](#), [29](#), [31](#), [41](#), [42](#)
- get_parameter_names(), [9](#), [28](#), [42](#)
- get_parameter_types, [6](#), [8](#), [9](#), [13](#), [14](#), [17](#), [27–30](#), [30](#), [41](#), [42](#)
- get_parameter_types(), [4](#), [8](#), [9](#), [28](#), [30](#), [42](#)
- get_priors, [17](#), [31](#), [55](#)
- get_priors(), [15](#)
- ggplot2::facet_wrap(), [45](#), [48](#)
- lags, [17](#), [20](#), [33](#), [34](#), [53](#), [54](#)
- lags(), [20](#)
- lfactor, [17](#), [20](#), [33](#), [34](#), [53](#), [54](#)
- lfo, [35](#), [37](#), [38](#)
- loo (loo.dynamitefit), [37](#)
- loo.dynamitefit, [36](#), [37](#), [38](#)
- loo::loo(), [37](#)
- mcmc_diagnostics, [36](#), [37](#), [38](#)
- multichannel_example, [10](#), [11](#), [24](#), [25](#), [39](#), [40](#)
- multichannel_example_fit, [10](#), [11](#), [24](#), [25](#), [39](#), [39](#)
- ndraws (ndraws.dynamitefit), [41](#)
- ndraws.dynamitefit, [6](#), [8](#), [9](#), [13](#), [14](#), [17](#), [27–31](#), [41](#), [42](#)
- nobs.dynamitefit, [6](#), [8](#), [9](#), [13](#), [14](#), [17](#), [27–31](#), [41](#), [41](#)
- obs (dynamiteformula), [18](#)
- plot.dynamitefit, [42](#), [44–48](#)
- plot.lfo, [43](#)
- plot_betas, [43](#), [44](#), [45–48](#)
- plot_deltas, [43](#), [44](#), [45](#), [46–48](#)
- plot_lambdas, [43–45](#), [46](#), [47](#), [48](#)
- plot_nus, [43–46](#), [46](#), [48](#)
- plot_psis, [43–47](#), [47](#)
- posterior::default_convergence_measures(), [38](#)
- predict.dynamitefit, [22](#), [48](#)
- predict.dynamitefit(), [21](#)
- print.dynamitefit (dynamite), [14](#)
- print.dynamiteformula (dynamiteformula), [18](#)
- print.lfo, [51](#)
- random_spec, [17](#), [20](#), [33](#), [34](#), [52](#), [54](#)
- random_spec(), [20](#)
- rstan::check_hmc_diagnostics(), [38](#)
- rstan::rstan_options(), [16](#)
- rstan::sampling(), [16](#), [35](#)
- splines, [17](#), [20](#), [33](#), [34](#), [53](#), [53](#)
- splines::bs(), [54](#)
- stats::model.matrix.lm(), [15](#), [26](#), [27](#), [29](#), [32](#)
- summary.dynamitefit (dynamite), [14](#)
- tibble::formatting, [16](#)
- update.dynamitefit, [17](#), [32](#), [55](#)