

# Package ‘ggstatsplot’

April 14, 2023

**Type** Package

**Title** 'ggplot2' Based Plots with Statistical Details

**Version** 0.11.1

**Maintainer** Indrajeet Patil <patilindrajeet.science@gmail.com>

**Description** Extension of 'ggplot2', 'ggstatsplot' creates graphics with details from statistical tests included in the plots themselves. It provides an easier syntax to generate information-rich plots for statistical analysis of continuous (violin plots, scatterplots, histograms, dot plots, dot-and-whisker plots) or categorical (pie and bar charts) data. Currently, it supports the most common types of statistical approaches and tests: parametric, nonparametric, robust, and Bayesian versions of t-test/ANOVA, correlation analyses, contingency table analysis, meta-analysis, and regression analyses. References: Patil (2021) <doi:10.21105/joss.03236>.

**License** GPL-3 | file LICENSE

**URL** <https://indrajeetpatil.github.io/ggstatsplot/>,  
<https://github.com/IndrajeetPatil/ggstatsplot>

**BugReports** <https://github.com/IndrajeetPatil/ggstatsplot/issues>

**Depends** R (>= 4.1.0)

**Imports** correlation (>= 0.8.4), datawizard (>= 0.7.1), dplyr (>= 1.1.1), ggplot2 (>= 3.4.2), ggrepel (>= 0.9.3), ggsignif, glue, insight (>= 0.19.1), paletteer, parameters (>= 0.20.3), patchwork, performance (>= 0.10.2), purrr (>= 1.0.1), rlang, stats, statsExpressions (>= 1.5.0), tidyr, utils

**Suggests** afex, BayesFactor (>= 0.9.12-4.4), gapminder, ggcorrplot (>= 0.1.4), ggside (>= 0.2.2), knitr, lme4, MASS, metaBMA, metafor, metaplus, PMCMRplus, psych, rmarkdown, survival, testthat (>= 3.1.7), tibble, vdiffR (>= 1.0.5), WRS2

**VignetteBuilder** knitr

**Encoding** UTF-8

**Language** en-US

**LazyData** true

**RoxygenNote** 7.2.3.9000

**Config/testthat/edition** 3

**Config/testthat/parallel** true

**NeedsCompilation** no

**Author** Indrajeet Patil [cre, aut, cph]

(<<https://orcid.org/0000-0003-1995-6531>>, @patilindrajeets),

Chuck Powell [ctb] (<<https://orcid.org/0000-0002-3606-2188>>)

**Repository** CRAN

**Date/Publication** 2023-04-14 07:50:03 UTC

## R topics documented:

bugs_long . . . . .	3
bugs_wide . . . . .	4
combine_plots . . . . .	5
extract_stats . . . . .	6
ggbarstats . . . . .	7
ggbetweenstats . . . . .	13
ggcoefstats . . . . .	20
ggcorrmat . . . . .	24
ggdotplotstats . . . . .	27
gghistostats . . . . .	31
ggpiestats . . . . .	35
ggscatterstats . . . . .	39
ggwithinstats . . . . .	43
grouped_ggbarstats . . . . .	51
grouped_ggbetweenstats . . . . .	54
grouped_ggcorrmat . . . . .	58
grouped_ggdotplotstats . . . . .	61
grouped_gghistostats . . . . .	63
grouped_ggpiestats . . . . .	66
grouped_ggscatterstats . . . . .	69
grouped_ggwithinstats . . . . .	72
iris_long . . . . .	76
movies_long . . . . .	77
theme_ggstatsplot . . . . .	78
Titanic_full . . . . .	78

**Index** **80**

---

`bugs_long`*Tidy version of the "Bugs" dataset.*

---

**Description**

Tidy version of the "Bugs" dataset.

**Usage**

```
bugs_long
```

**Format**

A data frame with 372 rows and 6 variables

- `subject`. Dummy identity number for each participant.
- `gender`. Participant's gender (Female, Male).
- `region`. Region of the world the participant was from.
- `education`. Level of education.
- `condition`. Condition of the experiment the participant gave rating for (**LDLF**: low frighteningness and low disgustingness; **LFHD**: low frighteningness and high disgustingness; **HFHD**: high frighteningness and low disgustingness; **HFHD**: high frighteningness and high disgustingness).
- `desire`. The desire to kill an arthropod was indicated on a scale from 0 to 10.

**Details**

This data set, "Bugs", provides the extent to which men and women want to kill arthropods that vary in frighteningness (low, high) and disgustingness (low, high). Each participant rates their attitudes towards all arthropods. Subset of the data reported by Ryan et al. (2013).

**Source**

<https://www.sciencedirect.com/science/article/pii/S0747563213000277>

**Examples**

```
dim(bugs_long)
head(bugs_long)
dplyr::glimpse(bugs_long)
```

---

bugs\_wide

*Wide-format version of the "Bugs" dataset.*

---

## Description

Wide-format version of the "Bugs" dataset.

## Usage

```
bugs_wide
```

## Format

A data frame with 93 rows and 6 variables

- `subject`. Dummy identity number for each participant.
- `gender`. Participant's gender (Female, Male).
- `region`. Region of the world the participant was from.
- `education`. Level of education.
- `ldlf,ldhf,hdlf,hdhf`. The desire to kill an arthropod was indicated on a scale from 0 to 10 in each condition of the experiment (**LDLF**: low frighteningness and low disgustingness; **LFHD**: low frighteningness and high disgustingness; **HFHD**: high frighteningness and low disgustingness; **HFHD**: high frighteningness and high disgustingness).

## Details

This data set, "Bugs", provides the extent to which men and women want to kill arthropods that vary in frighteningness (low, high) and disgustingness (low, high). Each participant rates their attitudes towards all anthropods. Subset of the data reported by Ryan et al. (2013).

## Source

<https://www.sciencedirect.com/science/article/pii/S0747563213000277>

## Examples

```
dim(bugs_wide)
head(bugs_wide)
dplyr::glimpse(bugs_wide)
```

## Description

Wrapper around `patchwork::wrap_plots()` that will return a combined grid of plots with annotations. In case you want to create a grid of plots, it is **highly recommended** that you use `{patchwork}` package directly and not this wrapper around it which is mostly useful with `{ggstatsplot}` plots. It is exported only for backward compatibility.

## Usage

```
combine_plots(  
  plotlist,  
  plotgrid.args = list(),  
  annotation.args = list(),  
  guides = "collect",  
  ...  
)
```

## Arguments

<code>plotlist</code>	A list containing ggplot objects.
<code>plotgrid.args</code>	A list of additional arguments passed to <code>patchwork::wrap_plots()</code> , except for <code>guides</code> argument which is already separately specified here.
<code>annotation.args</code>	A list of additional arguments passed to <code>patchwork::plot_annotation()</code> .
<code>guides</code>	A string specifying how guides should be treated in the layout. 'collect' will collect guides below to the given nesting level, removing duplicates. 'keep' will stop collection at this level and let guides be placed alongside their plot. 'auto' will allow guides to be collected if a upper level tries, but place them alongside the plot if not. If you modify default guide "position" with <a href="#">theme(legend.position=...)</a> while also collecting guides you must apply that change to the overall patchwork (see example).
<code>...</code>	Currently ignored.

## Value

Combined plot with annotation labels

## Examples

```
library(ggplot2)  
  
# preparing the first plot  
p1 <- ggplot(  
  data = subset(iris, iris$Species == "setosa"),
```

```

  aes(x = Sepal.Length, y = Sepal.Width)
) +
  geom_point() +
  labs(title = "setosa")

# preparing the second plot
p2 <- ggplot(
  data = subset(iris, iris$Species == "versicolor"),
  aes(x = Sepal.Length, y = Sepal.Width)
) +
  geom_point() +
  labs(title = "versicolor")

# combining the plot with a title and a caption
combine_plots(
  plotlist = list(p1, p2),
  plotgrid.args = list(nrow = 1),
  annotation.args = list(
    tag_levels = "a",
    title = "Dataset: Iris Flower dataset",
    subtitle = "Edgar Anderson collected this data",
    caption = "Note: Only two species of flower are displayed",
    theme = theme(
      plot.subtitle = element_text(size = 20),
      plot.title = element_text(size = 30)
    )
  )
)
)

```

---

extract\_stats

*Extracting data frames or expressions from {ggstatsplot} plots*


---

## Description

Extracting data frames or expressions from {ggstatsplot} plots

## Usage

```
extract_stats(p, ...)
```

```
extract_subtitle(p)
```

```
extract_caption(p)
```

## Arguments

p	A plot from {ggstatsplot} package
...	Ignored

## Details

These are convenience functions to extract data frames or expressions with statistical details that are used to create expressions displayed in {ggstatsplot} plots as subtitle, caption, etc. Note that all of this analysis is carried out by the {statsExpressions} **package**. And so if you are using these functions only to extract data frames, you are better off using that package.

The only exception is the ggcorrmat() function. But, if a data frame is what you want, you shouldn't be using ggcorrmat() anyway. You can use correlation::correlation() function which provides tidy data frames by default.

## Value

A list of tibbles containing summaries of various statistical analyses. The exact details included will depend on the function.

## Examples

```
set.seed(123)

# non-grouped plot
p1 <- ggbetweenstats(mtcars, cyl, mpg)

# grouped plot
p2 <- grouped_ggbarstats(Titanic_full, Survived, Sex, grouping.var = Age)

# extracting expressions -----

extract_subtitle(p1)
extract_caption(p1)

extract_subtitle(p2)
extract_caption(p2)

# extracting data frames -----

extract_stats(p1)

extract_stats(p2[[1L]])
extract_stats(p2[[2L]])
```

## Description

Bar charts for categorical data with statistical details included in the plot as a subtitle.

**Usage**

```

ggbarstats(
  data,
  x,
  y,
  counts = NULL,
  type = "parametric",
  paired = FALSE,
  results.subtitle = TRUE,
  label = "percentage",
  label.args = list(alpha = 1, fill = "white"),
  k = 2L,
  proportion.test = results.subtitle,
  perc.k = 0L,
  bf.message = TRUE,
  ratio = NULL,
  conf.level = 0.95,
  sampling.plan = "indepMulti",
  fixed.margin = "rows",
  prior.concentration = 1,
  title = NULL,
  subtitle = NULL,
  caption = NULL,
  legend.title = NULL,
  xlab = NULL,
  ylab = NULL,
  ggtheme = ggstatsplot::theme_ggstatsplot(),
  package = "RColorBrewer",
  palette = "Dark2",
  ggplot.component = NULL,
  ...
)

```

**Arguments**

data	A data frame (or a tibble) from which variables specified are to be taken. Other data types (e.g., matrix, table, array, etc.) will <b>not</b> be accepted. Additionally, grouped data frames from {dplyr} should be ungrouped before they are entered as data.
x	The variable to use as the <b>rows</b> in the contingency table. Please note that if there are empty factor levels in your variable, they will be dropped.
y	The variable to use as the <b>columns</b> in the contingency table. Please note that if there are empty factor levels in your variable, they will be dropped. Default is NULL. If NULL, one-sample proportion test (a goodness of fit test) will be run for the x variable. Otherwise an appropriate association test will be run. This argument can not be NULL for ggbarstats function.
counts	The variable in data containing counts, or NULL if each row represents a single observation.



type	<p>A character specifying the type of statistical approach:</p> <ul style="list-style-type: none"> <li>• "parametric"</li> <li>• "nonparametric"</li> <li>• "robust"</li> <li>• "bayes"</li> </ul> <p>You can specify just the initial letter.</p>
paired	Logical indicating whether data came from a within-subjects or repeated measures design study (Default: FALSE). If TRUE, McNemar's test expression will be returned. If FALSE, Pearson's chi-square test will be returned.
results.subtitle	Decides whether the results of statistical tests are to be displayed as a subtitle (Default: TRUE). If set to FALSE, only the plot will be returned.
label	Character decides what information needs to be displayed on the label in each pie slice. Possible options are "percentage" (default), "counts", "both".
label.args	Additional aesthetic arguments that will be passed to geom_label.
k	Number of digits after decimal point (should be an integer) (Default: k = 2L).
proportion.test	Decides whether proportion test for x variable is to be carried out for each level of y. Defaults to results.subtitle. In ggbarstats, only p-values from this test will be displayed.
perc.k	Numeric that decides number of decimal places for percentage labels (Default: 0L).
bf.message	Logical that decides whether to display Bayes Factor in favor of the null hypothesis. This argument is relevant only <b>for parametric test</b> (Default: TRUE).
ratio	A vector of proportions: the expected proportions for the proportion test (should sum to 1). Default is NULL, which means the null is equal theoretical proportions across the levels of the nominal variable. This means if there are two levels this will be ratio = c(0.5, 0.5) or if there are four levels this will be ratio = c(0.25, 0.25, 0.25, 0.25), etc.
conf.level	Scalar between 0 and 1 (default: 95% confidence/credible intervals, 0.95). If NULL, no confidence intervals will be computed.
sampling.plan	Character describing the sampling plan. Possible options are "indepMulti" (independent multinomial; default), "poisson", "jointMulti" (joint multinomial), "hypergeom" (hypergeometric). For more, see ?BayesFactor::contingencyTableBF().
fixed.margin	For the independent multinomial sampling plan, which margin is fixed ("rows" or "cols"). Defaults to "rows".
prior.concentration	Specifies the prior concentration parameter, set to 1 by default. It indexes the expected deviation from the null hypothesis under the alternative, and corresponds to Gunel and Dickey's (1974) "a" parameter.
title	The text for the plot title.
subtitle	The text for the plot subtitle. Will work only if results.subtitle = FALSE.

caption	The text for the plot caption. This argument is relevant only if <code>bf.message = FALSE</code> .
legend.title	Title text for the legend.
xlab	Label for x axis variable. If NULL (default), variable name for x will be used.
ylab	Labels for y axis variable. If NULL (default), variable name for y will be used.
ggtheme	A {ggplot2} theme. Default value is <code>ggstatsplot::theme_ggstatsplot()</code> . Any of the {ggplot2} themes (e.g., <code>theme_bw()</code> ), or themes from extension packages are allowed (e.g., <code>ggthemes::theme_fivethirtyeight()</code> , <code>hrbrthemes::theme_ipsum_ps()</code> etc.). But note that sometimes these themes will remove some of the details that {ggstatsplot} plots typically contains. For example, if relevant, <code>ggbetweenstats()</code> shows details about multiple comparison test as a label on the secondary Y-axis. Some themes (e.g. <code>ggthemes::theme_fivethirtyeight()</code> ) will remove the secondary Y-axis and thus the details as well.
package, palette	Name of the package from which the given palette is to be extracted. The available palettes and packages can be checked by running <code>View(paletteer::palettes_d_names)</code> .
ggplot.component	A ggplot component to be added to the plot prepared by {ggstatsplot}. This argument is primarily helpful for grouped_ variants of all primary functions. Default is NULL. The argument should be entered as a {ggplot2} function or a list of {ggplot2} functions.
...	Currently ignored.

## Details

For details, see: [https://indrajeetpatil.github.io/ggstatsplot/articles/web\\_only/ggpiestats.html](https://indrajeetpatil.github.io/ggstatsplot/articles/web_only/ggpiestats.html)

## Summary of graphics

graphical element	geom used	argument for further modification
bars	<code>ggplot2::geom_bar()</code>	NA
descriptive labels	<code>ggplot2::geom_label()</code>	<code>label.args</code>

## Contingency table analyses

The table below provides summary about:

- statistical test carried out for inferential statistics
- type of effect size estimate and a measure of uncertainty for this estimate
- functions used internally to compute these details

### two-way table:

**Hypothesis testing**

Type	Design	Test	Function used
Parametric/Non-parametric	Unpaired	Pearson's chi-squared test	stats::chisq.test()
Bayesian	Unpaired	Bayesian Pearson's chi-squared test	BayesFactor::contingencyTableBF()
Parametric/Non-parametric	Paired	McNemar's chi-squared test	stats::mcnemar.test()
Bayesian	Paired	No	No

### Effect size estimation

Type	Design	Effect size	CI available?	Function used
Parametric/Non-parametric	Unpaired	Cramer's $V$	Yes	effectsize::cramers_v()
Bayesian	Unpaired	Cramer's $V$	Yes	effectsize::cramers_v()
Parametric/Non-parametric	Paired	Cohen's $g$	Yes	effectsize::cohens_g()
Bayesian	Paired	No	No	No

### one-way table:

#### Hypothesis testing

Type	Test	Function used
Parametric/Non-parametric	Goodness of fit chi-squared test	stats::chisq.test()
Bayesian	Bayesian Goodness of fit chi-squared test	(custom)

### Effect size estimation

Type	Effect size	CI available?	Function used
Parametric/Non-parametric	Pearson's $C$	Yes	effectsize::pearsons_c()
Bayesian	No	No	No

### See Also

[grouped\\_ggbarstats](#), [ggpiestats](#), [grouped\\_ggpiestats](#)

### Examples

```
# for reproducibility
set.seed(123)

# creating a plot
p <- ggbarstats(mtcars, x = vs, y = cyl)

# looking at the plot
p

# extracting details from statistical tests
extract_stats(p)
```

---

`ggbetweenstats`*Box/Violin plots for between-subjects comparisons*

---

**Description**

A combination of box and violin plots along with jittered data points for between-subjects designs with statistical details included in the plot as a subtitle.

**Usage**

```
ggbetweenstats(  
  data,  
  x,  
  y,  
  plot.type = "boxviolin",  
  type = "parametric",  
  pairwise.comparisons = TRUE,  
  pairwise.display = "significant",  
  p.adjust.method = "holm",  
  effsize.type = "unbiased",  
  bf.prior = 0.707,  
  bf.message = TRUE,  
  results.subtitle = TRUE,  
  xlab = NULL,  
  ylab = NULL,  
  caption = NULL,  
  title = NULL,  
  subtitle = NULL,  
  k = 2L,  
  var.equal = FALSE,  
  conf.level = 0.95,  
  nboot = 100L,  
  tr = 0.2,  
  centrality.plotting = TRUE,  
  centrality.type = type,  
  centrality.point.args = list(size = 5, color = "darkred"),  
  centrality.label.args = list(size = 3, nudge_x = 0.4, segment.linetype = 4,  
    min.segment.length = 0),  
  point.args = list(position = ggplot2::position_jitterdodge(dodge.width = 0.6), alpha =  
    0.4, size = 3, stroke = 0, na.rm = TRUE),  
  violin.args = list(width = 0.5, alpha = 0.2, na.rm = TRUE),  
  ggsignif.args = list(textsize = 3, tip_length = 0.01, na.rm = TRUE),  
  ggtheme = ggstatsplot::theme_ggstatsplot(),  
  package = "RColorBrewer",  
  palette = "Dark2",  
  ggplot.component = NULL,  
  ...  
)
```

)

**Arguments**

<code>data</code>	A data frame (or a tibble) from which variables specified are to be taken. Other data types (e.g., <code>matrix</code> , <code>table</code> , <code>array</code> , etc.) will <b>not</b> be accepted. Additionally, grouped data frames from <code>{dplyr}</code> should be ungrouped before they are entered as data.
<code>x</code>	The grouping (or independent) variable from data. In case of a repeated measures or within-subjects design, if <code>subject.id</code> argument is not available or not explicitly specified, the function assumes that the data has already been sorted by such an id by the user and creates an internal identifier. So if your data is <b>not</b> sorted, the results <i>can</i> be inaccurate when there are more than two levels in <code>x</code> and there are NAs present. The data is expected to be sorted by user in <code>subject-1,subject-2, ..., pattern</code> .
<code>y</code>	The response (or outcome or dependent) variable from data.
<code>plot.type</code>	Character describing the <i>type</i> of plot. Currently supported plots are "box" (for only boxplots), "violin" (for only violin plots), and "boxviolin" (for a combination of box and violin plots; default).
<code>type</code>	A character specifying the type of statistical approach: <ul style="list-style-type: none"> <li>• "parametric"</li> <li>• "nonparametric"</li> <li>• "robust"</li> <li>• "bayes"</li> </ul> <p>You can specify just the initial letter.</p>
<code>pairwise.comparisons</code>	Logical that decides whether pairwise comparisons are to be displayed (default: TRUE). Please note that only <b>significant</b> comparisons will be shown by default. To change this behavior, select appropriate option with <code>pairwise.display</code> argument. The pairwise comparison dataframes are prepared using the <code>pairwise_comparisons</code> function. For more details about pairwise comparisons, see the documentation for that function.
<code>pairwise.display</code>	Decides <i>which</i> pairwise comparisons to display. Available options are: <ul style="list-style-type: none"> <li>• "significant" (abbreviation accepted: "s")</li> <li>• "non-significant" (abbreviation accepted: "ns")</li> <li>• "all"</li> </ul> <p>You can use this argument to make sure that your plot is not uber-cluttered when you have multiple groups being compared and scores of pairwise comparisons being displayed.</p>
<code>p.adjust.method</code>	Adjustment method for <i>p</i> -values for multiple comparisons. Possible methods are: "holm" (default), "hochberg", "hommel", "bonferroni", "BH", "BY", "fdr", "none".

<code>effsize.type</code>	Type of effect size needed for <i>parametric</i> tests. The argument can be "eta" (partial eta-squared) or "omega" (partial omega-squared).
<code>bf.prior</code>	A number between 0.5 and 2 (default 0.707), the prior width to use in calculating Bayes factors and posterior estimates. In addition to numeric arguments, several named values are also recognized: "medium", "wide", and "ultrawide", corresponding to <i>r</i> scale values of 1/2, sqrt(2)/2, and 1, respectively. In case of an ANOVA, this value corresponds to scale for fixed effects.
<code>bf.message</code>	Logical that decides whether to display Bayes Factor in favor of the <i>null</i> hypothesis. This argument is relevant only <b>for parametric test</b> (Default: TRUE).
<code>results.subtitle</code>	Decides whether the results of statistical tests are to be displayed as a subtitle (Default: TRUE). If set to FALSE, only the plot will be returned.
<code>xlab</code>	Label for x axis variable. If NULL (default), variable name for x will be used.
<code>ylab</code>	Labels for y axis variable. If NULL (default), variable name for y will be used.
<code>caption</code>	The text for the plot caption. This argument is relevant only if <code>bf.message = FALSE</code> .
<code>title</code>	The text for the plot title.
<code>subtitle</code>	The text for the plot subtitle. Will work only if <code>results.subtitle = FALSE</code> .
<code>k</code>	Number of digits after decimal point (should be an integer) (Default: <code>k = 2L</code> ).
<code>var.equal</code>	a logical variable indicating whether to treat the two variances as being equal. If TRUE then the pooled variance is used to estimate the variance otherwise the Welch (or Satterthwaite) approximation to the degrees of freedom is used.
<code>conf.level</code>	Scalar between 0 and 1 (default: 95% confidence/credible intervals, 0.95). If NULL, no confidence intervals will be computed.
<code>nboot</code>	Number of bootstrap samples for computing confidence interval for the effect size (Default: 100L).
<code>tr</code>	Trim level for the mean when carrying out robust tests. In case of an error, try reducing the value of <code>tr</code> , which is by default set to 0.2. Lowering the value might help.
<code>centrality.plotting</code>	<p>Logical that decides whether centrality tendency measure is to be displayed as a point with a label (Default: TRUE). Function decides which central tendency measure to show depending on the <code>type</code> argument.</p> <ul style="list-style-type: none"> <li>• <b>mean</b> for parametric statistics</li> <li>• <b>median</b> for non-parametric statistics</li> <li>• <b>trimmed mean</b> for robust statistics</li> <li>• <b>MAP estimator</b> for Bayesian statistics</li> </ul> <p>If you want default centrality parameter, you can specify this using <code>centrality.type</code> argument.</p>
<code>centrality.type</code>	<p>Decides which centrality parameter is to be displayed. The default is to choose the same as <code>type</code> argument. You can specify this to be:</p> <ul style="list-style-type: none"> <li>• "parameteric" (for <b>mean</b>)</li> </ul>

- "nonparametric" (for **median**)
- robust (for **trimmed mean**)
- bayes (for **MAP estimator**)

Just as type argument, abbreviations are also accepted.

centrality.point.args, centrality.label.args	A list of additional aesthetic arguments to be passed to <code>geom_point</code> and <code>ggrepel::geom_label_repel</code> geoms, which are involved in mean plotting.
point.args	A list of additional aesthetic arguments to be passed to the <code>geom_point</code> displaying the raw data.
violin.args	A list of additional aesthetic arguments to be passed to the <code>geom_violin</code> .
ggsignif.args	A list of additional aesthetic arguments to be passed to <code>ggsignif::geom_signif</code> .
ggtheme	A <code>{ggplot2}</code> theme. Default value is <code>ggstatsplot::theme_ggstatsplot()</code> . Any of the <code>{ggplot2}</code> themes (e.g., <code>theme_bw()</code> ), or themes from extension packages are allowed (e.g., <code>ggthemes::theme_fivethirtyeight()</code> , <code>hrbrthemes::theme_ipsum_ps()</code> etc.). But note that sometimes these themes will remove some of the details that <code>{ggstatsplot}</code> plots typically contains. For example, if relevant, <code>ggbetweenstats()</code> shows details about multiple comparison test as a label on the secondary Y-axis. Some themes (e.g. <code>ggthemes::theme_fivethirtyeight()</code> ) will remove the secondary Y-axis and thus the details as well.
package, palette	Name of the package from which the given palette is to be extracted. The available palettes and packages can be checked by running <code>View(paletter::palettes_d_names)</code> .
ggplot.component	A <code>ggplot</code> component to be added to the plot prepared by <code>{ggstatsplot}</code> . This argument is primarily helpful for grouped_ variants of all primary functions. Default is NULL. The argument should be entered as a <code>{ggplot2}</code> function or a list of <code>{ggplot2}</code> functions.
...	Currently ignored.

## Details

For details, see: [https://indrajeetpatil.github.io/ggstatsplot/articles/web\\_only/ggbetweenstats.html](https://indrajeetpatil.github.io/ggstatsplot/articles/web_only/ggbetweenstats.html)

## Summary of graphics

graphical element	geom used	argument for further modification
raw data	<code>ggplot2::geom_point()</code>	<code>point.args</code>
box plot	<code>ggplot2::geom_boxplot()</code>	NA
density plot	<code>ggplot2::geom_violin()</code>	<code>violin.args</code>
centrality measure point	<code>ggplot2::geom_point()</code>	<code>centrality.point.args</code>
centrality measure label	<code>ggrepel::geom_label_repel()</code>	<code>centrality.label.args</code>
pairwise comparisons	<code>ggsignif::geom_signif()</code>	<code>ggsignif.args</code>



### Centrality measures

The table below provides summary about:

- statistical test carried out for inferential statistics
- type of effect size estimate and a measure of uncertainty for this estimate
- functions used internally to compute these details

Type	Measure	Function used
Parametric	mean	datawizard::describe_distribution()
Non-parametric	median	datawizard::describe_distribution()
Robust	trimmed mean	datawizard::describe_distribution()
Bayesian	MAP	datawizard::describe_distribution()

### Two-sample tests

The table below provides summary about:

- statistical test carried out for inferential statistics
- type of effect size estimate and a measure of uncertainty for this estimate
- functions used internally to compute these details

#### between-subjects: Hypothesis testing

Type	No. of groups	Test	Function used
Parametric	2	Student's or Welch's $t$ -test	stats::t.test()
Non-parametric	2	Mann-Whitney $U$ test	stats::wilcox.test()
Robust	2	Yuen's test for trimmed means	WRS2::yuen()
Bayesian	2	Student's $t$ -test	BayesFactor::ttestBF()

#### Effect size estimation

Type	No. of groups	Effect size	CI available?	Function used
Parametric	2	Cohen's $d$ , Hedge's $g$	Yes	effectsize:
Non-parametric	2	$r$ (rank-biserial correlation)	Yes	effectsize:
Robust	2	Algina-Keselman-Penfield robust standardized difference	Yes	WRS2::akp.e
Bayesian	2	difference	Yes	bayestestR:

#### within-subjects: Hypothesis testing

Type	No. of groups	Test	Function used
------	---------------	------	---------------

Parametric	2	Student's <i>t</i> -test	stats::t.test()
Non-parametric	2	Wilcoxon signed-rank test	stats::wilcox.test()
Robust	2	Yuen's test on trimmed means for dependent samples	WRS2::yuend()
Bayesian	2	Student's <i>t</i> -test	BayesFactor::ttestBF()

### Effect size estimation

Type	No. of groups	Effect size	CI available?	Function used
Parametric	2	Cohen's <i>d</i> , Hedge's <i>g</i>	Yes	effectsize::
Non-parametric	2	<i>r</i> (rank-biserial correlation)	Yes	effectsize::
Robust	2	Algina-Keselman-Penfield robust standardized difference	Yes	WRS2::wmcplA
Bayesian	2	difference	Yes	bayestestR:

### One-way ANOVA

The table below provides summary about:

- statistical test carried out for inferential statistics
- type of effect size estimate and a measure of uncertainty for this estimate
- functions used internally to compute these details

#### between-subjects:

##### Hypothesis testing

Type	No. of groups	Test	Function used
Parametric	> 2	Fisher's or Welch's one-way ANOVA	stats::oneway.test()
Non-parametric	> 2	Kruskal-Wallis one-way ANOVA	stats::kruskal.test()
Robust	> 2	Heteroscedastic one-way ANOVA for trimmed means	WRS2::t1way()
Bayes Factor	> 2	Fisher's ANOVA	BayesFactor::anovaBF()

### Effect size estimation

Type	No. of groups	Effect size	CI available?	Function used
Parametric	> 2	partial eta-squared, partial omega-squared	Yes	effectsize::omega_squared
Non-parametric	> 2	rank epsilon squared	Yes	effectsize::rank_epsilon
Robust	> 2	Explanatory measure of effect size	Yes	WRS2::t1way()
Bayes Factor	> 2	Bayesian R-squared	Yes	performance::r2_bayes()

#### within-subjects:

##### Hypothesis testing

Type	No. of groups	Test	Function used
Parametric	> 2	One-way repeated measures ANOVA	afex::aov_ez
Non-parametric	> 2	Friedman rank sum test	stats::fried

Robust	> 2	Heteroscedastic one-way repeated measures ANOVA for trimmed means	WRS2::rmanov
Bayes Factor	> 2	One-way repeated measures ANOVA	BayesFactor::

**Effect size estimation**

Type	No. of groups	Effect size	CI available?	Function
Parametric	> 2	partial eta-squared, partial omega-squared	Yes	effect
Non-parametric	> 2	Kendall's coefficient of concordance	Yes	effect
Robust	> 2	Algina-Keselman-Penfield robust standardized difference average	Yes	WRS2::
Bayes Factor	> 2	Bayesian R-squared	Yes	perform

**Pairwise comparison tests**

The table below provides summary about:

- statistical test carried out for inferential statistics
- type of effect size estimate and a measure of uncertainty for this estimate
- functions used internally to compute these details

**between-subjects:  
Hypothesis testing**

Type	Equal variance?	Test	p-value adjustment?	Function used
Parametric	No	Games-Howell test	Yes	PMCMRplus::gamesHowellTest()
Parametric	Yes	Student's <i>t</i> -test	Yes	stats::pairwise.t.test()
Non-parametric	No	Dunn test	Yes	PMCMRplus::kwAllPairsDunnTest()
Robust	No	Yuen's trimmed means test	Yes	WRS2::lincon()
Bayesian	NA	Student's <i>t</i> -test	NA	BayesFactor::ttestBF()

**Effect size estimation**  
Not supported.

**within-subjects:  
Hypothesis testing**

Type	Test	p-value adjustment?	Function used
Parametric	Student's <i>t</i> -test	Yes	stats::pairwise.t.test()
Non-parametric	Durbin-Conover test	Yes	PMCMRplus::durbinAllPairsTest()
Robust	Yuen's trimmed means test	Yes	WRS2::rmmcp()
Bayesian	Student's <i>t</i> -test	NA	BayesFactor::ttestBF()

**Effect size estimation**  
Not supported.

**See Also**

[grouped\\_ggbetweenstats](#), [ggwithinstats](#), [grouped\\_ggwithinstats](#)

**Examples**

```
# for reproducibility
set.seed(123)
library(PMCMRplus) # for pairwise comparisons

# create a plot
p <- ggbetweenstats(mtcars, am, mpg)

# looking at the plot
p

# extracting details from statistical tests
extract_stats(p)

# modifying defaults
ggbetweenstats(
  morley,
  x           = Expt,
  y           = Speed,
  type       = "robust",
  xlab       = "The experiment number",
  ylab       = "Speed-of-light measurement"
)
```

---

ggcoefstats

*Dot-and-whisker plots for regression analyses*

---

**Description**

Plot with the regression coefficients' point estimates as dots with confidence interval whiskers and other statistical details included as labels.

**Usage**

```
ggcoefstats(
  x,
  statistic = NULL,
  conf.int  = TRUE,
  conf.level = 0.95,
  k = 2L,
  exclude.intercept = FALSE,
  effectsize.type = "eta",
  meta.analytic.effect = FALSE,
```

```

meta.type = "parametric",
bf.message = TRUE,
sort = "none",
xlab = NULL,
ylab = NULL,
title = NULL,
subtitle = NULL,
caption = NULL,
only.significant = FALSE,
point.args = list(size = 3, color = "blue", na.rm = TRUE),
errorbar.args = list(height = 0, na.rm = TRUE),
vline = TRUE,
vline.args = list(linewidth = 1, linetype = "dashed"),
stats.labels = TRUE,
stats.label.color = NULL,
stats.label.args = list(size = 3, direction = "y", min.segment.length = 0),
package = "RColorBrewer",
palette = "Dark2",
ggtheme = ggstatsplot::theme_ggstatsplot(),
...
)

```

## Arguments

<code>x</code>	A model object to be tidied, or a tidy data frame from a regression model. Function internally uses <code>parameters::model_parameters()</code> to get a tidy data frame. If a data frame, it <i>must</i> contain at the minimum two columns named <code>term</code> (names of predictors) and <code>estimate</code> (corresponding estimates of coefficients or other quantities of interest).
<code>statistic</code>	Relevant statistic for the model (" <code>t</code> ", " <code>f</code> ", " <code>z</code> ", or " <code>chi</code> ") in the label. Relevant only if <code>x</code> is a <i>data frame</i> .
<code>conf.int</code>	Logical. Decides whether to display confidence intervals as error bars (Default: TRUE).
<code>conf.level</code>	Numeric deciding level of confidence or credible intervals (Default: 0.95).
<code>k</code>	Number of digits after decimal point (should be an integer) (Default: <code>k = 2L</code> ).
<code>exclude.intercept</code>	Logical that decides whether the intercept should be excluded from the plot (Default: FALSE).
<code>effectsize.type</code>	This is the same as <code>effectsize_type</code> argument of <code>parameters::model_parameters()</code> . Defaults to " <code>eta</code> ", and relevant for ANOVA-like objects.
<code>meta.analytic.effect</code>	Logical that decides whether subtitle for meta-analysis via linear (mixed-effects) models (default: FALSE). If TRUE, input to argument <code>subtitle</code> will be ignored. This will be mostly relevant if a data frame with estimates and their standard errors is entered.

<code>meta.type</code>	Type of statistics used to carry out random-effects meta-analysis. If "parametric" (default), <code>metafor::rma</code> function will be used. If "robust", <code>metaplus::metaplus</code> function will be used. If "bayes", <code>metaBMA::meta_random</code> function will be used.
<code>bf.message</code>	Logical that decides whether results from running a Bayesian meta-analysis assuming that the effect size $d$ varies across studies with standard deviation $t$ (i.e., a random-effects analysis) should be displayed in caption. Defaults to TRUE.
<code>sort</code>	If "none" (default) do not sort, "ascending" sort by increasing coefficient value, or "descending" sort by decreasing coefficient value.
<code>xlab</code>	Label for x axis variable. If NULL (default), variable name for x will be used.
<code>ylab</code>	Labels for y axis variable. If NULL (default), variable name for y will be used.
<code>title</code>	The text for the plot title.
<code>subtitle</code>	The text for the plot subtitle. The input to this argument will be ignored if <code>meta.analytic.effect</code> is set to TRUE.
<code>caption</code>	The text for the plot caption. This argument is relevant only if <code>bf.message = FALSE</code> .
<code>only.significant</code>	If TRUE, only stats labels for significant effects is shown (Default: FALSE). This can be helpful when a large number of regression coefficients are to be displayed in a single plot.
<code>point.args</code>	Additional arguments that will be passed to <code>geom_point</code> geom. Please see documentation for that function to know more about these arguments.
<code>errorbar.args</code>	Additional arguments that will be passed to <code>geom_errorbarh</code> geom. Please see documentation for that function to know more about these arguments.
<code>vline</code>	Decides whether to display a vertical line (Default: "TRUE").
<code>vline.args</code>	Additional arguments that will be passed to <code>geom_vline</code> geom. Please see documentation for that function to know more about these arguments.
<code>stats.labels</code>	Logical. Decides whether the statistic and $p$ -values for each coefficient are to be attached to each dot as a text label using <code>ggrepel</code> (Default: TRUE).
<code>stats.label.color</code>	Color for the labels. If set to NULL, colors will be chosen from the specified package (Default: "RColorBrewer") and <code>palette</code> (Default: "Dark2").
<code>stats.label.args</code>	Additional arguments that will be passed to <code>ggrepel::geom_label_repel()</code> . Please see documentation for that function to know more about these arguments.
<code>package, palette</code>	Name of the package from which the given palette is to be extracted. The available palettes and packages can be checked by running <code>View(paletteer::palettes_d_names)</code> .
<code>ggtheme</code>	A <code>{ggplot2}</code> theme. Default value is <code>ggstatsplot::theme_ggstatsplot()</code> . Any of the <code>{ggplot2}</code> themes (e.g., <code>theme_bw()</code> ), or themes from extension packages are allowed (e.g., <code>ggthemes::theme_fivethirtyeight()</code> , <code>hrbrthemes::theme_ipsum_ps()</code> etc.). But note that sometimes these themes will remove some of the details that <code>{ggstatsplot}</code> plots typically contains. For example, if relevant, <code>ggbetweenstats()</code> shows details about multiple comparison test as a label on the secondary Y-axis. Some themes (e.g. <code>ggthemes::theme_fivethirtyeight()</code> ) will remove the secondary Y-axis and thus the details as well.

... Additional arguments to tidying method. For more, see `parameters::model_parameters`.

## Details

For details, see: [https://indrajeetpatil.github.io/ggstatsplot/articles/web\\_only/ggcoefstats.html](https://indrajeetpatil.github.io/ggstatsplot/articles/web_only/ggcoefstats.html)

## Summary of graphics

graphical element	geom used	argument for further modification
regression estimate	<code>ggplot2::geom_point()</code>	<code>point.args</code>
error bars	<code>ggplot2::geom_errorbarh()</code>	<code>errorbar.args</code>
vertical line	<code>ggplot2::geom_vline()</code>	<code>vline.args</code>
label with statistical details	<code>ggrepel::geom_label_repel()</code>	<code>stats.label.args</code>

## Random-effects meta-analysis

The table below provides summary about:

- statistical test carried out for inferential statistics
- type of effect size estimate and a measure of uncertainty for this estimate
- functions used internally to compute these details

### Hypothesis testing and Effect size estimation

Type	Test	CI available?	Function used
Parametric	Pearson's correlation coefficient	Yes	<code>correlation::correlation()</code>
Non-parametric	Spearman's rank correlation coefficient	Yes	<code>correlation::correlation()</code>
Robust	Winsorized Pearson's correlation coefficient	Yes	<code>correlation::correlation()</code>
Bayesian	Bayesian Pearson's correlation coefficient	Yes	<code>correlation::correlation()</code>

## Note

1. In case you want to carry out meta-analysis, you will be asked to install the needed packages (`{metafor}`, `{metaplust}`, or `{metaBMA}`) if they are unavailable.
2. All rows of regression estimates where either of the following quantities is NA will be removed if labels are requested: `estimate`, `statistic`, `p.value`.
3. Given the rapid pace at which new methods are added to these packages, it is recommended that you install development versions of `{easystats}` packages using the `install_latest()` function from `{easystats}`.

## Examples

```

# for reproducibility
set.seed(123)
library(lme4)

# model object
mod <- lm(formula = mpg ~ cyl * am, data = mtcars)

# creating a plot
p <- ggcoefstats(mod)

# looking at the plot
p

# extracting details from statistical tests
extract_stats(p)

# further arguments can be passed to `parameters::model_parameters()`
ggcoefstats(lmer(Reaction ~ Days + (Days | Subject), sleepstudy), effects = "fixed")

```

---

ggcorrmat

*Visualization of a correlation matrix*


---

## Description

Correlation matrix containing results from pairwise correlation tests. If you want a data frame of (grouped) correlation matrix, use `correlation::correlation()` instead. It can also do grouped analysis when used with output from `dplyr::group_by()`.

## Usage

```

ggcorrmat(
  data,
  cor.vars = NULL,
  cor.vars.names = NULL,
  matrix.type = "upper",
  type = "parametric",
  tr = 0.2,
  partial = FALSE,
  k = 2L,
  sig.level = 0.05,
  conf.level = 0.95,
  bf.prior = 0.707,
  p.adjust.method = "holm",
  pch = "cross",
  ggcorrplot.args = list(method = "square", outline.color = "black", pch.cex = 14),
  package = "RColorBrewer",
  palette = "Dark2",

```



```

  colors = c("#E69F00", "white", "#009E73"),
  ggtheme = ggstatsplot::theme_ggstatsplot(),
  ggplot.component = NULL,
  title = NULL,
  subtitle = NULL,
  caption = NULL,
  ...
)

```

## Arguments

<code>data</code>	A data frame from which variables specified are to be taken.
<code>cor.vars</code>	List of variables for which the correlation matrix is to be computed and visualized. If <code>NULL</code> (default), all numeric variables from <code>data</code> will be used.
<code>cor.vars.names</code>	Optional list of names to be used for <code>cor.vars</code> . The names should be entered in the same order.
<code>matrix.type</code>	Character, "upper" (default), "lower", or "full", display full matrix, lower triangular or upper triangular matrix.
<code>type</code>	A character specifying the type of statistical approach: <ul style="list-style-type: none"> <li>• "parametric"</li> <li>• "nonparametric"</li> <li>• "robust"</li> <li>• "bayes"</li> </ul> <p>You can specify just the initial letter.</p>
<code>tr</code>	Trim level for the mean when carrying out robust tests. In case of an error, try reducing the value of <code>tr</code> , which is by default set to 0.2. Lowering the value might help.
<code>partial</code>	Can be <code>TRUE</code> for partial correlations. For Bayesian partial correlations, "full" instead of pseudo-Bayesian partial correlations (i.e., Bayesian correlation based on frequentist partialization) are returned.
<code>k</code>	Number of digits after decimal point (should be an integer) (Default: <code>k = 2L</code> ).
<code>sig.level</code>	Significance level (Default: 0.05). If the $p$ -value in $p$ -value matrix is bigger than <code>sig.level</code> , then the corresponding correlation coefficient is regarded as insignificant and flagged as such in the plot.
<code>conf.level</code>	Scalar between 0 and 1 (default: 95% confidence/credible intervals, 0.95). If <code>NULL</code> , no confidence intervals will be computed.
<code>bf.prior</code>	A number between 0.5 and 2 (default 0.707), the prior width to use in calculating Bayes factors and posterior estimates. In addition to numeric arguments, several named values are also recognized: "medium", "wide", and "ultrawide", corresponding to $r$ scale values of 1/2, $\sqrt{2}/2$ , and 1, respectively. In case of an ANOVA, this value corresponds to scale for fixed effects.
<code>p.adjust.method</code>	Adjustment method for $p$ -values for multiple comparisons. Possible methods are: "holm" (default), "hochberg", "hommel", "bonferroni", "BH", "BY", "fdr", "none".

<code>pch</code>	Decides the point shape to be used for insignificant correlation coefficients (only valid when <code>insig = "pch"</code> ). Default: <code>pch = "cross"</code> .
<code>ggcorrplot.args</code>	A list of additional (mostly aesthetic) arguments that will be passed to <code>ggcorrplot::ggcorrplot()</code> function. The list should avoid any of the following arguments since they are already internally being used: <code>corr</code> , <code>method</code> , <code>p.mat</code> , <code>sig.level</code> , <code>ggtheme</code> , <code>colors</code> , <code>lab</code> , <code>pch</code> , <code>legend.title</code> , <code>digits</code> .
<code>package, palette</code>	Name of the package from which the given palette is to be extracted. The available palettes and packages can be checked by running <code>View(paletteer::palettes_d_names)</code> .
<code>colors</code>	A vector of 3 colors for low, mid, and high correlation values. If set to <code>NULL</code> , manual specification of colors will be turned off and 3 colors from the specified palette from package will be selected.
<code>ggtheme</code>	A <code>{ggplot2}</code> theme. Default value is <code>ggstatsplot::theme_ggstatsplot()</code> . Any of the <code>{ggplot2}</code> themes (e.g., <code>theme_bw()</code> ), or themes from extension packages are allowed (e.g., <code>ggthemes::theme_fivethirtyeight()</code> , <code>hrbrthemes::theme_ipsum_ps()</code> etc.). But note that sometimes these themes will remove some of the details that <code>{ggstatsplot}</code> plots typically contains. For example, if relevant, <code>ggbetweenstats()</code> shows details about multiple comparison test as a label on the secondary Y-axis. Some themes (e.g. <code>ggthemes::theme_fivethirtyeight()</code> ) will remove the secondary Y-axis and thus the details as well.
<code>ggplot.component</code>	A <code>ggplot</code> component to be added to the plot prepared by <code>{ggstatsplot}</code> . This argument is primarily helpful for <code>grouped_</code> variants of all primary functions. Default is <code>NULL</code> . The argument should be entered as a <code>{ggplot2}</code> function or a list of <code>{ggplot2}</code> functions.
<code>title</code>	The text for the plot title.
<code>subtitle</code>	The text for the plot subtitle. Will work only if <code>results.subtitle = FALSE</code> .
<code>caption</code>	The text for the plot caption. This argument is relevant only if <code>bf.message = FALSE</code> .
<code>...</code>	Currently ignored.

## Details

For details, see: [https://indrajeetpatil.github.io/ggstatsplot/articles/web\\_only/ggcorrmat.html](https://indrajeetpatil.github.io/ggstatsplot/articles/web_only/ggcorrmat.html)

## Summary of graphics

graphical element	geom used	argument for further modification
correlation matrix	<code>ggcorrplot::ggcorrplot()</code>	<code>ggcorrplot.args</code>

## Correlation analyses

The table below provides summary about:

- statistical test carried out for inferential statistics
- type of effect size estimate and a measure of uncertainty for this estimate
- functions used internally to compute these details

### Hypothesis testing and Effect size estimation

Type	Test	CI available?	Function used
Parametric	Pearson's correlation coefficient	Yes	<code>correlation::correlation()</code>
Non-parametric	Spearman's rank correlation coefficient	Yes	<code>correlation::correlation()</code>
Robust	Winsorized Pearson's correlation coefficient	Yes	<code>correlation::correlation()</code>
Bayesian	Bayesian Pearson's correlation coefficient	Yes	<code>correlation::correlation()</code>

## See Also

[grouped\\_ggcorrmat](#) [ggscatterstats](#) [grouped\\_ggscatterstats](#)

## Examples

```
# for reproducibility
set.seed(123)
library(ggcorrplot) # for plot

ggcorrmat(iris)
```

---

ggdotplotstats

*Dot plot/chart for labeled numeric data.*

---

## Description

A dot chart (as described by William S. Cleveland) with statistical details from one-sample test.

## Usage

```
ggdotplotstats(
  data,
  x,
  y,
  xlab = NULL,
  ylab = NULL,
  title = NULL,
  subtitle = NULL,
```

```

caption = NULL,
type = "parametric",
test.value = 0,
bf.prior = 0.707,
bf.message = TRUE,
effsize.type = "g",
conf.level = 0.95,
tr = 0.2,
k = 2L,
results.subtitle = TRUE,
point.args = list(color = "black", size = 3, shape = 16),
centrality.plotting = TRUE,
centrality.type = type,
centrality.line.args = list(color = "blue", linewidth = 1, linetype = "dashed"),
ggplot.component = NULL,
ggtheme = ggstatsplot::theme_ggstatsplot(),
...
)

```

## Arguments

<code>data</code>	A data frame (or a tibble) from which variables specified are to be taken. Other data types (e.g., matrix, table, array, etc.) will <b>not</b> be accepted. Additionally, grouped data frames from {dplyr} should be ungrouped before they are entered as data.
<code>x</code>	A numeric variable from the data frame <code>data</code> .
<code>y</code>	Label or grouping variable.
<code>xlab</code>	Label for x axis variable. If NULL (default), variable name for x will be used.
<code>ylab</code>	Labels for y axis variable. If NULL (default), variable name for y will be used.
<code>title</code>	The text for the plot title.
<code>subtitle</code>	The text for the plot subtitle. Will work only if <code>results.subtitle = FALSE</code> .
<code>caption</code>	The text for the plot caption. This argument is relevant only if <code>bf.message = FALSE</code> .
<code>type</code>	A character specifying the type of statistical approach: <ul style="list-style-type: none"> <li>• "parametric"</li> <li>• "nonparametric"</li> <li>• "robust"</li> <li>• "bayes"</li> </ul> <p>You can specify just the initial letter.</p>
<code>test.value</code>	A number indicating the true value of the mean (Default: 0).
<code>bf.prior</code>	A number between 0.5 and 2 (default 0.707), the prior width to use in calculating Bayes factors and posterior estimates. In addition to numeric arguments, several named values are also recognized: "medium", "wide", and "ultrawide", corresponding to $r$ scale values of 1/2, $\sqrt{2}/2$ , and 1, respectively. In case of an ANOVA, this value corresponds to scale for fixed effects.

<code>bf.message</code>	Logical that decides whether to display Bayes Factor in favor of the <i>null</i> hypothesis. This argument is relevant only <b>for parametric test</b> (Default: TRUE).
<code>effsize.type</code>	Type of effect size needed for <i>parametric</i> tests. The argument can be "d" (for Cohen's <i>d</i> ) or "g" (for Hedge's <i>g</i> ).
<code>conf.level</code>	Scalar between 0 and 1 (default: 95% confidence/credible intervals, 0.95). If NULL, no confidence intervals will be computed.
<code>tr</code>	Trim level for the mean when carrying out robust tests. In case of an error, try reducing the value of <code>tr</code> , which is by default set to 0.2. Lowering the value might help.
<code>k</code>	Number of digits after decimal point (should be an integer) (Default: <code>k = 2L</code> ).
<code>results.subtitle</code>	Decides whether the results of statistical tests are to be displayed as a subtitle (Default: TRUE). If set to FALSE, only the plot will be returned.
<code>point.args</code>	A list of additional aesthetic arguments passed to <code>geom_point</code> .
<code>centrality.plotting</code>	<p>Logical that decides whether centrality tendency measure is to be displayed as a point with a label (Default: TRUE). Function decides which central tendency measure to show depending on the <code>type</code> argument.</p> <ul style="list-style-type: none"> <li>• <b>mean</b> for parametric statistics</li> <li>• <b>median</b> for non-parametric statistics</li> <li>• <b>trimmed mean</b> for robust statistics</li> <li>• <b>MAP estimator</b> for Bayesian statistics</li> </ul> <p>If you want default centrality parameter, you can specify this using <code>centrality.type</code> argument.</p>
<code>centrality.type</code>	<p>Decides which centrality parameter is to be displayed. The default is to choose the same as <code>type</code> argument. You can specify this to be:</p> <ul style="list-style-type: none"> <li>• "parameteric" (for <b>mean</b>)</li> <li>• "nonparametric" (for <b>median</b>)</li> <li>• robust (for <b>trimmed mean</b>)</li> <li>• bayes (for <b>MAP estimator</b>)</li> </ul> <p>Just as <code>type</code> argument, abbreviations are also accepted.</p>
<code>centrality.line.args</code>	A list of additional aesthetic arguments to be passed to the <code>geom_line</code> used to display the lines corresponding to the centrality parameter.
<code>ggplot.component</code>	A <code>ggplot</code> component to be added to the plot prepared by <code>{ggstatsplot}</code> . This argument is primarily helpful for <code>grouped_</code> variants of all primary functions. Default is NULL. The argument should be entered as a <code>{ggplot2}</code> function or a list of <code>{ggplot2}</code> functions.
<code>ggtheme</code>	A <code>{ggplot2}</code> theme. Default value is <code>ggstatsplot::theme_ggstatsplot()</code> . Any of the <code>{ggplot2}</code> themes (e.g., <code>theme_bw()</code> ), or themes from extension packages are allowed (e.g., <code>ggthemes::theme_fivethirtyeight()</code> , <code>hrbrthemes::theme_ipsum_ps()</code> ).

etc.). But note that sometimes these themes will remove some of the details that `{ggstatsplot}` plots typically contains. For example, if relevant, `ggbetweenstats()` shows details about multiple comparison test as a label on the secondary Y-axis. Some themes (e.g. `ggthemes::theme_fivethirtyeight()`) will remove the secondary Y-axis and thus the details as well.

... Currently ignored.

## Details

For details, see: [https://indrajeetpatil.github.io/ggstatsplot/articles/web\\_only/ggdotplotstats.html](https://indrajeetpatil.github.io/ggstatsplot/articles/web_only/ggdotplotstats.html)

## Summary of graphics

graphical element	geom used	argument for further modification
histogram bin	<code>ggplot2::stat_bin()</code>	<code>bin.args</code>
centrality measure line	<code>ggplot2::geom_vline()</code>	<code>centrality.line.args</code>
normality curve	<code>ggplot2::stat_function()</code>	<code>normal.curve.args</code>

## One-sample tests

The table below provides summary about:

- statistical test carried out for inferential statistics
- type of effect size estimate and a measure of uncertainty for this estimate
- functions used internally to compute these details

## Hypothesis testing

Type	Test	Function used
Parametric	One-sample Student's $t$ -test	<code>stats::t.test()</code>
Non-parametric	One-sample Wilcoxon test	<code>stats::wilcox.test()</code>
Robust	Bootstrap- $t$ method for one-sample test	<code>WRS2::trimcibt()</code>
Bayesian	One-sample Student's $t$ -test	<code>BayesFactor::ttestBF()</code>

## Effect size estimation

Type	Effect size	CI available?	Function used
Parametric	Cohen's $d$ , Hedge's $g$	Yes	<code>effectsize::cohens_d()</code> , <code>effectsize::hedges_g()</code>
Non-parametric	$r$ (rank-biserial correlation)	Yes	<code>effectsize::rank_biserial()</code>
Robust	trimmed mean	Yes	<code>WRS2::trimcibt()</code>
Bayes Factor	difference	Yes	<code>bayestestR::describe_posterior()</code>

**See Also**

[grouped\\_gghistostats](#), [gghistostats](#), [grouped\\_ggdotplotstats](#)

**Examples**

```
# for reproducibility
set.seed(123)

# creating a plot
p <- ggdotplotstats(
  data = ggplot2::mpg,
  x = cty,
  y = manufacturer,
  title = "Fuel economy data",
  xlab = "city miles per gallon"
)

# looking at the plot
p

# extracting details from statistical tests
extract_stats(p)
```

---

gghistostats

*Histogram for distribution of a numeric variable*

---

**Description**

Histogram with statistical details from one-sample test included in the plot as a subtitle.

**Usage**

```
gghistostats(
  data,
  x,
  binwidth = NULL,
  xlab = NULL,
  title = NULL,
  subtitle = NULL,
  caption = NULL,
  type = "parametric",
  test.value = 0,
  bf.prior = 0.707,
  bf.message = TRUE,
  effsize.type = "g",
  conf.level = 0.95,
```

```

tr = 0.2,
k = 2L,
ggtheme = ggstatsplot::theme_ggstatsplot(),
results.subtitle = TRUE,
bin.args = list(color = "black", fill = "grey50", alpha = 0.7),
centrality.plotting = TRUE,
centrality.type = type,
centrality.line.args = list(color = "blue", linewidth = 1, linetype = "dashed"),
normal.curve = FALSE,
normal.curve.args = list(linewidth = 2),
ggplot.component = NULL,
...
)

```

## Arguments

data	A data frame (or a tibble) from which variables specified are to be taken. Other data types (e.g., matrix, table, array, etc.) will <b>not</b> be accepted. Additionally, grouped data frames from {dplyr} should be ungrouped before they are entered as data.
x	A numeric variable from the data frame data.
binwidth	The width of the histogram bins. Can be specified as a numeric value, or a function that calculates width from $x$ . The default is to use the $\max(x) - \min(x) / \sqrt{N}$ . You should always check this value and explore multiple widths to find the best to illustrate the stories in your data.
xlab	Label for x axis variable. If NULL (default), variable name for x will be used.
title	The text for the plot title.
subtitle	The text for the plot subtitle. Will work only if <code>results.subtitle = FALSE</code> .
caption	The text for the plot caption. This argument is relevant only if <code>bf.message = FALSE</code> .
type	A character specifying the type of statistical approach: <ul style="list-style-type: none"> <li>• "parametric"</li> <li>• "nonparametric"</li> <li>• "robust"</li> <li>• "bayes"</li> </ul> <p>You can specify just the initial letter.</p>
test.value	A number indicating the true value of the mean (Default: 0).
bf.prior	A number between 0.5 and 2 (default 0.707), the prior width to use in calculating Bayes factors and posterior estimates. In addition to numeric arguments, several named values are also recognized: "medium", "wide", and "ultrawide", corresponding to $r$ scale values of 1/2, $\sqrt{2}/2$ , and 1, respectively. In case of an ANOVA, this value corresponds to scale for fixed effects.
bf.message	Logical that decides whether to display Bayes Factor in favor of the <i>null</i> hypothesis. This argument is relevant only <b>for parametric test</b> (Default: TRUE).



<code>effsize.type</code>	Type of effect size needed for <i>parametric</i> tests. The argument can be "d" (for Cohen's <i>d</i> ) or "g" (for Hedge's <i>g</i> ).
<code>conf.level</code>	Scalar between 0 and 1 (default: 95% confidence/credible intervals, 0.95). If NULL, no confidence intervals will be computed.
<code>tr</code>	Trim level for the mean when carrying out robust tests. In case of an error, try reducing the value of <code>tr</code> , which is by default set to 0.2. Lowering the value might help.
<code>k</code>	Number of digits after decimal point (should be an integer) (Default: <code>k = 2L</code> ).
<code>ggtheme</code>	A {ggplot2} theme. Default value is <code>ggstatsplot::theme_ggstatsplot()</code> . Any of the {ggplot2} themes (e.g., <code>theme_bw()</code> ), or themes from extension packages are allowed (e.g., <code>ggthemes::theme_fivethirtyeight()</code> , <code>hrbrthemes::theme_ipsum_ps()</code> etc.). But note that sometimes these themes will remove some of the details that {ggstatsplot} plots typically contains. For example, if relevant, <code>ggbetweenstats()</code> shows details about multiple comparison test as a label on the secondary Y-axis. Some themes (e.g. <code>ggthemes::theme_fivethirtyeight()</code> ) will remove the secondary Y-axis and thus the details as well.
<code>results.subtitle</code>	Decides whether the results of statistical tests are to be displayed as a subtitle (Default: TRUE). If set to FALSE, only the plot will be returned.
<code>bin.args</code>	A list of additional aesthetic arguments to be passed to the <code>stat_bin</code> used to display the bins. Do not specify <code>binwidth</code> argument in this list since it has already been specified using the dedicated argument.
<code>centrality.plotting</code>	<p>Logical that decides whether centrality tendency measure is to be displayed as a point with a label (Default: TRUE). Function decides which central tendency measure to show depending on the <code>type</code> argument.</p> <ul style="list-style-type: none"> <li>• <b>mean</b> for parametric statistics</li> <li>• <b>median</b> for non-parametric statistics</li> <li>• <b>trimmed mean</b> for robust statistics</li> <li>• <b>MAP estimator</b> for Bayesian statistics</li> </ul> <p>If you want default centrality parameter, you can specify this using <code>centrality.type</code> argument.</p>
<code>centrality.type</code>	<p>Decides which centrality parameter is to be displayed. The default is to choose the same as <code>type</code> argument. You can specify this to be:</p> <ul style="list-style-type: none"> <li>• "parameteric" (for <b>mean</b>)</li> <li>• "nonparametric" (for <b>median</b>)</li> <li>• robust (for <b>trimmed mean</b>)</li> <li>• bayes (for <b>MAP estimator</b>)</li> </ul> <p>Just as <code>type</code> argument, abbreviations are also accepted.</p>
<code>centrality.line.args</code>	A list of additional aesthetic arguments to be passed to the <code>geom_line</code> used to display the lines corresponding to the centrality parameter.

<code>normal.curve</code>	A logical value that decides whether to super-impose a normal curve using <code>stats::dnorm(mean(x), sd(x))</code> . Default is FALSE.
<code>normal.curve.args</code>	A list of additional aesthetic arguments to be passed to the normal curve.
<code>ggplot.component</code>	A ggplot component to be added to the plot prepared by <code>{ggstatsplot}</code> . This argument is primarily helpful for <code>grouped_</code> variants of all primary functions. Default is NULL. The argument should be entered as a <code>{ggplot2}</code> function or a list of <code>{ggplot2}</code> functions.
<code>...</code>	Currently ignored.

### Details

For details, see: [https://indrajeetpatil.github.io/ggstatsplot/articles/web\\_only/gghistostats.html](https://indrajeetpatil.github.io/ggstatsplot/articles/web_only/gghistostats.html)

### Summary of graphics

graphical element	geom used	argument for further modification
histogram bin	<code>ggplot2::stat_bin()</code>	<code>bin.args</code>
centrality measure line	<code>ggplot2::geom_vline()</code>	<code>centrality.line.args</code>
normality curve	<code>ggplot2::stat_function()</code>	<code>normal.curve.args</code>

### One-sample tests

The table below provides summary about:

- statistical test carried out for inferential statistics
- type of effect size estimate and a measure of uncertainty for this estimate
- functions used internally to compute these details

### Hypothesis testing

Type	Test	Function used
Parametric	One-sample Student's <i>t</i> -test	<code>stats::t.test()</code>
Non-parametric	One-sample Wilcoxon test	<code>stats::wilcox.test()</code>
Robust	Bootstrap- <i>t</i> method for one-sample test	<code>WRS2::trimcibt()</code>
Bayesian	One-sample Student's <i>t</i> -test	<code>BayesFactor::ttestBF()</code>

### Effect size estimation

Type	Effect size	CI available?	Function used
Parametric	Cohen's <i>d</i> , Hedge's <i>g</i>	Yes	<code>effectsize::cohens_d()</code> , <code>effectsize::hedges_g()</code>
Non-parametric	<i>r</i> (rank-biserial correlation)	Yes	<code>effectsize::rank_biserial()</code>

Robust	trimmed mean	Yes	WRS2::trimcibt()
Bayes Factor	difference	Yes	bayestestR::describe_posterior()

**See Also**

[grouped\\_gghistostats](#), [ggdotplotstats](#), [grouped\\_ggdotplotstats](#)

**Examples**

```
# for reproducibility
set.seed(123)

# creating a plot
p <- gghistostats(
  data      = ToothGrowth,
  x         = len,
  xlab      = "Tooth length",
  centrality.type = "np"
)

# looking at the plot
p

# extracting details from statistical tests
extract_stats(p)
```

---

ggpiestats

*Pie charts with statistical tests*


---

**Description**

Pie charts for categorical data with statistical details included in the plot as a subtitle.

**Usage**

```
ggpiestats(
  data,
  x,
  y = NULL,
  counts = NULL,
  type = "parametric",
  paired = FALSE,
  results.subtitle = TRUE,
  label = "percentage",
  label.args = list(direction = "both"),
```

```

label.repel = FALSE,
k = 2L,
proportion.test = results.subtitle,
perc.k = 0L,
bf.message = TRUE,
ratio = NULL,
conf.level = 0.95,
sampling.plan = "indepMulti",
fixed.margin = "rows",
prior.concentration = 1,
title = NULL,
subtitle = NULL,
caption = NULL,
legend.title = NULL,
ggtheme = ggstatsplot::theme_ggstatsplot(),
package = "RColorBrewer",
palette = "Dark2",
ggplot.component = NULL,
...
)

```

### Arguments

data	A data frame (or a tibble) from which variables specified are to be taken. Other data types (e.g., matrix, table, array, etc.) will <b>not</b> be accepted. Additionally, grouped data frames from {dplyr} should be ungrouped before they are entered as data.
x	The variable to use as the <b>rows</b> in the contingency table. Please note that if there are empty factor levels in your variable, they will be dropped.
y	The variable to use as the <b>columns</b> in the contingency table. Please note that if there are empty factor levels in your variable, they will be dropped. Default is NULL. If NULL, one-sample proportion test (a goodness of fit test) will be run for the x variable. Otherwise an appropriate association test will be run. This argument can not be NULL for ggbarstats function.
counts	The variable in data containing counts, or NULL if each row represents a single observation.
type	A character specifying the type of statistical approach: <ul style="list-style-type: none"> <li>• "parametric"</li> <li>• "nonparametric"</li> <li>• "robust"</li> <li>• "bayes"</li> </ul> <p>You can specify just the initial letter.</p>
paired	Logical indicating whether data came from a within-subjects or repeated measures design study (Default: FALSE). If TRUE, McNemar's test expression will be returned. If FALSE, Pearson's chi-square test will be returned.

<code>results.subtitle</code>	Decides whether the results of statistical tests are to be displayed as a subtitle (Default: TRUE). If set to FALSE, only the plot will be returned.
<code>label</code>	Character decides what information needs to be displayed on the label in each pie slice. Possible options are "percentage" (default), "counts", "both".
<code>label.args</code>	Additional aesthetic arguments that will be passed to <code>geom_label</code> .
<code>label.repel</code>	Whether labels should be repelled using <code>ggrepel</code> package. This can be helpful in case the labels are overlapping.
<code>k</code>	Number of digits after decimal point (should be an integer) (Default: $k = 2L$ ).
<code>proportion.test</code>	Decides whether proportion test for $x$ variable is to be carried out for each level of $y$ . Defaults to <code>results.subtitle</code> . In <code>ggbarstats</code> , only $p$ -values from this test will be displayed.
<code>perc.k</code>	Numeric that decides number of decimal places for percentage labels (Default: $0L$ ).
<code>bf.message</code>	Logical that decides whether to display Bayes Factor in favor of the <i>null</i> hypothesis. This argument is relevant only <b>for parametric test</b> (Default: TRUE).
<code>ratio</code>	A vector of proportions: the expected proportions for the proportion test (should sum to 1). Default is NULL, which means the null is equal theoretical proportions across the levels of the nominal variable. This means if there are two levels this will be <code>ratio = c(0.5, 0.5)</code> or if there are four levels this will be <code>ratio = c(0.25, 0.25, 0.25, 0.25)</code> , etc.
<code>conf.level</code>	Scalar between 0 and 1 (default: 95% confidence/credible intervals, 0.95). If NULL, no confidence intervals will be computed.
<code>sampling.plan</code>	Character describing the sampling plan. Possible options are "indepMulti" (independent multinomial; default), "poisson", "jointMulti" (joint multinomial), "hypergeom" (hypergeometric). For more, see <code>?BayesFactor::contingencyTableBF()</code> .
<code>fixed.margin</code>	For the independent multinomial sampling plan, which margin is fixed ("rows" or "cols"). Defaults to "rows".
<code>prior.concentration</code>	Specifies the prior concentration parameter, set to 1 by default. It indexes the expected deviation from the null hypothesis under the alternative, and corresponds to Gunel and Dickey's (1974) "a" parameter.
<code>title</code>	The text for the plot title.
<code>subtitle</code>	The text for the plot subtitle. Will work only if <code>results.subtitle = FALSE</code> .
<code>caption</code>	The text for the plot caption. This argument is relevant only if <code>bf.message = FALSE</code> .
<code>legend.title</code>	Title text for the legend.
<code>ggtheme</code>	A <code>{ggplot2}</code> theme. Default value is <code>ggstatsplot::theme_ggstatsplot()</code> . Any of the <code>{ggplot2}</code> themes (e.g., <code>theme_bw()</code> ), or themes from extension packages are allowed (e.g., <code>ggthemes::theme_fivethirtyeight()</code> , <code>hrbrthemes::theme_ipsum_ps()</code> etc.). But note that sometimes these themes will remove some of the details that <code>{ggstatsplot}</code> plots typically contains. For example, if relevant, <code>ggbetweenstats()</code> shows details about multiple comparison test as a label on the secondary Y-axis.

Some themes (e.g. `ggthemes::theme_fivethirtyeight()`) will remove the secondary Y-axis and thus the details as well.

package, palette

Name of the package from which the given palette is to be extracted. The available palettes and packages can be checked by running `View(paletter::palettes_d_names)`.

ggplot.component

A ggplot component to be added to the plot prepared by `{ggstatsplot}`. This argument is primarily helpful for grouped\_ variants of all primary functions. Default is NULL. The argument should be entered as a `{ggplot2}` function or a list of `{ggplot2}` functions.

...

Currently ignored.

## Details

For details, see: [https://indrajeetpatil.github.io/ggstatsplot/articles/web\\_only/ggpiestats.html](https://indrajeetpatil.github.io/ggstatsplot/articles/web_only/ggpiestats.html)

## Summary of graphics

graphical element	geom used	argument for further modification
pie slices	<code>ggplot2::geom_col()</code>	NA
labels	<code>ggplot2::geom_label()/ggrepel::geom_label_repel()</code>	<code>label.args</code>

## Contingency table analyses

The table below provides summary about:

- statistical test carried out for inferential statistics
- type of effect size estimate and a measure of uncertainty for this estimate
- functions used internally to compute these details

### two-way table:

#### Hypothesis testing

Type	Design	Test	Function used
Parametric/Non-parametric	Unpaired	Pearson's chi-squared test	<code>stats::chisq.test()</code>
Bayesian	Unpaired	Bayesian Pearson's chi-squared test	<code>BayesFactor::contingencyTableBF()</code>
Parametric/Non-parametric	Paired	McNemar's chi-squared test	<code>stats::mcnemar.test()</code>
Bayesian	Paired	No	No

#### Effect size estimation

Type	Design	Effect size	CI available?	Function used
Parametric/Non-parametric	Unpaired	Cramer's V	Yes	<code>effectsize::cramers_v()</code>

Bayesian	Unpaired	Cramer's $V$	Yes	<code>effectsize::cramers_v()</code>
Parametric/Non-parametric	Paired	Cohen's $g$	Yes	<code>effectsize::cohens_g()</code>
Bayesian	Paired	No	No	No

**one-way table:**  
**Hypothesis testing**

Type	Test	Function used
Parametric/Non-parametric	Goodness of fit chi-squared test	<code>stats::chisq.test()</code>
Bayesian	Bayesian Goodness of fit chi-squared test	(custom)

**Effect size estimation**

Type	Effect size	CI available?	Function used
Parametric/Non-parametric	Pearson's $C$	Yes	<code>effectsize::pearsons_c()</code>
Bayesian	No	No	No

**See Also**

[grouped\\_ggpiestats](#), [ggbarstats](#), [grouped\\_ggbarstats](#)

**Examples**

```
# for reproducibility
set.seed(123)

# one sample goodness of fit proportion test
p <- ggpiestats(mtcars, vs)

# looking at the plot
p

# extracting details from statistical tests
extract_stats(p)

# association test (or contingency table analysis)
ggpiestats(mtcars, vs, cyl)
```

## Description

Scatterplots from {ggplot2} combined with marginal densigram (density + histogram) plots with statistical details.

## Usage

```
ggscatterstats(
  data,
  x,
  y,
  type = "parametric",
  conf.level = 0.95,
  bf.prior = 0.707,
  bf.message = TRUE,
  tr = 0.2,
  k = 2L,
  results.subtitle = TRUE,
  label.var = NULL,
  label.expression = NULL,
  marginal = TRUE,
  point.args = list(size = 3, alpha = 0.4, stroke = 0),
  point.width.jitter = 0,
  point.height.jitter = 0,
  point.label.args = list(size = 3, max.overlaps = 1e+06),
  smooth.line.args = list(linewidth = 1.5, color = "blue", method = "lm", formula = y ~
    x),
  xsidehistogram.args = list(fill = "#009E73", color = "black", na.rm = TRUE),
  ysidehistogram.args = list(fill = "#D55E00", color = "black", na.rm = TRUE),
  xlab = NULL,
  ylab = NULL,
  title = NULL,
  subtitle = NULL,
  caption = NULL,
  ggtheme = ggstatsplot::theme_ggstatsplot(),
  ggplot.component = NULL,
  ...
)
```

## Arguments

data	A data frame (or a tibble) from which variables specified are to be taken. Other data types (e.g., matrix, table, array, etc.) will <b>not</b> be accepted. Additionally, grouped data frames from {dplyr} should be ungrouped before they are entered as data.
x	The column in data containing the explanatory variable to be plotted on the x-axis.
y	The column in data containing the response (outcome) variable to be plotted on the y-axis.



type	<p>A character specifying the type of statistical approach:</p> <ul style="list-style-type: none"> <li>• "parametric"</li> <li>• "nonparametric"</li> <li>• "robust"</li> <li>• "bayes"</li> </ul> <p>You can specify just the initial letter.</p>
conf.level	Scalar between 0 and 1 (default: 95% confidence/credible intervals, 0.95). If NULL, no confidence intervals will be computed.
bf.prior	A number between 0.5 and 2 (default 0.707), the prior width to use in calculating Bayes factors and posterior estimates. In addition to numeric arguments, several named values are also recognized: "medium", "wide", and "ultrawide", corresponding to <i>r</i> scale values of 1/2, sqrt(2)/2, and 1, respectively. In case of an ANOVA, this value corresponds to scale for fixed effects.
bf.message	Logical that decides whether to display Bayes Factor in favor of the <i>null</i> hypothesis. This argument is relevant only <b>for parametric test</b> (Default: TRUE).
tr	Trim level for the mean when carrying out robust tests. In case of an error, try reducing the value of tr, which is by default set to 0.2. Lowering the value might help.
k	Number of digits after decimal point (should be an integer) (Default: k = 2L).
results.subtitle	Decides whether the results of statistical tests are to be displayed as a subtitle (Default: TRUE). If set to FALSE, only the plot will be returned.
label.var	Variable to use for points labels entered as a symbol (e.g. var1).
label.expression	An expression evaluating to a logical vector that determines the subset of data points to label (e.g. $y < 4$ & $z < 20$ ). While using this argument with <code>purrr::pmap()</code> , you will have to provide a quoted expression (e.g. <code>quote(y &lt; 4 &amp; z &lt; 20)</code> ).
marginal	Decides whether marginal distributions will be plotted on axes using <code>ggside</code> functions. The default is TRUE. The package <code>ggside</code> must already be installed by the user.
point.args	A list of additional aesthetic arguments to be passed to <code>geom_point</code> geom used to display the raw data points.
point.width.jitter, point.height.jitter	Degree of jitter in x and y direction, respectively. Defaults to 0 (0%) of the resolution of the data. Note that the jitter should not be specified in the <code>point.args</code> because this information will be passed to two different geoms: one displaying the <b>points</b> and the other displaying the <b>*labels</b> for these points.
point.label.args	A list of additional aesthetic arguments to be passed to <code>ggrepel::geom_label_repel</code> geom used to display the labels.
smooth.line.args	A list of additional aesthetic arguments to be passed to <code>geom_smooth</code> geom used to display the regression line.

<code>xsidehistogram.args</code> , <code>ysidehistogram.args</code>	A list of arguments passed to respective <code>geom_s</code> from the <code>{ggside}</code> package to change the marginal distribution histograms plots.
<code>xlab</code>	Label for x axis variable. If NULL (default), variable name for x will be used.
<code>ylab</code>	Labels for y axis variable. If NULL (default), variable name for y will be used.
<code>title</code>	The text for the plot title.
<code>subtitle</code>	The text for the plot subtitle. Will work only if <code>results.subtitle = FALSE</code> .
<code>caption</code>	The text for the plot caption. This argument is relevant only if <code>bf.message = FALSE</code> .
<code>ggtheme</code>	A <code>{ggplot2}</code> theme. Default value is <code>ggstatsplot::theme_ggstatsplot()</code> . Any of the <code>{ggplot2}</code> themes (e.g., <code>theme_bw()</code> ), or themes from extension packages are allowed (e.g., <code>ggthemes::theme_fivethirtyeight()</code> , <code>hrbrthemes::theme_ipsum_ps()</code> etc.). But note that sometimes these themes will remove some of the details that <code>{ggstatsplot}</code> plots typically contains. For example, if relevant, <code>ggbetweenstats()</code> shows details about multiple comparison test as a label on the secondary Y-axis. Some themes (e.g. <code>ggthemes::theme_fivethirtyeight()</code> ) will remove the secondary Y-axis and thus the details as well.
<code>ggplot.component</code>	A <code>ggplot</code> component to be added to the plot prepared by <code>{ggstatsplot}</code> . This argument is primarily helpful for <code>grouped_</code> variants of all primary functions. Default is NULL. The argument should be entered as a <code>{ggplot2}</code> function or a list of <code>{ggplot2}</code> functions.
<code>...</code>	Currently ignored.

## Details

For details, see: [https://indrajeetpatil.github.io/ggstatsplot/articles/web\\_only/ggscatterstats.html](https://indrajeetpatil.github.io/ggstatsplot/articles/web_only/ggscatterstats.html)

## Summary of graphics

graphical element	geom used	argument for further modification
histogram bin	<code>ggplot2::stat_bin()</code>	<code>bin.args</code>
centrality measure line	<code>ggplot2::geom_vline()</code>	<code>centrality.line.args</code>
normality curve	<code>ggplot2::stat_function()</code>	<code>normal.curve.args</code>

## Correlation analyses

The table below provides summary about:

- statistical test carried out for inferential statistics
- type of effect size estimate and a measure of uncertainty for this estimate
- functions used internally to compute these details

**Hypothesis testing and Effect size estimation**

Type	Test	CI available?	Function used
Parametric	Pearson's correlation coefficient	Yes	correlation::correlation()
Non-parametric	Spearman's rank correlation coefficient	Yes	correlation::correlation()
Robust	Winsorized Pearson's correlation coefficient	Yes	correlation::correlation()
Bayesian	Bayesian Pearson's correlation coefficient	Yes	correlation::correlation()

**Note**

The plot uses `ggrepel::geom_label_repel()` to attempt to keep labels from over-lapping to the largest degree possible. As a consequence plot times will slow down massively (and the plot file will grow in size) if you have a lot of labels that overlap.

**See Also**

[grouped\\_ggscatterstats](#), [ggcorrmat](#), [grouped\\_ggcorrmat](#)

**Examples**

```
set.seed(123)
library(ggside) # for plotting marginals

# creating a plot
p <- ggscatterstats(
  iris,
  x = Sepal.Width,
  y = Petal.Length,
  label.var = Species,
  label.expression = Sepal.Length > 7.6
) +
  ggplot2::geom_rug(sides = "b")

# looking at the plot
p

# extracting details from statistical tests
extract_stats(p)
```

**Description**

A combination of box and violin plots along with raw (unjittered) data points for within-subjects designs with statistical details included in the plot as a subtitle.

**Usage**

```

ggwithinstats(
  data,
  x,
  y,
  type = "parametric",
  pairwise.comparisons = TRUE,
  pairwise.display = "significant",
  p.adjust.method = "holm",
  effsize.type = "unbiased",
  bf.prior = 0.707,
  bf.message = TRUE,
  results.subtitle = TRUE,
  xlab = NULL,
  ylab = NULL,
  caption = NULL,
  title = NULL,
  subtitle = NULL,
  k = 2L,
  conf.level = 0.95,
  nboot = 100L,
  tr = 0.2,
  centrality.plotting = TRUE,
  centrality.type = type,
  centrality.point.args = list(size = 5, color = "darkred"),
  centrality.label.args = list(size = 3, nudge_x = 0.4, segment.linetype = 4),
  centrality.path = TRUE,
  centrality.path.args = list(linewidth = 1, color = "red", alpha = 0.5),
  point.args = list(size = 3, alpha = 0.5, na.rm = TRUE),
  point.path = TRUE,
  point.path.args = list(alpha = 0.5, linetype = "dashed"),
  boxplot.args = list(width = 0.2, alpha = 0.5, na.rm = TRUE),
  violin.args = list(width = 0.5, alpha = 0.2, na.rm = TRUE),
  ggsignif.args = list(textsize = 3, tip_length = 0.01, na.rm = TRUE),
  ggtheme = ggstatsplot::theme_ggstatsplot(),
  package = "RColorBrewer",
  palette = "Dark2",
  ggplot.component = NULL,
  ...
)

```

**Arguments**

data	A data frame (or a tibble) from which variables specified are to be taken. Other data types (e.g., matrix, table, array, etc.) will <b>not</b> be accepted. Additionally, grouped data frames from {dplyr} should be ungrouped before they are entered as data.
x	The grouping (or independent) variable from data. In case of a repeated mea-

	<p>tures or within-subjects design, if <code>subject.id</code> argument is not available or not explicitly specified, the function assumes that the data has already been sorted by such an id by the user and creates an internal identifier. So if your data is <b>not</b> sorted, the results <i>can</i> be inaccurate when there are more than two levels in <code>x</code> and there are NAs present. The data is expected to be sorted by user in <code>subject-1,subject-2, ..., pattern</code>.</p>
<code>y</code>	The response (or outcome or dependent) variable from data.
<code>type</code>	<p>A character specifying the type of statistical approach:</p> <ul style="list-style-type: none"> <li>• "parametric"</li> <li>• "nonparametric"</li> <li>• "robust"</li> <li>• "bayes"</li> </ul> <p>You can specify just the initial letter.</p>
<code>pairwise.comparisons</code>	<p>Logical that decides whether pairwise comparisons are to be displayed (default: TRUE). Please note that only <b>significant</b> comparisons will be shown by default. To change this behavior, select appropriate option with <code>pairwise.display</code> argument. The pairwise comparison dataframes are prepared using the <code>pairwise_comparisons</code> function. For more details about pairwise comparisons, see the documentation for that function.</p>
<code>pairwise.display</code>	<p>Decides <i>which</i> pairwise comparisons to display. Available options are:</p> <ul style="list-style-type: none"> <li>• "significant" (abbreviation accepted: "s")</li> <li>• "non-significant" (abbreviation accepted: "ns")</li> <li>• "all"</li> </ul> <p>You can use this argument to make sure that your plot is not uber-cluttered when you have multiple groups being compared and scores of pairwise comparisons being displayed.</p>
<code>p.adjust.method</code>	<p>Adjustment method for <i>p</i>-values for multiple comparisons. Possible methods are: "holm" (default), "hochberg", "hommel", "bonferroni", "BH", "BY", "fdr", "none".</p>
<code>effsize.type</code>	Type of effect size needed for <i>parametric</i> tests. The argument can be "eta" (partial eta-squared) or "omega" (partial omega-squared).
<code>bf.prior</code>	<p>A number between 0.5 and 2 (default 0.707), the prior width to use in calculating Bayes factors and posterior estimates. In addition to numeric arguments, several named values are also recognized: "medium", "wide", and "ultrawide", corresponding to <i>r</i> scale values of 1/2, sqrt(2)/2, and 1, respectively. In case of an ANOVA, this value corresponds to scale for fixed effects.</p>
<code>bf.message</code>	<p>Logical that decides whether to display Bayes Factor in favor of the <i>null</i> hypothesis. This argument is relevant only <b>for parametric test</b> (Default: TRUE).</p>
<code>results.subtitle</code>	<p>Decides whether the results of statistical tests are to be displayed as a subtitle (Default: TRUE). If set to FALSE, only the plot will be returned.</p>

<code>xlab</code>	Label for x axis variable. If NULL (default), variable name for x will be used.
<code>ylab</code>	Labels for y axis variable. If NULL (default), variable name for y will be used.
<code>caption</code>	The text for the plot caption. This argument is relevant only if <code>bf.message = FALSE</code> .
<code>title</code>	The text for the plot title.
<code>subtitle</code>	The text for the plot subtitle. Will work only if <code>results.subtitle = FALSE</code> .
<code>k</code>	Number of digits after decimal point (should be an integer) (Default: <code>k = 2L</code> ).
<code>conf.level</code>	Scalar between 0 and 1 (default: 95% confidence/credible intervals, 0.95). If NULL, no confidence intervals will be computed.
<code>nboot</code>	Number of bootstrap samples for computing confidence interval for the effect size (Default: <code>100L</code> ).
<code>tr</code>	Trim level for the mean when carrying out robust tests. In case of an error, try reducing the value of <code>tr</code> , which is by default set to 0.2. Lowering the value might help.
<code>centrality.plotting</code>	<p>Logical that decides whether centrality tendency measure is to be displayed as a point with a label (Default: TRUE). Function decides which central tendency measure to show depending on the <code>type</code> argument.</p> <ul style="list-style-type: none"> <li>• <b>mean</b> for parametric statistics</li> <li>• <b>median</b> for non-parametric statistics</li> <li>• <b>trimmed mean</b> for robust statistics</li> <li>• <b>MAP estimator</b> for Bayesian statistics</li> </ul> <p>If you want default centrality parameter, you can specify this using <code>centrality.type</code> argument.</p>
<code>centrality.type</code>	<p>Decides which centrality parameter is to be displayed. The default is to choose the same as <code>type</code> argument. You can specify this to be:</p> <ul style="list-style-type: none"> <li>• "parameteric" (for <b>mean</b>)</li> <li>• "nonparametric" (for <b>median</b>)</li> <li>• robust (for <b>trimmed mean</b>)</li> <li>• bayes (for <b>MAP estimator</b>)</li> </ul> <p>Just as <code>type</code> argument, abbreviations are also accepted.</p>
<code>centrality.point.args</code> , <code>centrality.label.args</code>	A list of additional aesthetic arguments to be passed to <code>geom_point</code> and <code>ggrepel::geom_label_repel</code> geoms, which are involved in mean plotting.
<code>centrality.path.args</code> , <code>point.path.args</code>	A list of additional aesthetic arguments passed on to <code>geom_path</code> connecting raw data points and mean points.
<code>point.args</code>	A list of additional aesthetic arguments to be passed to the <code>geom_point</code> displaying the raw data.

<code>point.path</code> , <code>centrality.path</code>	Logical that decides whether individual data points and means, respectively, should be connected using <code>geom_path</code> . Both default to <code>TRUE</code> . Note that <code>point.path</code> argument is relevant only when there are two groups (i.e., in case of a <i>t</i> -test). In case of large number of data points, it is advisable to set <code>point.path = FALSE</code> as these lines can overwhelm the plot.
<code>boxplot.args</code>	A list of additional aesthetic arguments passed on to <code>geom_boxplot</code> .
<code>violin.args</code>	A list of additional aesthetic arguments to be passed to the <code>geom_violin</code> .
<code>ggsignif.args</code>	A list of additional aesthetic arguments to be passed to <code>ggsignif::geom_signif</code> .
<code>ggtheme</code>	A <code>{ggplot2}</code> theme. Default value is <code>ggstatsplot::theme_ggstatsplot()</code> . Any of the <code>{ggplot2}</code> themes (e.g., <code>theme_bw()</code> ), or themes from extension packages are allowed (e.g., <code>ggthemes::theme_fivethirtyeight()</code> , <code>hrbrthemes::theme_ipsum_ps()</code> etc.). But note that sometimes these themes will remove some of the details that <code>{ggstatsplot}</code> plots typically contains. For example, if relevant, <code>ggbetweenstats()</code> shows details about multiple comparison test as a label on the secondary Y-axis. Some themes (e.g. <code>ggthemes::theme_fivethirtyeight()</code> ) will remove the secondary Y-axis and thus the details as well.
<code>package</code> , <code>palette</code>	Name of the package from which the given palette is to be extracted. The available palettes and packages can be checked by running <code>View(paletteer::palettes_d_names)</code> .
<code>ggplot.component</code>	A <code>ggplot</code> component to be added to the plot prepared by <code>{ggstatsplot}</code> . This argument is primarily helpful for grouped_ variants of all primary functions. Default is <code>NULL</code> . The argument should be entered as a <code>{ggplot2}</code> function or a list of <code>{ggplot2}</code> functions.
<code>...</code>	Currently ignored.

## Details

For details, see: [https://indrajeetpatil.github.io/ggstatsplot/articles/web\\_only/ggwithinstats.html](https://indrajeetpatil.github.io/ggstatsplot/articles/web_only/ggwithinstats.html)

## Summary of graphics

graphical element	geom used	argument for further modification
raw data	<code>ggplot2::geom_point()</code>	<code>point.args</code>
point path	<code>ggplot2::geom_path()</code>	<code>point.path.args</code>
box plot	<code>ggplot2::geom_boxplot()</code>	<code>boxplot.args</code>
density plot	<code>ggplot2::geom_violin()</code>	<code>violin.args</code>
centrality measure point	<code>ggplot2::geom_point()</code>	<code>centrality.point.args</code>
centrality measure point path	<code>ggplot2::geom_path()</code>	<code>centrality.path.args</code>
centrality measure label	<code>ggrepel::geom_label_repel()</code>	<code>centrality.label.args</code>
pairwise comparisons	<code>ggsignif::geom_signif()</code>	<code>ggsignif.args</code>

### Centrality measures

The table below provides summary about:

- statistical test carried out for inferential statistics
- type of effect size estimate and a measure of uncertainty for this estimate
- functions used internally to compute these details

Type	Measure	Function used
Parametric	mean	<code>datawizard::describe_distribution()</code>
Non-parametric	median	<code>datawizard::describe_distribution()</code>
Robust	trimmed mean	<code>datawizard::describe_distribution()</code>
Bayesian	MAP	<code>datawizard::describe_distribution()</code>

### Two-sample tests

The table below provides summary about:

- statistical test carried out for inferential statistics
- type of effect size estimate and a measure of uncertainty for this estimate
- functions used internally to compute these details

#### between-subjects:

##### Hypothesis testing

Type	No. of groups	Test	Function used
Parametric	2	Student's or Welch's <i>t</i> -test	<code>stats::t.test()</code>
Non-parametric	2	Mann-Whitney <i>U</i> test	<code>stats::wilcox.test()</code>
Robust	2	Yuen's test for trimmed means	<code>WRS2::yuen()</code>
Bayesian	2	Student's <i>t</i> -test	<code>BayesFactor::ttestBF()</code>

##### Effect size estimation

Type	No. of groups	Effect size	CI available?	Function used
Parametric	2	Cohen's <i>d</i> , Hedge's <i>g</i>	Yes	<code>effectsize::</code>
Non-parametric	2	<i>r</i> (rank-biserial correlation)	Yes	<code>effectsize::</code>
Robust	2	Algina-Keselman-Penfield robust standardized difference	Yes	<code>WRS2::akp.e</code>
Bayesian	2	difference	Yes	<code>bayestestR::</code>

#### within-subjects:

##### Hypothesis testing

Type	No. of groups	Test	Function used
Parametric	2	Student's <i>t</i> -test	<code>stats::t.test()</code>
Non-parametric	2	Wilcoxon signed-rank test	<code>stats::wilcox.test()</code>



Robust	2	Yuen's test on trimmed means for dependent samples	WRS2::yuend()
Bayesian	2	Student's <i>t</i> -test	BayesFactor::ttestBF()

### Effect size estimation

Type	No. of groups	Effect size	CI available?	Function used
Parametric	2	Cohen's <i>d</i> , Hedge's <i>g</i>	Yes	effectsize::
Non-parametric	2	<i>r</i> (rank-biserial correlation)	Yes	effectsize::
Robust	2	Algina-Keselman-Penfield robust standardized difference	Yes	WRS2::wmcprA
Bayesian	2	difference	Yes	bayestestR:

## One-way ANOVA

The table below provides summary about:

- statistical test carried out for inferential statistics
- type of effect size estimate and a measure of uncertainty for this estimate
- functions used internally to compute these details

### between-subjects:

#### Hypothesis testing

Type	No. of groups	Test	Function used
Parametric	> 2	Fisher's or Welch's one-way ANOVA	stats::oneway.test()
Non-parametric	> 2	Kruskal-Wallis one-way ANOVA	stats::kruskal.test()
Robust	> 2	Heteroscedastic one-way ANOVA for trimmed means	WRS2::t1way()
Bayes Factor	> 2	Fisher's ANOVA	BayesFactor::anovaBF()

### Effect size estimation

Type	No. of groups	Effect size	CI available?	Function used
Parametric	> 2	partial eta-squared, partial omega-squared	Yes	effectsize::omega_squared
Non-parametric	> 2	rank epsilon squared	Yes	effectsize::rank_epsilon
Robust	> 2	Explanatory measure of effect size	Yes	WRS2::t1way()
Bayes Factor	> 2	Bayesian R-squared	Yes	performance::r2_bayes()

### within-subjects:

#### Hypothesis testing

Type	No. of groups	Test	Function used
Parametric	> 2	One-way repeated measures ANOVA	afex::aov_ez
Non-parametric	> 2	Friedman rank sum test	stats::fried
Robust	> 2	Heteroscedastic one-way repeated measures ANOVA for trimmed means	WRS2::rmanov
Bayes Factor	> 2	One-way repeated measures ANOVA	BayesFactor:

**Effect size estimation**

Type	No. of groups	Effect size	CI available?	Function used
Parametric	> 2	partial eta-squared, partial omega-squared	Yes	effectsize::partialEtaSquared(), effectsize::partialOmegaSquared()
Non-parametric	> 2	Kendall's coefficient of concordance	Yes	effectsize::kendallTauB(), effectsize::kendallTauC()
Robust	> 2	Algina-Keselman-Penfield robust standardized difference average	Yes	WRS2::lincon()
Bayes Factor	> 2	Bayesian R-squared	Yes	BayesFactor::ttestBF()

**Pairwise comparison tests**

The table below provides summary about:

- statistical test carried out for inferential statistics
- type of effect size estimate and a measure of uncertainty for this estimate
- functions used internally to compute these details

**between-subjects:****Hypothesis testing**

Type	Equal variance?	Test	<i>p</i> -value adjustment?	Function used
Parametric	No	Games-Howell test	Yes	PMCMRplus::gamesHowellTest()
Parametric	Yes	Student's <i>t</i> -test	Yes	stats::pairwise.t.test()
Non-parametric	No	Dunn test	Yes	PMCMRplus::kwAllPairsDunnTest()
Robust	No	Yuen's trimmed means test	Yes	WRS2::lincon()
Bayesian	NA	Student's <i>t</i> -test	NA	BayesFactor::ttestBF()

**Effect size estimation**

Not supported.

**within-subjects:****Hypothesis testing**

Type	Test	<i>p</i> -value adjustment?	Function used
Parametric	Student's <i>t</i> -test	Yes	stats::pairwise.t.test()
Non-parametric	Durbin-Conover test	Yes	PMCMRplus::durbinAllPairsTest()
Robust	Yuen's trimmed means test	Yes	WRS2::rmmcp()
Bayesian	Student's <i>t</i> -test	NA	BayesFactor::ttestBF()

**Effect size estimation**

Not supported.

**See Also**

[grouped\\_ggbetweenstats](#), [ggbetweenstats](#), [grouped\\_ggwithinstats](#)

## Examples

```
# for reproducibility
set.seed(123)
library(dplyr, warn.conflicts = FALSE)

# create a plot
p <- ggwithinstats(
  data = filter(bugs_long, condition %in% c("HDHF", "HDLF")),
  x     = condition,
  y     = desire,
  type  = "np"
)

# looking at the plot
p

# extracting details from statistical tests
extract_stats(p)

# modifying defaults
ggwithinstats(
  data      = bugs_long,
  x         = condition,
  y         = desire,
  type      = "robust"
)
```

---

grouped\_ggbarstats      *Grouped bar charts with statistical tests*

---

## Description

Helper function for `ggstatsplot::ggbarstats()` to apply this function across multiple levels of a given factor and combining the resulting plots using `ggstatsplot::combine_plots()`.

## Usage

```
grouped_ggbarstats(
  data,
  ...,
  grouping.var,
  plotgrid.args = list(),
  annotation.args = list()
)
```

**Arguments**

- `data` A data frame (or a tibble) from which variables specified are to be taken. Other data types (e.g., matrix, table, array, etc.) will **not** be accepted. Additionally, grouped data frames from {dplyr} should be ungrouped before they are entered as data.
- `...` Arguments passed on to `ggbarstats`
- `x` The variable to use as the **rows** in the contingency table. Please note that if there are empty factor levels in your variable, they will be dropped.
  - `y` The variable to use as the **columns** in the contingency table. Please note that if there are empty factor levels in your variable, they will be dropped. Default is NULL. If NULL, one-sample proportion test (a goodness of fit test) will be run for the x variable. Otherwise an appropriate association test will be run. This argument can not be NULL for `ggbarstats` function.
  - `proportion.test` Decides whether proportion test for x variable is to be carried out for each level of y. Defaults to `results.subtitle`. In `ggbarstats`, only *p*-values from this test will be displayed.
  - `perc.k` Numeric that decides number of decimal places for percentage labels (Default: 0L).
  - `label` Character decides what information needs to be displayed on the label in each pie slice. Possible options are "percentage" (default), "counts", "both".
  - `label.args` Additional aesthetic arguments that will be passed to `geom_label`.
  - `legend.title` Title text for the legend.
  - `bf.message` Logical that decides whether to display Bayes Factor in favor of the *null* hypothesis. This argument is relevant only **for parametric test** (Default: TRUE).
  - `results.subtitle` Decides whether the results of statistical tests are to be displayed as a subtitle (Default: TRUE). If set to FALSE, only the plot will be returned.
  - `subtitle` The text for the plot subtitle. Will work only if `results.subtitle = FALSE`.
  - `caption` The text for the plot caption. This argument is relevant only if `bf.message = FALSE`.
  - `ggplot.component` A ggplot component to be added to the plot prepared by {ggstatsplot}. This argument is primarily helpful for grouped\_ variants of all primary functions. Default is NULL. The argument should be entered as a {ggplot2} function or a list of {ggplot2} functions.
  - `package,palette` Name of the package from which the given palette is to be extracted. The available palettes and packages can be checked by running `View(paletteer::palettes_d_names)`.
  - `ggtheme` A {ggplot2} theme. Default value is `ggstatsplot::theme_ggstatsplot()`. Any of the {ggplot2} themes (e.g., `theme_bw()`), or themes from extension packages are allowed (e.g., `ggthemes::theme_fivethirtyeight()`, `hrbrthemes::theme_ipsum_ps()`, etc.). But note that sometimes these themes will remove some of the details that {ggstatsplot} plots typically

contains. For example, if relevant, `ggbetweenstats()` shows details about multiple comparison test as a label on the secondary Y-axis. Some themes (e.g. `ggthemes::theme_fivethirtyeight()`) will remove the secondary Y-axis and thus the details as well.

`type` A character specifying the type of statistical approach:

- "parametric"
- "nonparametric"
- "robust"
- "bayes"

You can specify just the initial letter.

`k` Number of digits after decimal point (should be an integer) (Default: `k = 2L`).

`conf.level` Scalar between 0 and 1 (default: 95% confidence/credible intervals, 0.95). If NULL, no confidence intervals will be computed.

`paired` Logical indicating whether data came from a within-subjects or repeated measures design study (Default: FALSE). If TRUE, McNemar's test expression will be returned. If FALSE, Pearson's chi-square test will be returned.

`counts` The variable in data containing counts, or NULL if each row represents a single observation.

`ratio` A vector of proportions: the expected proportions for the proportion test (should sum to 1). Default is NULL, which means the null is equal theoretical proportions across the levels of the nominal variable. This means if there are two levels this will be `ratio = c(0.5, 0.5)` or if there are four levels this will be `ratio = c(0.25, 0.25, 0.25, 0.25)`, etc.

`sampling.plan` Character describing the sampling plan. Possible options are "indepMulti" (independent multinomial; default), "poisson", "jointMulti" (joint multinomial), "hypergeom" (hypergeometric). For more, see `?BayesFactor::contingencyTable`.

`fixed.margin` For the independent multinomial sampling plan, which margin is fixed ("rows" or "cols"). Defaults to "rows".

`prior.concentration` Specifies the prior concentration parameter, set to 1 by default. It indexes the expected deviation from the null hypothesis under the alternative, and corresponds to Gunel and Dickey's (1974) "a" parameter.

`xlab` Label for x axis variable. If NULL (default), variable name for x will be used.

`ylab` Labels for y axis variable. If NULL (default), variable name for y will be used.

`grouping.var` A single grouping variable.

`plotgrid.args` A list of additional arguments passed to `patchwork::wrap_plots()`, except for `guides` argument which is already separately specified here.

`annotation.args` A list of additional arguments passed to `patchwork::plot_annotation()`.

## Details

For details, see: [https://indrajeetpatil.github.io/ggstatsplot/articles/web\\_only/ggpiestats.html](https://indrajeetpatil.github.io/ggstatsplot/articles/web_only/ggpiestats.html)

**See Also**

[ggbarstats](#), [ggpiestats](#), [grouped\\_ggpiestats](#)

**Examples**

```
# for reproducibility
set.seed(123)
library(dplyr, warn.conflicts = FALSE)

# let's create a smaller data frame
diamonds_short <- ggplot2::diamonds %>%
  filter(cut %in% c("Very Good", "Ideal")) %>%
  filter(clarity %in% c("SI1", "SI2", "VS1", "VS2")) %>%
  sample_frac(size = 0.05)

# plot
grouped_ggbarstats(
  data      = diamonds_short,
  x         = color,
  y         = clarity,
  grouping.var = cut,
  plotgrid.args = list(nrow = 2)
)
```

---

`grouped_ggbetweenstats`

*Violin plots for group or condition comparisons in between-subjects designs repeated across all levels of a grouping variable.*

---

**Description**

Helper function for `ggstatsplot::ggbetweenstats` to apply this function across multiple levels of a given factor and combining the resulting plots using `ggstatsplot::combine_plots`.

**Usage**

```
grouped_ggbetweenstats(
  data,
  ...,
  grouping.var,
  plotgrid.args = list(),
  annotation.args = list()
)
```

**Arguments**

data	A data frame (or a tibble) from which variables specified are to be taken. Other data types (e.g., matrix, table, array, etc.) will <b>not</b> be accepted. Additionally, grouped data frames from {dplyr} should be ungrouped before they are entered as data.
...	Arguments passed on to <a href="#">ggbetweenstats</a>
plot.type	Character describing the <i>type</i> of plot. Currently supported plots are "box" (for only boxplots), "violin" (for only violin plots), and "boxviolin" (for a combination of box and violin plots; default).
xlab	Label for x axis variable. If NULL (default), variable name for x will be used.
ylab	Labels for y axis variable. If NULL (default), variable name for y will be used.
pairwise.comparisons	Logical that decides whether pairwise comparisons are to be displayed (default: TRUE). Please note that only <b>significant</b> comparisons will be shown by default. To change this behavior, select appropriate option with pairwise.display argument. The pairwise comparison dataframes are prepared using the pairwise_comparisons function. For more details about pairwise comparisons, see the documentation for that function.
p.adjust.method	Adjustment method for <i>p</i> -values for multiple comparisons. Possible methods are: "holm" (default), "hochberg", "hommel", "bonferroni", "BH", "BY", "fdr", "none".
pairwise.display	Decides <i>which</i> pairwise comparisons to display. Available options are: <ul style="list-style-type: none"> <li>• "significant" (abbreviation accepted: "s")</li> <li>• "non-significant" (abbreviation accepted: "ns")</li> <li>• "all"</li> </ul> You can use this argument to make sure that your plot is not uber-cluttered when you have multiple groups being compared and scores of pairwise comparisons being displayed.
bf.message	Logical that decides whether to display Bayes Factor in favor of the <i>null</i> hypothesis. This argument is relevant only <b>for parametric test</b> (Default: TRUE).
results.subtitle	Decides whether the results of statistical tests are to be displayed as a subtitle (Default: TRUE). If set to FALSE, only the plot will be returned.
subtitle	The text for the plot subtitle. Will work only if results.subtitle = FALSE.
caption	The text for the plot caption. This argument is relevant only if bf.message = FALSE.
centrality.plotting	Logical that decides whether centrality tendency measure is to be displayed as a point with a label (Default: TRUE). Function decides which central tendency measure to show depending on the type argument.

- **mean** for parametric statistics
- **median** for non-parametric statistics
- **trimmed mean** for robust statistics
- **MAP estimator** for Bayesian statistics

If you want default centrality parameter, you can specify this using `centrality.type` argument.

`centrality.type` Decides which centrality parameter is to be displayed. The default is to choose the same as `type` argument. You can specify this to be:

- "parameteric" (for **mean**)
- "nonparametric" (for **median**)
- robust (for **trimmed mean**)
- bayes (for **MAP estimator**)

Just as `type` argument, abbreviations are also accepted.

`point.args` A list of additional aesthetic arguments to be passed to the `geom_point` displaying the raw data.

`violin.args` A list of additional aesthetic arguments to be passed to the `geom_violin`.

`ggplot.component` A ggplot component to be added to the plot prepared by `{ggstatsplot}`. This argument is primarily helpful for grouped\_ variants of all primary functions. Default is NULL. The argument should be entered as a `{ggplot2}` function or a list of `{ggplot2}` functions.

`package,palette` Name of the package from which the given palette is to be extracted. The available palettes and packages can be checked by running `View(paletteer::palettes_d_names)`.

`centrality.point.args,centrality.label.args` A list of additional aesthetic arguments to be passed to `geom_point` and `ggrepel::geom_label_repel` geoms, which are involved in mean plotting.

`ggsignif.args` A list of additional aesthetic arguments to be passed to `ggsignif::geom_signif`.

`ggtheme` A `{ggplot2}` theme. Default value is `ggstatsplot::theme_ggstatsplot()`.

Any of the `{ggplot2}` themes (e.g., `theme_bw()`), or themes from extension packages are allowed (e.g., `ggthemes::theme_fivethirtyeight()`, `hrbrthemes::theme_ipsum_ps()`, etc.). But note that sometimes these themes will remove some of the details that `{ggstatsplot}` plots typically contains. For example, if relevant, `ggbetweenstats()` shows details about multiple comparison test as a label on the secondary Y-axis. Some themes (e.g. `ggthemes::theme_fivethirtyeight()`) will remove the secondary Y-axis and thus the details as well.

`x` The grouping (or independent) variable from data. In case of a repeated measures or within-subjects design, if `subject.id` argument is not available or not explicitly specified, the function assumes that the data has already been sorted by such an id by the user and creates an internal identifier. So if your data is **not** sorted, the results *can* be inaccurate when there are more than two levels in `x` and there are NAs present. The data is expected to be sorted by user in subject-1,subject-2, ..., pattern.

`y` The response (or outcome or dependent) variable from data.

`type` A character specifying the type of statistical approach:



- "parametric"
- "nonparametric"
- "robust"
- "bayes"

You can specify just the initial letter.

`k` Number of digits after decimal point (should be an integer) (Default:  $k = 2L$ ).  
`conf.level` Scalar between 0 and 1 (default: 95% confidence/credible intervals, 0.95). If NULL, no confidence intervals will be computed.

`effsize.type` Type of effect size needed for *parametric* tests. The argument can be "eta" (partial eta-squared) or "omega" (partial omega-squared).

`var.equal` a logical variable indicating whether to treat the two variances as being equal. If TRUE then the pooled variance is used to estimate the variance otherwise the Welch (or Satterthwaite) approximation to the degrees of freedom is used.

`bf.prior` A number between 0.5 and 2 (default 0.707), the prior width to use in calculating Bayes factors and posterior estimates. In addition to numeric arguments, several named values are also recognized: "medium", "wide", and "ultrawide", corresponding to  $r$  scale values of 1/2,  $\sqrt{2}/2$ , and 1, respectively. In case of an ANOVA, this value corresponds to scale for fixed effects.

`tr` Trim level for the mean when carrying out robust tests. In case of an error, try reducing the value of `tr`, which is by default set to 0.2. Lowering the value might help.

`nboot` Number of bootstrap samples for computing confidence interval for the effect size (Default:  $100L$ ).

`grouping.var` A single grouping variable.

`plotgrid.args` A list of additional arguments passed to `patchwork::wrap_plots()`, except for `guides` argument which is already separately specified here.

`annotation.args`

A list of additional arguments passed to `patchwork::plot_annotation()`.

## See Also

[ggbetweenstats](#), [ggwithinstats](#), [grouped\\_ggwithinstats](#)

## Examples

```
# for reproducibility
set.seed(123)
library(PMCMRplus) # for pairwise comparisons
library(dplyr, warn.conflicts = FALSE)
library(ggplot2)

# the most basic function call
grouped_ggbetweenstats(
  data = filter(ggplot2::mpg, drv != "4"),
```

```

x = year,
y = hwy,
grouping.var = drv
)

# modifying individual plots using `ggplot.component` argument
grouped_ggbetweenstats(
  data = filter(
    movies_long,
    genre %in% c("Action", "Comedy"),
    mpaa %in% c("R", "PG")
  ),
  x = genre,
  y = rating,
  grouping.var = mpaa,
  ggplot.component = scale_y_continuous(
    breaks = seq(1, 9, 1),
    limits = c(1, 9)
  )
)

```

---

grouped_ggcorrmat	<i>Visualization of a correlalogram (or correlation matrix) for all levels of a grouping variable</i>
-------------------	---

---

## Description

Helper function for `ggstatsplot::ggcorrmat()` to apply this function across multiple levels of a given factor and combining the resulting plots using `ggstatsplot::combine_plots()`.

## Usage

```

grouped_ggcorrmat(
  data,
  ...,
  grouping.var,
  plotgrid.args = list(),
  annotation.args = list()
)

```

## Arguments

<code>data</code>	A data frame from which variables specified are to be taken.
<code>...</code>	Arguments passed on to <a href="#">ggcorrmat</a>
<code>cor.vars</code>	List of variables for which the correlation matrix is to be computed and visualized. If NULL (default), all numeric variables from <code>data</code> will be used.

- `cor.vars.names` Optional list of names to be used for `cor.vars`. The names should be entered in the same order.
- `partial` Can be TRUE for partial correlations. For Bayesian partial correlations, "full" instead of pseudo-Bayesian partial correlations (i.e., Bayesian correlation based on frequentist partialization) are returned.
- `matrix.type` Character, "upper" (default), "lower", or "full", display full matrix, lower triangular or upper triangular matrix.
- `sig.level` Significance level (Default: 0.05). If the  $p$ -value in  $p$ -value matrix is bigger than `sig.level`, then the corresponding correlation coefficient is regarded as insignificant and flagged as such in the plot.
- `colors` A vector of 3 colors for low, mid, and high correlation values. If set to NULL, manual specification of colors will be turned off and 3 colors from the specified palette from package will be selected.
- `pch` Decides the point shape to be used for insignificant correlation coefficients (only valid when `insig = "pch"`). Default: `pch = "cross"`.
- `ggcorrplot.args` A list of additional (mostly aesthetic) arguments that will be passed to `ggcorrplot::ggcorrplot()` function. The list should avoid any of the following arguments since they are already internally being used: `corr`, `method`, `p.mat`, `sig.level`, `ggtheme`, `colors`, `lab`, `pch`, `legend.title`, `digits`.
- `type` A character specifying the type of statistical approach:
- "parametric"
  - "nonparametric"
  - "robust"
  - "bayes"
- You can specify just the initial letter.
- `k` Number of digits after decimal point (should be an integer) (Default: `k = 2L`).
- `conf.level` Scalar between 0 and 1 (default: 95% confidence/credible intervals, 0.95). If NULL, no confidence intervals will be computed.
- `tr` Trim level for the mean when carrying out robust tests. In case of an error, try reducing the value of `tr`, which is by default set to 0.2. Lowering the value might help.
- `bf.prior` A number between 0.5 and 2 (default 0.707), the prior width to use in calculating Bayes factors and posterior estimates. In addition to numeric arguments, several named values are also recognized: "medium", "wide", and "ultrawide", corresponding to  $r$  scale values of 1/2,  $\sqrt{2}/2$ , and 1, respectively. In case of an ANOVA, this value corresponds to scale for fixed effects.
- `p.adjust.method` Adjustment method for  $p$ -values for multiple comparisons. Possible methods are: "holm" (default), "hochberg", "hommel", "bonferroni", "BH", "BY", "fdr", "none".
- `subtitle` The text for the plot subtitle. Will work only if `results.subtitle = FALSE`.
- `caption` The text for the plot caption. This argument is relevant only if `bf.message = FALSE`.

- `ggplot.component` A ggplot component to be added to the plot prepared by `{ggstatsplot}`. This argument is primarily helpful for grouped\_ variants of all primary functions. Default is NULL. The argument should be entered as a `{ggplot2}` function or a list of `{ggplot2}` functions.
- `package,palette` Name of the package from which the given palette is to be extracted. The available palettes and packages can be checked by running `View(paletteer::palettes_d_names)`.
- `ggtheme` A `{ggplot2}` theme. Default value is `ggstatsplot::theme_ggstatsplot()`. Any of the `{ggplot2}` themes (e.g., `theme_bw()`), or themes from extension packages are allowed (e.g., `ggthemes::theme_fivethirtyeight()`, `hrbrthemes::theme_ipsum_ps()`, etc.). But note that sometimes these themes will remove some of the details that `{ggstatsplot}` plots typically contains. For example, if relevant, `ggbetweenstats()` shows details about multiple comparison test as a label on the secondary Y-axis. Some themes (e.g. `ggthemes::theme_fivethirtyeight()`) will remove the secondary Y-axis and thus the details as well.
- `grouping.var` A single grouping variable.
- `plotgrid.args` A list of additional arguments passed to `patchwork::wrap_plots()`, except for guides argument which is already separately specified here.
- `annotation.args` A list of additional arguments passed to `patchwork::plot_annotation()`.

## Details

For details, see: [https://indrajeetpatil.github.io/ggstatsplot/articles/web\\_only/ggcorrmat.html](https://indrajeetpatil.github.io/ggstatsplot/articles/web_only/ggcorrmat.html)

## See Also

[ggcorrmat](#), [ggscatterstats](#), [grouped\\_ggscatterstats](#)

## Examples

```
# for reproducibility
set.seed(123)
library(ggcorrplot) # for plot

grouped_ggcorrmat(
  data = iris,
  grouping.var = Species,
  type = "robust",
  p.adjust.method = "holm",
  plotgrid.args = list(ncol = 1),
  annotation.args = list(tag_levels = "i")
)
```

---

 grouped\_ggdotplotstats

*Grouped histograms for distribution of a labeled numeric variable*


---

## Description

Helper function for `ggstatsplot::ggdotplotstats` to apply this function across multiple levels of a given factor and combining the resulting plots using `ggstatsplot::combine_plots`.

## Usage

```
grouped_ggdotplotstats(
  data,
  ...,
  grouping.var,
  plotgrid.args = list(),
  annotation.args = list()
)
```

## Arguments

<code>data</code>	A data frame (or a tibble) from which variables specified are to be taken. Other data types (e.g., matrix, table, array, etc.) will <b>not</b> be accepted. Additionally, grouped data frames from <code>{dplyr}</code> should be ungrouped before they are entered as data.
<code>...</code>	Arguments passed on to <a href="#">ggdotplotstats</a>
<code>y</code>	Label or grouping variable.
<code>point.args</code>	A list of additional aesthetic arguments passed to <code>geom_point</code> .
<code>centrality.line.args</code>	A list of additional aesthetic arguments to be passed to the <code>geom_line</code> used to display the lines corresponding to the centrality parameter.
<code>x</code>	A numeric variable from the data frame <code>data</code> .
<code>type</code>	A character specifying the type of statistical approach: <ul style="list-style-type: none"> <li>• "parametric"</li> <li>• "nonparametric"</li> <li>• "robust"</li> <li>• "bayes"</li> </ul> You can specify just the initial letter.
<code>test.value</code>	A number indicating the true value of the mean (Default: 0).
<code>k</code>	Number of digits after decimal point (should be an integer) (Default: <code>k = 2L</code> ).
<code>conf.level</code>	Scalar between 0 and 1 (default: 95% confidence/credible intervals, 0.95). If NULL, no confidence intervals will be computed.
<code>tr</code>	Trim level for the mean when carrying out robust tests. In case of an error, try reducing the value of <code>tr</code> , which is by default set to 0.2. Lowering the value might help.

- `bf.prior` A number between 0.5 and 2 (default 0.707), the prior width to use in calculating Bayes factors and posterior estimates. In addition to numeric arguments, several named values are also recognized: "medium", "wide", and "ultrawide", corresponding to  $r$  scale values of 1/2,  $\sqrt{2}/2$ , and 1, respectively. In case of an ANOVA, this value corresponds to scale for fixed effects.
- `effsize.type` Type of effect size needed for *parametric* tests. The argument can be "d" (for Cohen's  $d$ ) or "g" (for Hedge's  $g$ ).
- `xlab` Label for x axis variable. If NULL (default), variable name for x will be used.
- `bf.message` Logical that decides whether to display Bayes Factor in favor of the *null* hypothesis. This argument is relevant only **for parametric test** (Default: TRUE).
- `results.subtitle` Decides whether the results of statistical tests are to be displayed as a subtitle (Default: TRUE). If set to FALSE, only the plot will be returned.
- `subtitle` The text for the plot subtitle. Will work only if `results.subtitle = FALSE`.
- `caption` The text for the plot caption. This argument is relevant only if `bf.message = FALSE`.
- `centrality.plotting` Logical that decides whether centrality tendency measure is to be displayed as a point with a label (Default: TRUE). Function decides which central tendency measure to show depending on the type argument.
- **mean** for parametric statistics
  - **median** for non-parametric statistics
  - **trimmed mean** for robust statistics
  - **MAP estimator** for Bayesian statistics
- If you want default centrality parameter, you can specify this using `centrality.type` argument.
- `centrality.type` Decides which centrality parameter is to be displayed. The default is to choose the same as type argument. You can specify this to be:
- "parameteric" (for **mean**)
  - "nonparametric" (for **median**)
  - robust (for **trimmed mean**)
  - bayes (for **MAP estimator**)
- Just as type argument, abbreviations are also accepted.
- `ggplot.component` A ggplot component to be added to the plot prepared by `{ggstatsplot}`. This argument is primarily helpful for `grouped_` variants of all primary functions. Default is NULL. The argument should be entered as a `{ggplot2}` function or a list of `{ggplot2}` functions.
- `ggtheme` A `{ggplot2}` theme. Default value is `ggstatsplot::theme_ggstatsplot()`. Any of the `{ggplot2}` themes (e.g., `theme_bw()`), or themes from extension packages are allowed (e.g., `ggthemes::theme_fivethirtyeight()`, `hrbrthemes::theme_ipsum_ps()`, etc.). But note that sometimes these themes will remove some of the details that `{ggstatsplot}` plots typically

contains. For example, if relevant, `ggbetweenstats()` shows details about multiple comparison test as a label on the secondary Y-axis. Some themes (e.g. `ggthemes::theme_fivethirtyeight()`) will remove the secondary Y-axis and thus the details as well.

`ylab` Labels for y axis variable. If NULL (default), variable name for y will be used.

`grouping.var` A single grouping variable.

`plotgrid.args` A list of additional arguments passed to `patchwork::wrap_plots()`, except for `guides` argument which is already separately specified here.

`annotation.args`

A list of additional arguments passed to `patchwork::plot_annotation()`.

## Details

For details, see: [https://indrajeetpatil.github.io/ggstatsplot/articles/web\\_only/ggdotplotstats.html](https://indrajeetpatil.github.io/ggstatsplot/articles/web_only/ggdotplotstats.html)

## See Also

[grouped\\_gghistostats](#), [ggdotplotstats](#), [gghistostats](#)

## Examples

```
# for reproducibility
set.seed(123)
library(dplyr, warn.conflicts = FALSE)

# removing factor level with very few no. of observations
df <- filter(ggplot2::mpg, cyl %in% c("4", "6", "8"))

# plot
grouped_ggdotplotstats(
  data      = df,
  x         = cty,
  y         = manufacturer,
  grouping.var = cyl,
  test.value = 15.5
)
```

---

`grouped_gghistostats` *Grouped histograms for distribution of a numeric variable*

---

## Description

Helper function for `ggstatsplot::gghistostats` to apply this function across multiple levels of a given factor and combining the resulting plots using `ggstatsplot::combine_plots`.

**Usage**

```
grouped_gghistostats(
  data,
  x,
  grouping.var,
  binwidth = NULL,
  plotgrid.args = list(),
  annotation.args = list(),
  ...
)
```

**Arguments**

<code>data</code>	A data frame (or a tibble) from which variables specified are to be taken. Other data types (e.g., matrix, table, array, etc.) will <b>not</b> be accepted. Additionally, grouped data frames from <code>{dplyr}</code> should be ungrouped before they are entered as data.
<code>x</code>	A numeric variable from the data frame <code>data</code> .
<code>grouping.var</code>	A single grouping variable.
<code>binwidth</code>	The width of the histogram bins. Can be specified as a numeric value, or a function that calculates width from <code>x</code> . The default is to use the $\max(x) - \min(x) / \sqrt{N}$ . You should always check this value and explore multiple widths to find the best to illustrate the stories in your data.
<code>plotgrid.args</code>	A list of additional arguments passed to <code>patchwork::wrap_plots()</code> , except for guides argument which is already separately specified here.
<code>annotation.args</code>	A list of additional arguments passed to <code>patchwork::plot_annotation()</code> .
<code>...</code>	Arguments passed on to <code>gghistostats</code>
<code>normal.curve</code>	A logical value that decides whether to super-impose a normal curve using <code>stats::dnorm(mean(x), sd(x))</code> . Default is <code>FALSE</code> .
<code>normal.curve.args</code>	A list of additional aesthetic arguments to be passed to the normal curve.
<code>bin.args</code>	A list of additional aesthetic arguments to be passed to the <code>stat_bin</code> used to display the bins. Do not specify <code>binwidth</code> argument in this list since it has already been specified using the dedicated argument.
<code>centrality.line.args</code>	A list of additional aesthetic arguments to be passed to the <code>geom_line</code> used to display the lines corresponding to the centrality parameter.
<code>type</code>	A character specifying the type of statistical approach: <ul style="list-style-type: none"> <li>• "parametric"</li> <li>• "nonparametric"</li> <li>• "robust"</li> <li>• "bayes"</li> </ul> <p>You can specify just the initial letter.</p>
<code>test.value</code>	A number indicating the true value of the mean (Default: 0).



- `k` Number of digits after decimal point (should be an integer) (Default: `k = 2L`).
- `conf.level` Scalar between 0 and 1 (default: 95% confidence/credible intervals, 0.95). If NULL, no confidence intervals will be computed.
- `tr` Trim level for the mean when carrying out robust tests. In case of an error, try reducing the value of `tr`, which is by default set to 0.2. Lowering the value might help.
- `bf.prior` A number between 0.5 and 2 (default 0.707), the prior width to use in calculating Bayes factors and posterior estimates. In addition to numeric arguments, several named values are also recognized: "medium", "wide", and "ultrawide", corresponding to *r* scale values of 1/2, sqrt(2)/2, and 1, respectively. In case of an ANOVA, this value corresponds to scale for fixed effects.
- `effsize.type` Type of effect size needed for *parametric* tests. The argument can be "d" (for Cohen's *d*) or "g" (for Hedge's *g*).
- `xlab` Label for x axis variable. If NULL (default), variable name for x will be used.
- `bf.message` Logical that decides whether to display Bayes Factor in favor of the *null* hypothesis. This argument is relevant only **for parametric test** (Default: TRUE).
- `results.subtitle` Decides whether the results of statistical tests are to be displayed as a subtitle (Default: TRUE). If set to FALSE, only the plot will be returned.
- `subtitle` The text for the plot subtitle. Will work only if `results.subtitle = FALSE`.
- `caption` The text for the plot caption. This argument is relevant only if `bf.message = FALSE`.
- `centrality.plotting` Logical that decides whether centrality tendency measure is to be displayed as a point with a label (Default: TRUE). Function decides which central tendency measure to show depending on the type argument.
- **mean** for parametric statistics
  - **median** for non-parametric statistics
  - **trimmed mean** for robust statistics
  - **MAP estimator** for Bayesian statistics
- If you want default centrality parameter, you can specify this using `centrality.type` argument.
- `centrality.type` Decides which centrality parameter is to be displayed. The default is to choose the same as type argument. You can specify this to be:
- "parameteric" (for **mean**)
  - "nonparametric" (for **median**)
  - robust (for **trimmed mean**)
  - bayes (for **MAP estimator**)
- Just as type argument, abbreviations are also accepted.
- `ggplot.component` A ggplot component to be added to the plot prepared by {ggstatsplot}. This argument is primarily helpful for grouped\_ variants

of all primary functions. Default is NULL. The argument should be entered as a {ggplot2} function or a list of {ggplot2} functions.

`ggtheme` A {ggplot2} theme. Default value is `ggstatsplot::theme_ggstatsplot()`.

Any of the {ggplot2} themes (e.g., `theme_bw()`), or themes from extension packages are allowed (e.g., `ggthemes::theme_fivethirtyeight()`, `hrbrthemes::theme_ipsum_ps()`, etc.). But note that sometimes these themes will remove some of the details that {ggstatsplot} plots typically contains. For example, if relevant, `ggbetweenstats()` shows details about multiple comparison test as a label on the secondary Y-axis. Some themes (e.g. `ggthemes::theme_fivethirtyeight()`) will remove the secondary Y-axis and thus the details as well.

## Details

For details, see: [https://indrajeetpatil.github.io/ggstatsplot/articles/web\\_only/gghistostats.html](https://indrajeetpatil.github.io/ggstatsplot/articles/web_only/gghistostats.html)

## See Also

[gghistostats](#), [ggdotplotstats](#), [grouped\\_ggdotplotstats](#)

## Examples

```
# for reproducibility
set.seed(123)

# plot
grouped_gghistostats(
  data      = iris,
  x         = Sepal.Length,
  test.value = 5,
  grouping.var = Species,
  plotgrid.args = list(nrow = 1),
  annotation.args = list(tag_levels = "i")
)
```

---

grouped\_ggpiestats      *Grouped pie charts with statistical tests*

---

## Description

Helper function for `ggstatsplot::ggpiestats` to apply this function across multiple levels of a given factor and combining the resulting plots using `ggstatsplot::combine_plots`.

**Usage**

```
grouped_ggpiestats(
  data,
  ...,
  grouping.var,
  plotgrid.args = list(),
  annotation.args = list()
)
```

**Arguments**

**data** A data frame (or a tibble) from which variables specified are to be taken. Other data types (e.g., matrix, table, array, etc.) will **not** be accepted. Additionally, grouped data frames from {dplyr} should be ungrouped before they are entered as data.

**...** Arguments passed on to [ggpiestats](#)

**x** The variable to use as the **rows** in the contingency table. Please note that if there are empty factor levels in your variable, they will be dropped.

**y** The variable to use as the **columns** in the contingency table. Please note that if there are empty factor levels in your variable, they will be dropped. Default is NULL. If NULL, one-sample proportion test (a goodness of fit test) will be run for the x variable. Otherwise an appropriate association test will be run. This argument can not be NULL for ggbarstats function.

**proportion.test** Decides whether proportion test for x variable is to be carried out for each level of y. Defaults to results.subtitle. In ggbarstats, only *p*-values from this test will be displayed.

**perc.k** Numeric that decides number of decimal places for percentage labels (Default: 0L).

**label** Character decides what information needs to be displayed on the label in each pie slice. Possible options are "percentage" (default), "counts", "both".

**label.args** Additional aesthetic arguments that will be passed to geom\_label.

**label.repel** Whether labels should be repelled using ggrepel package. This can be helpful in case the labels are overlapping.

**legend.title** Title text for the legend.

**bf.message** Logical that decides whether to display Bayes Factor in favor of the *null* hypothesis. This argument is relevant only **for parametric test** (Default: TRUE).

**results.subtitle** Decides whether the results of statistical tests are to be displayed as a subtitle (Default: TRUE). If set to FALSE, only the plot will be returned.

**subtitle** The text for the plot subtitle. Will work only if results.subtitle = FALSE.

**caption** The text for the plot caption. This argument is relevant only if bf.message = FALSE.

- `ggplot.component` A ggplot component to be added to the plot prepared by `{ggstatsplot}`. This argument is primarily helpful for grouped\_ variants of all primary functions. Default is NULL. The argument should be entered as a `{ggplot2}` function or a list of `{ggplot2}` functions.
- `package,palette` Name of the package from which the given palette is to be extracted. The available palettes and packages can be checked by running `View(paletteer::palettes_d_names)`.
- `ggtheme` A `{ggplot2}` theme. Default value is `ggstatsplot::theme_ggstatsplot()`. Any of the `{ggplot2}` themes (e.g., `theme_bw()`), or themes from extension packages are allowed (e.g., `ggthemes::theme_fivethirtyeight()`, `hrbrthemes::theme_ipsum_ps()`, etc.). But note that sometimes these themes will remove some of the details that `{ggstatsplot}` plots typically contains. For example, if relevant, `ggbetweenstats()` shows details about multiple comparison test as a label on the secondary Y-axis. Some themes (e.g. `ggthemes::theme_fivethirtyeight()`) will remove the secondary Y-axis and thus the details as well.
- `type` A character specifying the type of statistical approach:
- "parametric"
  - "nonparametric"
  - "robust"
  - "bayes"
- You can specify just the initial letter.
- `k` Number of digits after decimal point (should be an integer) (Default:  $k = 2L$ ).
- `conf.level` Scalar between 0 and 1 (default: 95% confidence/credible intervals, 0.95). If NULL, no confidence intervals will be computed.
- `paired` Logical indicating whether data came from a within-subjects or repeated measures design study (Default: FALSE). If TRUE, McNemar's test expression will be returned. If FALSE, Pearson's chi-square test will be returned.
- `counts` The variable in data containing counts, or NULL if each row represents a single observation.
- `ratio` A vector of proportions: the expected proportions for the proportion test (should sum to 1). Default is NULL, which means the null is equal theoretical proportions across the levels of the nominal variable. This means if there are two levels this will be `ratio = c(0.5, 0.5)` or if there are four levels this will be `ratio = c(0.25, 0.25, 0.25, 0.25)`, etc.
- `sampling.plan` Character describing the sampling plan. Possible options are "indepMulti" (independent multinomial; default), "poisson", "jointMulti" (joint multinomial), "hypergeom" (hypergeometric). For more, see `?BayesFactor::contingencyTable`.
- `fixed.margin` For the independent multinomial sampling plan, which margin is fixed ("rows" or "cols"). Defaults to "rows".
- `prior.concentration` Specifies the prior concentration parameter, set to 1 by default. It indexes the expected deviation from the null hypothesis under the alternative, and corresponds to Gunel and Dickey's (1974) "a" parameter.
- `grouping.var` A single grouping variable.

`plotgrid.args` A list of additional arguments passed to `patchwork::wrap_plots()`, except for `guides` argument which is already separately specified here.

`annotation.args` A list of additional arguments passed to `patchwork::plot_annotation()`.

### Details

For details, see: [https://indrajeetpatil.github.io/ggstatsplot/articles/web\\_only/ggpiestats.html](https://indrajeetpatil.github.io/ggstatsplot/articles/web_only/ggpiestats.html)

### See Also

[ggbarstats](#), [ggpiestats](#), [grouped\\_ggbarstats](#)

### Examples

```
set.seed(123)
# grouped one-sample proportion test
grouped_ggpiestats(mtcars, x = cyl, grouping.var = am)
```

---

`grouped_ggscatterstats`

*Scatterplot with marginal distributions for all levels of a grouping variable*

---

### Description

Grouped scatterplots from `{ggplot2}` combined with marginal distribution plots with statistical details added as a subtitle.

### Usage

```
grouped_ggscatterstats(
  data,
  ...,
  grouping.var,
  plotgrid.args = list(),
  annotation.args = list()
)
```

### Arguments

`data` A data frame (or a tibble) from which variables specified are to be taken. Other data types (e.g., `matrix`, `table`, `array`, etc.) will **not** be accepted. Additionally, grouped data frames from `{dplyr}` should be ungrouped before they are entered as data.

...

Arguments passed on to `ggscatterstats`

`label.var` Variable to use for points labels entered as a symbol (e.g. `var1`).

`label.expression` An expression evaluating to a logical vector that determines the subset of data points to label (e.g. `y < 4 & z < 20`). While using this argument with `purrr::pmap()`, you will have to provide a quoted expression (e.g. `quote(y < 4 & z < 20)`).

`point.label.args` A list of additional aesthetic arguments to be passed to `ggrepel::geom_label_repel` geom used to display the labels.

`smooth.line.args` A list of additional aesthetic arguments to be passed to `geom_smooth` geom used to display the regression line.

`point.args` A list of additional aesthetic arguments to be passed to `geom_point` geom used to display the raw data points.

`marginal` Decides whether marginal distributions will be plotted on axes using `ggside` functions. The default is `TRUE`. The package `ggside` must already be installed by the user.

`point.width.jitter`, `point.height.jitter` Degree of jitter in x and y direction, respectively. Defaults to 0 (0%) of the resolution of the data. Note that the jitter should not be specified in the `point.args` because this information will be passed to two different geoms: one displaying the **points** and the other displaying the **\*labels** for these points.

`xsidehistogram.args`, `ysidehistogram.args` A list of arguments passed to respective `geom_s` from the `{ggside}` package to change the marginal distribution histograms plots.

`x` The column in data containing the explanatory variable to be plotted on the x-axis.

`y` The column in data containing the response (outcome) variable to be plotted on the y-axis.

`type` A character specifying the type of statistical approach:

- "parametric"
- "nonparametric"
- "robust"
- "bayes"

You can specify just the initial letter.

`k` Number of digits after decimal point (should be an integer) (Default: `k = 2L`).

`conf.level` Scalar between 0 and 1 (default: 95% confidence/credible intervals, 0.95). If `NULL`, no confidence intervals will be computed.

`tr` Trim level for the mean when carrying out robust tests. In case of an error, try reducing the value of `tr`, which is by default set to 0.2. Lowering the value might help.

`bf.prior` A number between 0.5 and 2 (default 0.707), the prior width to use in calculating Bayes factors and posterior estimates. In addition to numeric arguments, several named values are also recognized: "medium", "wide", and "ultrawide", corresponding to *r* scale values of 1/2,  $\sqrt{2}/2$ , and 1, respectively. In case of an ANOVA, this value corresponds to scale for fixed effects.

- `xlab` Label for x axis variable. If NULL (default), variable name for x will be used.
- `ylab` Labels for y axis variable. If NULL (default), variable name for y will be used.
- `bf.message` Logical that decides whether to display Bayes Factor in favor of the *null* hypothesis. This argument is relevant only **for parametric test** (Default: TRUE).
- `results.subtitle` Decides whether the results of statistical tests are to be displayed as a subtitle (Default: TRUE). If set to FALSE, only the plot will be returned.
- `subtitle` The text for the plot subtitle. Will work only if `results.subtitle = FALSE`.
- `caption` The text for the plot caption. This argument is relevant only if `bf.message = FALSE`.
- `ggplot.component` A ggplot component to be added to the plot prepared by `{ggstatsplot}`. This argument is primarily helpful for `grouped_` variants of all primary functions. Default is NULL. The argument should be entered as a `{ggplot2}` function or a list of `{ggplot2}` functions.
- `ggtheme` A `{ggplot2}` theme. Default value is `ggstatsplot::theme_ggstatsplot()`. Any of the `{ggplot2}` themes (e.g., `theme_bw()`), or themes from extension packages are allowed (e.g., `ggthemes::theme_fivethirtyeight()`, `hrbrthemes::theme_ipsum_ps()`, etc.). But note that sometimes these themes will remove some of the details that `{ggstatsplot}` plots typically contains. For example, if relevant, `ggbetweenstats()` shows details about multiple comparison test as a label on the secondary Y-axis. Some themes (e.g. `ggthemes::theme_fivethirtyeight()`) will remove the secondary Y-axis and thus the details as well.
- `grouping.var` A single grouping variable.
- `plotgrid.args` A list of additional arguments passed to `patchwork::wrap_plots()`, except for `guides` argument which is already separately specified here.
- `annotation.args`  
A list of additional arguments passed to `patchwork::plot_annotation()`.

## Details

For details, see: [https://indrajeetpatil.github.io/ggstatsplot/articles/web\\_only/ggscatterstats.html](https://indrajeetpatil.github.io/ggstatsplot/articles/web_only/ggscatterstats.html)

## See Also

[ggscatterstats](#), [ggcorrmat](#), [grouped\\_ggcorrmat](#)

## Examples

```
# to ensure reproducibility
set.seed(123)
```

```

library(dplyr, warn.conflicts = FALSE)
library(ggplot2)

# basic function call
grouped_ggscatterstats(
  data      = filter(movies_long, genre == "Comedy" | genre == "Drama"),
  x         = length,
  y         = rating,
  type     = "robust",
  grouping.var = genre,
  ggplot.component = list(geom_rug(sides = "b"))
)

# using labeling
# (also show how to modify basic plot from within function call)
grouped_ggscatterstats(
  data      = filter(ggplot2::mpg, cyl != 5),
  x         = displ,
  y         = hwy,
  grouping.var = cyl,
  type     = "robust",
  label.var = manufacturer,
  label.expression = hwy > 25 & displ > 2.5,
  ggplot.component = scale_y_continuous(sec.axis = dup_axis())
)

# labeling without expression
grouped_ggscatterstats(
  data      = filter(movies_long, rating == 7, genre %in% c("Drama", "Comedy")),
  x         = budget,
  y         = length,
  grouping.var = genre,
  bf.message = FALSE,
  label.var = "title",
  annotation.args = list(tag_levels = "a")
)

```

---

grouped\_ggwithinstats *Violin plots for group or condition comparisons in within-subjects designs repeated across all levels of a grouping variable.*

---

### Description

A combined plot of comparison plot created for levels of a grouping variable.

### Usage

```

grouped_ggwithinstats(
  data,

```



```

    ...,
    grouping.var,
    plotgrid.args = list(),
    annotation.args = list()
  )

```

## Arguments

- data** A data frame (or a tibble) from which variables specified are to be taken. Other data types (e.g., matrix, table, array, etc.) will **not** be accepted. Additionally, grouped data frames from {dplyr} should be ungrouped before they are entered as data.
- ...** Arguments passed on to [ggwithinstats](#)
- point.path, centrality.path** Logical that decides whether individual data points and means, respectively, should be connected using `geom_path`. Both default to TRUE. Note that `point.path` argument is relevant only when there are two groups (i.e., in case of a *t*-test). In case of large number of data points, it is advisable to set `point.path = FALSE` as these lines can overwhelm the plot.
- centrality.path.args, point.path.args** A list of additional aesthetic arguments passed on to `geom_path` connecting raw data points and mean points.
- boxplot.args** A list of additional aesthetic arguments passed on to `geom_boxplot`.
- xlab** Label for x axis variable. If NULL (default), variable name for x will be used.
- ylab** Labels for y axis variable. If NULL (default), variable name for y will be used.
- pairwise.comparisons** Logical that decides whether pairwise comparisons are to be displayed (default: TRUE). Please note that only **significant** comparisons will be shown by default. To change this behavior, select appropriate option with `pairwise.display` argument. The pairwise comparison dataframes are prepared using the `pairwise_comparisons` function. For more details about pairwise comparisons, see the documentation for that function.
- p.adjust.method** Adjustment method for *p*-values for multiple comparisons. Possible methods are: "holm" (default), "hochberg", "hommel", "bonferroni", "BH", "BY", "fdr", "none".
- pairwise.display** Decides *which* pairwise comparisons to display. Available options are:
- "significant" (abbreviation accepted: "s")
  - "non-significant" (abbreviation accepted: "ns")
  - "all"
- You can use this argument to make sure that your plot is not uber-cluttered when you have multiple groups being compared and scores of pairwise comparisons being displayed.

`bf.message` Logical that decides whether to display Bayes Factor in favor of the *null* hypothesis. This argument is relevant only for **parametric test** (Default: TRUE).

`results.subtitle` Decides whether the results of statistical tests are to be displayed as a subtitle (Default: TRUE). If set to FALSE, only the plot will be returned.

`subtitle` The text for the plot subtitle. Will work only if `results.subtitle = FALSE`.

`caption` The text for the plot caption. This argument is relevant only if `bf.message = FALSE`.

`centrality.plotting` Logical that decides whether centrality tendency measure is to be displayed as a point with a label (Default: TRUE). Function decides which central tendency measure to show depending on the type argument.

- **mean** for parametric statistics
- **median** for non-parametric statistics
- **trimmed mean** for robust statistics
- **MAP estimator** for Bayesian statistics

If you want default centrality parameter, you can specify this using `centrality.type` argument.

`centrality.type` Decides which centrality parameter is to be displayed. The default is to choose the same as `type` argument. You can specify this to be:

- "parameteric" (for **mean**)
- "nonparametric" (for **median**)
- robust (for **trimmed mean**)
- bayes (for **MAP estimator**)

Just as `type` argument, abbreviations are also accepted.

`point.args` A list of additional aesthetic arguments to be passed to the `geom_point` displaying the raw data.

`violin.args` A list of additional aesthetic arguments to be passed to the `geom_violin`.

`ggplot.component` A ggplot component to be added to the plot prepared by `{ggstatsplot}`. This argument is primarily helpful for `grouped_` variants of all primary functions. Default is NULL. The argument should be entered as a `{ggplot2}` function or a list of `{ggplot2}` functions.

`package,palette` Name of the package from which the given palette is to be extracted. The available palettes and packages can be checked by running `View(paletteer::palettes_d_names)`.

`centrality.point.args,centrality.label.args` A list of additional aesthetic arguments to be passed to `geom_point` and `ggrepel::geom_label_repel` geoms, which are involved in mean plotting.

`ggsignif.args` A list of additional aesthetic arguments to be passed to `ggsignif::geom_signif`.

`ggtheme` A `{ggplot2}` theme. Default value is `ggstatsplot::theme_ggstatsplot()`. Any of the `{ggplot2}` themes (e.g., `theme_bw()`), or themes from extension packages are allowed (e.g., `ggthemes::theme_fivethirtyeight()`, `hrbrthemes::theme_ipsum_ps()`, etc.). But note that sometimes these

themes will remove some of the details that `{ggstatsplot}` plots typically contains. For example, if relevant, `ggbetweenstats()` shows details about multiple comparison test as a label on the secondary Y-axis. Some themes (e.g. `ggthemes::theme_fivethirtyeight()`) will remove the secondary Y-axis and thus the details as well.

`x` The grouping (or independent) variable from data. In case of a repeated measures or within-subjects design, if `subject.id` argument is not available or not explicitly specified, the function assumes that the data has already been sorted by such an id by the user and creates an internal identifier. So if your data is **not** sorted, the results *can* be inaccurate when there are more than two levels in `x` and there are NAs present. The data is expected to be sorted by user in `subject-1,subject-2, ..., pattern`.

`y` The response (or outcome or dependent) variable from data.

`type` A character specifying the type of statistical approach:

- "parametric"
- "nonparametric"
- "robust"
- "bayes"

You can specify just the initial letter.

`k` Number of digits after decimal point (should be an integer) (Default: `k = 2L`).

`conf.level` Scalar between 0 and 1 (default: 95% confidence/credible intervals, 0.95). If NULL, no confidence intervals will be computed.

`effsize.type` Type of effect size needed for *parametric* tests. The argument can be "eta" (partial eta-squared) or "omega" (partial omega-squared).

`bf.prior` A number between 0.5 and 2 (default 0.707), the prior width to use in calculating Bayes factors and posterior estimates. In addition to numeric arguments, several named values are also recognized: "medium", "wide", and "ultrawide", corresponding to *r* scale values of 1/2,  $\sqrt{2}/2$ , and 1, respectively. In case of an ANOVA, this value corresponds to scale for fixed effects.

`tr` Trim level for the mean when carrying out robust tests. In case of an error, try reducing the value of `tr`, which is by default set to 0.2. Lowering the value might help.

`nboot` Number of bootstrap samples for computing confidence interval for the effect size (Default: 100L).

`grouping.var` A single grouping variable.

`plotgrid.args` A list of additional arguments passed to `patchwork::wrap_plots()`, except for `guides` argument which is already separately specified here.

`annotation.args`

A list of additional arguments passed to `patchwork::plot_annotation()`.

## See Also

[ggwithinstats](#), [ggbetweenstats](#), [grouped\\_ggbetweenstats](#)

**Examples**

```
# for reproducibility
set.seed(123)
library(dplyr, warn.conflicts = FALSE)
library(ggplot2)

# the most basic function call
grouped_ggwithinstats(
  data      = filter(iris_long, condition %in% c("HDHF", "HDLF")),
  x         = condition,
  y         = sepal.length,
  grouping.var = gender,
  type      = "np",
  # additional modifications for each plot using {ggplot2} functions
  ggplot.component = scale_y_continuous(breaks = seq(0, 10, 1), limits = c(0, 10))
)
```

---

iris\_long

*Edgar Anderson's Iris Data in long format.*


---

**Description**

Edgar Anderson's Iris Data in long format.

**Usage**

```
iris_long
```

**Format**

A data frame with 600 rows and 5 variables

- `id`. Dummy identity number for each flower (150 flowers in total).
- `Species`. The species are *Iris setosa*, *versicolor*, and *virginica*.
- `condition`. Factor giving a detailed description of the attribute (Four levels: "Petal.Length", "Petal.Width", "Sepal.Length", "Sepal.Width").
- `attribute`. What attribute is being measured ("Sepal" or "Petal").
- `measure`. What aspect of the attribute is being measured ("Length" or "Width").
- `value`. Value of the measurement.

**Details**

This famous (Fisher's or Anderson's) iris data set gives the measurements in centimeters of the variables sepal length and width and petal length and width, respectively, for 50 flowers from each of 3 species of iris. The species are *Iris setosa*, *versicolor*, and *virginica*.

This is a modified dataset from `{datasets}` package.

**Examples**

```
dim(iris_long)
head(iris_long)
dplyr::glimpse(iris_long)
```

---

movies_long	<i>Movie information and user ratings from IMDB.com (long format).</i>
-------------	--

---

**Description**

Movie information and user ratings from IMDB.com (long format).

**Usage**

```
movies_long
```

**Format**

A data frame with 1,579 rows and 8 variables

- title. Title of the movie.
- year. Year of release.
- budget. Total budget (if known) in US dollars
- length. Length in minutes.
- rating. Average IMDB user rating.
- votes. Number of IMDB users who rated this movie.
- mpaa. MPAA rating.
- genre. Different genres of movies (action, animation, comedy, drama, documentary, romance, short).

**Details**

Modified dataset from {ggplot2movies} package.

The internet movie database, <https://imdb.com/>, is a website devoted to collecting movie data supplied by studios and fans. It claims to be the biggest movie database on the web and is run by amazon.

**Source**

<https://CRAN.R-project.org/package=ggplot2movies>

**Examples**

```
dim(movies_long)
head(movies_long)
dplyr::glimpse(movies_long)
```

---

theme_ggstatsplot	<i>Default theme used in {ggstatsplot}</i>
-------------------	--

---

### Description

Common theme used across all plots generated in {ggstatsplot} and *assumed* by the author to be aesthetically pleasing to the user/reader. The theme is a wrapper around theme\_bw().

All {ggstatsplot} functions have a ggtheme parameter that let you choose a different theme.

### Usage

```
theme_ggstatsplot()
```

### Value

A ggplot object with the theme\_ggstatsplot theme overlaid.

### Examples

```
library(ggplot2)

ggplot(mtcars, aes(wt, mpg)) +
  geom_point() +
  theme_ggstatsplot()
```

---

Titanic_full	<i>Titanic dataset.</i>
--------------	-------------------------

---

### Description

Titanic dataset.

### Usage

```
Titanic_full
```

### Format

A data frame with 2201 rows and 5 variables

- id. Dummy identity number for each person.
- Class. 1st, 2nd, 3rd, Crew.
- Sex. Male, Female.
- Age. Child, Adult.
- Survived. No, Yes.

**Details**

This data set provides information on the fate of passengers on the fatal maiden voyage of the ocean liner 'Titanic', summarized according to economic status (class), sex, age and survival.

This is a modified dataset from {`datasets`} package.

**Examples**

```
dim(Titanic_full)
head(Titanic_full)
dplyr::glimpse(Titanic_full)
```

# Index

## \* datasets

- bugs\_long, 3
- bugs\_wide, 4
- iris\_long, 76
- movies\_long, 77
- Titanic\_full, 78

bugs\_long, 3  
bugs\_wide, 4

combine\_plots, 5

extract\_caption (extract\_stats), 6  
extract\_stats, 6  
extract\_subtitle (extract\_stats), 6

ggbarstats, 7, 39, 52, 54, 69  
ggbetweenstats, 13, 50, 55, 57, 75  
ggcoefstats, 20  
ggcorrmat, 24, 43, 58, 60, 71  
ggdotplotstats, 27, 35, 61, 63, 66  
gghistostats, 31, 31, 63, 64, 66  
ggpiestats, 12, 35, 54, 67, 69  
ggscatterstats, 27, 39, 60, 70, 71  
ggwithinstats, 20, 43, 57, 73, 75  
grouped\_ggbarstats, 12, 39, 51, 69  
grouped\_ggbetweenstats, 20, 50, 54, 75  
grouped\_ggcorrmat, 27, 43, 58, 71  
grouped\_ggdotplotstats, 31, 35, 61, 66  
grouped\_gghistostats, 31, 35, 63, 63  
grouped\_ggpiestats, 12, 39, 54, 66  
grouped\_ggscatterstats, 27, 43, 60, 69  
grouped\_ggwithinstats, 20, 50, 57, 72

iris\_long, 76

movies\_long, 77

theme(legend.position=...), 5  
theme\_ggstatsplot, 78  
Titanic\_full, 78