

Package ‘hydReng’

November 16, 2025

Type Package

Title Hydraulic Engineering Tools

Version 1.0.0

Description The 'hydReng' package provides a set of functions for hydraulic engineering tasks and natural hazard assessments. It includes basic hydraulics (wetted area, wetted perimeter, flow, flow velocity, flow depth, and maximum flow) for open channels with arbitrary geometry under uniform flow conditions. For structures such as circular pipes, weirs, and gates, the package includes calculations for pressure flow, backwater depth, and overflow over a weir crest. Additionally, it provides formulas for calculating bedload transport. The formulas used can be found in standard literature on hydraulics, such as Bollrich (2019, ISBN:978-3-410-29169-5) or Hager (2011, ISBN:978-3-642-77430-0).

License GPL-3

Encoding UTF-8

RoxygenNote 7.3.3

URL <https://github.com/NiccoloGalatioto/hydReng>

BugReports <https://github.com/NiccoloGalatioto/hydReng/issues>

Suggests testthat (>= 3.0.0)

Imports methods

NeedsCompilation no

Author Galatioto Niccolo [cre, aut],
Bühlmann Marius [aut],
HOLINGER AG [cph, fnd]

Maintainer Galatioto Niccolo <niccolo.galatioto@gmail.com>

Repository CRAN

Date/Publication 2025-11-16 17:00:02 UTC

Contents

bedload_MPM	2
bedload_SJ	3

block_size	4
CSarbitrary-class	6
CScircle-class	6
d_aequiv	7
filterlayer	7
flow	8
flow_depth	9
flow_depth_gate	10
flow_depth_weir	11
flow_gate	12
flow_max	13
flow_max_freeboard	14
flow_velocity	15
flow_weir	16
freeboard	17
froude_number	18
mean_roughness	18
par_fill	19
pressflow	20
pressflow_depth	21
pressflow_depth_sub	22
scour_curve	23
scour_groyne	24
scour_horz	26
scour_vert	28
shear_str	29
wetted_area	30
wetted_perimeter	31
wt_sup	32
Index	33

bedload_MPM	<i>Bedload Transport Capacity (Meyer-Peter Müller)</i>
-------------	--

Description

Calculates the bedload transport capacity using the formula by Meyer-Peter Müller. The formula is valid for bed slopes less than 0.005.

Usage

bedload_MPM(dm, J, Rs, B, f_kSt = 0.85, t_crit = 0.047, rho_s = 2650, s = 2.65)

Arguments

dm	Median grain size [m].
J	Bottom slope [-].
Rs	Hydraulic radius [m].
B	Bottom width [m].
f_kSt	Friction factor = $(k_{StS} / k_{Str})^{(3/2)}$ (default: 0.85).
t_crit	Critical shear stress [-] (default: 0.047).
rho_s	Density of bedload material [kg/m ³] (default: 2650).
s	Relative solid density [-] (default: 2.65).

Value

Returns the bedload transport rate [kg/s].

References

Bezzola, G.R. (2012). Vorlesungsmanuskript Flussbau. ETH Zürich, Versuchsanstalt für Wasserbau, Hydrologie und Glaziologie VAW.

Examples

```
bedload_MPM(dm = 0.1, J = 0.01, Rs = 1.5, B = 20)
bedload_MPM(dm = 0.1, J = 0.01, Rs = 1.5, B = 20, t_crit = 0.06)
```

bedload_SJ	<i>Bedload Transport Capacity (Smart and Jaeggi)</i>
------------	--

Description

Calculates the bedload transport capacity based on the formula by Smart and Jaeggi (1983). This formula is recommended for slopes between 0.005 and 0.2.

Usage

```
bedload_SJ(d30, dm, d90, J, Rs, um, B, t_crit = 0.05, rho_s = 2650,
s_value = 2.65)
```

Arguments

d30	Grain size distribution parameter [m].
dm	Median grain size [m].
d90	Grain size distribution parameter [m].
J	Bottom slope [-].
Rs	Hydraulic radius [m].
um	Mean flow velocity [m/s].
B	Bottom width [m].
t_crit	Critical shear stress [-] (default: 0.05).
rho_s	Density of bedload material [kg/m3] (default: 2650).
s_value	Relative solid density [-] (default: 2.65).

Value

bedload_SJ returns the bedload transport rate [kg/s]

References

Smart, G. M., & Jäggi, M. N. R. (1983). Sediment transport in steilen Gerinnen. Mitteilungen der Versuchsanstalt für Wasserbau, Hydrologie und Glaziologie der ETH Zürich, 64, Zürich.

Examples

```
d30 <- 0.05
dm <- 0.1
d90 <- 0.2
J <- 0.03
Rs <- 1
um <- 2
B <- 3

bedload_SJ(d30 = 0.05, dm = 0.10, d90 = 0.2, J = 0.03, Rs = 1, um = 2, B = 5)
```

block_size

Calculate dimensions of rip rap block size

Description

Calculates the dimensions and mass of a rip rap block based on slope geometry, water table levels, and material properties.

Usage

```
block_size(h, h_z, J, gamma, psi, geo = NULL, S = 1.15, Theta_c = 0.047,
  s = 2.65, ret = "all")
```

Arguments

h	Numeric. Global maximum water table level above riverbed [m].
h_z	Numeric. Local water table level above the regarded block [m].
J	Numeric. Bottom slope [-].
gamma	Numeric or NULL. Angle of bank slope [degrees]. Use NULL if specifying geo.
psi	Numeric. Inner friction angle [degrees]. Values between 50 and 55 are recommended (Bezzola 2012).
geo	Numeric vector of length 2 or NULL. Slope geometry as a triangle: c(vertical length, horizontal length) [-]. If given, gamma is ignored.
S	Numeric. Safety factor, default is 1.15 [-].
Theta_c	Numeric. Shear stress parameter, default is 0.047 [-].
s	Numeric. Relative density of blocks, default is 2.65 [-].
ret	Character. Result to return: "all" (default), "D", or "b".

Value

If ret = "all", returns a list with:

D	Diameter of block [m]
m	Mass of block [kg]
a	a-axis length [m]
b	b-axis length [m]
c	c-axis length [m]

Otherwise returns the requested single value:

- "D" Diameter of block [m]
- "b" b-axis length [m]

References

Bezzola (2012). Flussbau, Vorlesungsmanuskript, ETH Zuerich

Examples

```
# Calculate block size at bottom of slope with given slope angle
block_size(h = 5, h_z = 5, J = 0.0015, gamma = 33.69, psi = 50)

# Calculate block size with slope geometries 2:3
block_size(h = 5, h_z = 5, J = 0.0015, gamma = NULL, psi = 50, geo = c(2, 3))

# Calculate block size at middle of slope with slope geometries 2:3
block_size(h = 5, h_z = 2.5, J = 0.0015, gamma = NULL, psi = 50, geo = c(2, 3))
```

CSarbitrary-class	<i>CSarbitrary Class</i>
-------------------	--------------------------

Description

Defines a cross-section class with arbitrary geometry for hydraulic calculations. For single open channels only, avoid geometries with multiple channels.

Slots

x A numeric vector of x-coordinates [m].
 z A numeric vector of z-coordinates [m].
 xb_l x-coordinate of the left bank bottom [m].
 xb_r x-coordinate of the right bank bottom [m].
 kSt_B Roughness of the channel bed [$m^{1/3}/s$].
 kSt_l Roughness of the left bank [$m^{1/3}/s$].
 kSt_r Roughness of the right bank [$m^{1/3}/s$].

Examples

```
# Define sample cross-section data
x <- c(0, 4, 9, 13)
z <- c(2, 0, 0, 2)
cs <- new("CSarbitrary", x = x, z = z, xb_l = 4, xb_r = 9,
          kSt_B = 35, kSt_l = 45, kSt_r = 45)
```

CScircle-class	<i>CScircle Class</i>
----------------	-----------------------

Description

Defines a cross-section class with circular geometry for hydraulic calculations.

Slots

Di Diameter of the pipe [m].
 kSt Roughness of the pipe according to Strickler [$m^{1/3}/s$].
 ks Roughness of the pipe according to Prandtl-Colebrook-White [mm] (SIA 190)

Examples

```
csC <- CScircle(Di = 1, kSt = 75)
csC <- CScircle(Di = 1, ks = 1.5)
```

`d_aequiv`*Equivalent Hydraulic Diameter*

Description

Calculates the equivalent hydraulic diameter of a rectangular cross-section given its width and height.

Usage

```
d_aequiv(b, h)
```

Arguments

b	Width of the rectangle [m].
h	Height of the rectangle [m].

Value

The equivalent hydraulic diameter [m].

Examples

```
d_aequiv(b = 2, h = 1)
```

`filterlayer`*Calculate grain size distribution of a filter layer*

Description

Tool to calculate the range of the grain size distribution of a filter layer.

Usage

```
filterlayer(  
  d15B,  
  d50B,  
  d15U,  
  d50U,  
  d85U,  
  dmax = 400,  
  plot = TRUE,  
  fuller = FALSE  
)
```

Arguments

d15B	Numeric. d15 of block [mm].
d50B	Numeric. d50 of block [mm].
d15U	Numeric. d15 of soil [mm].
d50U	Numeric. d50 of soil [mm].
d85U	Numeric. d85 of soil [mm].
dmax	Numeric. Maximum grain diameter of filter layer [mm].
plot	Logical. If TRUE, the results are plotted (default is TRUE).
fuller	Logical. If TRUE, adds curves of Fuller distributions with exponents $0.5 < q < 1.5$ to the plot. For an ideal grain size distribution, q is estimated as 0.5 (default is FALSE).

Value

A list with the following components:

d15min	Minimum d15 of filter layer [mm].
d15max	Maximum d15 of filter layer [mm].
d50min	Minimum d50 of filter layer [mm].
d50max	Maximum d50 of filter layer [mm].
d85min	Minimum d85 of filter layer [mm].

Examples

```
# Calculate range of the grain size distribution
filterlayer(1000, 1500, 5, 10, 20, 400)

# Calculate range of the grain size distribution and add Fuller curves
filterlayer(1000, 1500, 5, 10, 20, 400, fuller = TRUE)
```

flow	<i>Flow</i>
------	-------------

Description

Calculates the discharge of a CSarbitrary or CScircle object for a given flow depth and bottom slope under uniform flow conditions.

Usage

```
flow(object, h, J, method = "Strickler", ret = "all", plot = FALSE)
```

Arguments

object	A CSarbitrary or CScircle object.
h	Flow depth [m].
J	Bottom slope [-].
method	Method to calculate the roughness. Allowed are "Strickler" (equal roughness) "Einstein" (mean roughness) and "Prandtl-Coolebrook-White".
ret	Defines the result returned by the function.
plot	Logical; if 'TRUE', plots the results.

Value

A list containing the following hydraulic variables:

Q Discharge [m³/s].

v Flow velocity [m/s].

kSt_m Mean roughness [m^{1/3}/s] (if method = "Einstein").

A Wetted area [m²].

Examples

```
# Example for CSarbitrary object
x <- c(0, 4, 9, 13)
z <- c(2, 0, 0, 2)
cs <- CSarbitrary(
  x = x, z = z, xb_l = 4, xb_r = 9,
  kSt_B = 35, kSt_l = 45, kSt_r = 45
)
flow(cs, h = 2, J = 0.0001, method = "Einstein", ret = "Q")
flow(cs, h = 2, J = 0.0001, method = "Einstein", plot = TRUE)

# Example for CScircle object
csC <- CScircle(Di = 0.7, ks = 1.5, kSt = 75)
flow(csC, h = 0.46, J = 0.004)
flow(csC, h = 0.46, J = 0.004, method = "Prandtl-Coolebrook-White", plot = TRUE)
```

flow_depth

Flow Depth

Description

Calculates the flow depth of a CSarbitrary or CScircle object for a given discharge and bottom slope under uniform flow conditions.

Usage

```
flow_depth(object, Q, J, method = "Strickler", ret = "all", plot = FALSE)
```

Arguments

object	A CSarbitrary or CScircle object.
Q	Discharge [m ³ /s].
J	Bottom slope [-].
method	Method to calculate the roughness. Allowed are "Strickler" (equal roughness) "Einstein" (mean roughness) and "Prandtl-Coolebrook-White".
ret	Defines the result returned by the function.
plot	Logical; if 'TRUE', plots the results.

Value

A list containing the following hydraulic variables:

h Flow depth [m].

v Flow velocity [m/s].

Fr Froude number [-].

kSt_m Mean roughness [m^(1/3)/s] (if method = "Einstein").

A Wetted area [m²].

P Wetted perimeter [m].

Examples

```
# Example for CSarbitrary object
x <- c(0, 4, 9, 13)
z <- c(2, 0, 0, 2)
cs <- CSarbitrary(
  x = x, z = z, xb_l = 4, xb_r = 9,
  kSt_B = 35, kSt_l = 45, kSt_r = 45
)
flow_depth(cs, Q = 8.677, J = 0.0001, method = "Einstein", ret = "h")
flow_depth(cs, Q = 8.677, J = 0.0001, method = "Einstein", plot = TRUE)

# Example for CScircle object
csC <- CScircle(Di = 0.7, ks = 1.5, kSt = 75)
flow_depth(csC, Q = 0.46, J = 0.004)
flow_depth(csC, Q = 0.46, J = 0.004, method = "Prandtl-Coolebrook-White", plot = TRUE)
```

flow_depth_gate

Water Depth Upstream Of Gate

Description

Calculates the upstream water depth for a gate based on given discharge and gate parameters.

Usage

```
flow_depth_gate(a, Q, B, alpha, h2 = NULL, ret = "h0")
```

Arguments

a	Gate opening height [m].
Q	Discharge [m ³ /s].
B	Gate width [m].
alpha	Gate angle from horizontal [degrees].
h2	Optional. Downstream water depth [m]. Default is NULL (free flow).
ret	Specifies the return value. "h0" for depth only or "all" for all intermediate results.

Value

A list containing the following hydraulic variables:

h0 Upstream water depth [m].
psi Contraction coefficient [-].
mu Discharge coefficient [-].
v Flow velocity [m/s].

Examples

```
flow_depth_gate(a = 0.5, Q = 2.5, B = 2.0, alpha = 90)
flow_depth_gate(a = 0.5, Q = 2.5, B = 2.0, alpha = 90, h2 = 0.8)
flow_depth_gate(a = 0.5, Q = 2.5, B = 2.0, alpha = 90, h2 = 0.8, ret = "all")
```

flow_depth_weir	<i>Flow Depth At Weir Crest</i>
-----------------	---------------------------------

Description

Calculates the height difference between the upstream water level and the weir crest.

Usage

```
flow_depth_weir(B, Q, w = Inf, mu = 0.73)
```

Arguments

B	Width of the weir [m].
Q	Flow rate [m ³ /s].
w	Height of the weir crest (upstream) [m]. If w = Inf, the upstream velocity is considered 0.
mu	Discharge coefficient [-]. Default is 0.73.

Value

A list with the following components:

h Flow depth over the weir [m].

v Flow velocity [m/s].

Examples

```
flow_depth_weir(B = 3, Q = 5)
flow_depth_weir(B = 3, Q = 5, w = 1)
```

flow_gate	<i>Discharge At Underflow Gate</i>
-----------	------------------------------------

Description

Calculates the discharge through a gate under free or submerged conditions.

Usage

```
flow_gate(a, h0, B, alpha, h2 = NULL, ret = "Q")
```

Arguments

a	Gate opening height [m].
h0	Upstream water depth [m].
B	Gate width [m].
alpha	Gate angle from horizontal [degrees].
h2	Optional. Downstream water depth [m]. Default is NULL (free flow).
ret	Specifies the return value. "Q" for discharge only or "all" for all intermediate results.

Value

A list containing the following hydraulic variables:

Q Flow [m³/s].

psi Contraction coefficient [-].

mu Discharge coefficient [-].

v Flow velocity [m/s].

chi Coefficient for submerged flow [-].

Examples

```
flow_gate(a = 0.5, h0 = 1.0, B = 2.0, alpha = 90)
flow_gate(a = 0.5, h0 = 1.0, B = 2.0, alpha = 90, h2 = 0.8)
flow_gate(a = 0.5, h0 = 1.0, B = 2.0, alpha = 90, h2 = 0.8, ret = "all")
```

flow_max	<i>Maximum Flow</i>
----------	---------------------

Description

Calculates the maximum discharge of a CSarbitrary or CScircle object for a given bottom slope under uniform flow conditions.

Usage

```
flow_max(object, J, method = "Strickler", ret = "all", plot = FALSE)
```

Arguments

object	A CSarbitrary or CScircle object.
J	Bottom slope [-].
method	Method to calculate the roughness. Allowed are "Strickler" (equal roughness) "Einstein" (mean roughness) and "Prandtl-Coolebrook-White".
ret	Defines the result returned by the function.
plot	Logical; if TRUE, plots the results.

Value

A list containing the following hydraulic variables:

Qmax Maximum discharge [m³/s].

hmax Maximum flow depth [m].

v Flow velocity [m/s].

kSt_m Mean roughness [m^{1/3}/s] (if method = "Einstein").

A Wetted area [m²].

Examples

```
# Example for CSarbitrary object
x <- c(0, 4, 9, 13)
z <- c(2, 0, 0, 2)
cs <- CSarbitrary(
  x = x, z = z, xb_l = 4, xb_r = 9,
  kSt_B = 35, kSt_l = 45, kSt_r = 45
)
flow_max(cs, J=0.0001, method="Einstein",ret="Qmax")
flow_max(cs, J=0.0001, method="Einstein",plot=TRUE)

# Example for CScircle object
csC <- CScircle(Di = 0.7, ks = 1.5, kSt = 75)
flow_max(csC, J=0.004)
flow_max(csC, J = 0.004, method = "Prandtl-Coolebrook-White", plot = TRUE)
```

flow_max_freeboard	<i>Maximum Flow Including Freeboard</i>
--------------------	---

Description

Calculates the maximum discharge of a CSarbitrary object including a freebord for a given bottom slope under uniform flow conditions.

Usage

```
flow_max_freeboard(object, J, type = "KOHS", sigma_wz = 0, fw = TRUE, fv = FALSE, ft = 0,
  fe = NULL, fe_min = 0, fe_max = Inf, method = "Strickler",
  ret = "all", plot = FALSE)
```

Arguments

object	A CSarbitrary object.
J	Bottom slope [-].
type	Type of freeboard calculation. Defaults to "KOHS".
sigma_wz	Uncertainty in bed elevation (morphodynamics) [m].
fw	Logical; considers freeboard due to uncertainty in water elevation. If TRUE, calculates according to KOHS; if FALSE, sets fw = 0.
fv	Logical; considers freeboard due to waves. If 'TRUE', calculates according to KOHS; if FALSE, sets fv = 0.
ft	Freeboard due to driftwood based on KOHS (2013) [m].
fe	Fixed freeboard value to override calculations [m].
fe_min	Minimum freeboard [m].
fe_max	Maximum freeboard [m].
method	Method to calculate the roughness. Allowed are "Strickler" (equal roughness) and "Einstein" (mean roughness).
ret	Definition of the result returned by the function ("all", "Qmax", "hmax", "fe", or "v").
plot	Logical; whether to plot the results.

Value

Depending on ret, returns flow, water level, velocity, or all details.

References

KOHS (2013). Freibord bei Hochwasserschutzprojekten und Gefahrenbeurteilungen - Empfehlungen der Kommission Hochwasserschutz KOHS. Wasser Energie Luft 105(1): 43-53.

Examples

```
# Cross section
x <- c(-0.85, 3, 15, 18.85)
z <- c(3.85, 0, 0, 3.85)
cs<- CSarbitrary(x = x, z = z, xb_l = 3, xb_r = 15,
                kSt_B = 45)

# Channel
flow_max_freeboard(cs, sigma_wz = 0.3, fv = FALSE, J = 2.2 * 10^-2)
# Dam
flow_max_freeboard(cs, sigma_wz = 0.3, fv = TRUE, J = 2.2 * 10^-2)
# Bridge
flow_max_freeboard(cs, sigma_wz = 0.3, fv = TRUE, ft = 0.5,
                  J = 2.2 * 10^-2)

# Sensitivity analysis for slope
J <- seq(1, 3, 0.1) * 10^-2
Q <- sapply(J, function(J) {
  flow_max_freeboard(cs, sigma_wz = 0.3, fv = TRUE, ft = 0.5,
                    J = J)$Qmax
})
plot(J, Q, type = "l")
```

flow_velocity

*Flow Velocity***Description**

Calculates the flow velocity of a CSarbitrary or CScircle object for a given water level and bottom slope under uniform flow conditions.

Usage

```
flow_velocity(object, h, J, method = "Strickler", nu = 1.14e-6, ...)
```

Arguments

object	A CSarbitrary or CScircle object.
h	Flow depth [m].
J	Bottom slope [-].
method	Method to calculate the roughness. Allowed are "Strickler" (equal roughness) "Einstein" (mean roughness) and "Prandtl-Colebrook-White".
nu	Kinematic viscosity [m ² /s]. Only for CScircle objects
...	Additional arguments.

Value

Flow velocity [m/s]

Examples

```
# Example for CSarbitrary object
x <- c(0, 4, 9, 13)
z <- c(2, 0, 0, 2)
cs <- CSarbitrary(x = x, z = z, xb_l = 4, xb_r = 9, kSt_B = 35,
                 kSt_l = 45, kSt_r = 45)
flow_velocity(cs, h = 1, J = 0.01, method = "Einstein")

# Example for CScircle object
csC <- CScircle(Di = 0.7, ks = 1.5, kSt = 75)
flow_velocity(csC, h = 0.46, J = 0.004)
flow_velocity(csC, h = 0.46, J = 0.004, method = "Prandtl-Coolbrook-White")
```

flow_weir

Flow Over Weir Crest

Description

Calculates the flow over a weir crest based on upstream water level.

Usage

```
flow_weir(B, h, w = Inf, mu = 0.73)
```

Arguments

B	Width of the weir [m].
h	Height difference between the upstream water level and the weir crest [m].
w	Height of the weir crest (upstream) [m]. If w = Inf, the upstream velocity is considered 0.
mu	Discharge coefficient [-]. Default is 0.73.

Value

A list with the following components:

Q Flow over the weir [m³/s].

v Flow velocity [m/s].

Examples

```
flow_weir(B = 3, h = 1.2)
flow_weir(B = 3, h = 1.2, w = 1)
```

freeboard

Freeboard Calculation

Description

Calculates the required freeboard based on the KOHS (2013) recommendations.

Usage

```
freeboard(v, h, sigma_wz = 0, fw = TRUE, fv = FALSE, ft = 0, min = 0,
          max = Inf, fe_fixed = 0)
```

Arguments

v	Flow velocity [m/s].
h	Flow depth [m].
sigma_wz	Uncertainty in bed elevation (morphodynamics) [m].
fw	Logical; considers freeboard due to uncertainty in water elevation. If 'TRUE', calculates according to KOHS; if 'FALSE', sets 'fw = 0'.
fv	Logical; considers freeboard due to waves. If 'TRUE', calculates according to KOHS; if 'FALSE', sets 'fv = 0'.
ft	Freeboard due to driftwood based on KOHS (2013) [m].
min	Minimum allowable freeboard [m].
max	Maximum allowable freeboard [m].
fe_fixed	Fixed freeboard value to override calculations [m].

Value

A numeric value of the calculated freeboard [m].

References

KOHS (2013). Freibord bei Hochwasserschutzprojekten und Gefahrenbeurteilungen - Empfehlungen der Kommission Hochwasserschutz KOHS. Wasser Energie Luft 105(1): 43-53.

Examples

```
freeboard(h = 1.36, sigma_wz = 0.3, fv = FALSE, ft = 0) # Channel example.
freeboard(v = 4.56, h = 1.36, sigma_wz = 0.3, fv = TRUE, ft = 0) # Dam.
freeboard(v = 4.56, h = 1.36, sigma_wz = 0.3, fv = TRUE, ft = 0.5) # Bridge.
```

froude_number	<i>Froude Number</i>
---------------	----------------------

Description

Calculates the froude number of a CSarbitrary or CScircle object for a given water level and velocity under uniform flow conditions.

Usage

```
froude_number(object, v, h)
```

Arguments

object	A CSarbitrary or CScircle object.
v	Flow velocity [m/s].
h	Flow depth [m].

Value

Froude number [-]

Examples

```
# Example for CSarbitrary object
x <- c(0, 4, 9, 13)
z <- c(2, 0, 0, 2)
cs <- CSarbitrary(x = x, z = z, xb_l = 4, xb_r = 9, kSt_B = 35,
                 kSt_l = 45, kSt_r = 45)
froude_number(cs, h=1, v = 2.5)

# Example for CScircle object
csC <- CScircle(Di = 0.7, ks = 1.5, kSt = 75)
froude_number(csC, h = 0.46, v = 2.5)
```

mean_roughness	<i>Mean Roughness</i>
----------------	-----------------------

Description

Calculates the mean roughness of a CSarbitrary object for a given set of water levels, based on Einstein (1934).

Usage

```
mean_roughness(object, h)
```

Arguments

object A CSarbitrary object.
h A numeric vector of water levels [m].

Value

A numeric vector representing the mean roughness for the given water levels.

Examples

```
# Example usage:
x <- c(0, 4, 9, 13)
z <- c(2, 0, 0, 2)
cs <- CSarbitrary(x = x, z = z, xb_l = 4, xb_r = 9, kSt_B = 35,
                 kSt_l = 45, kSt_r = 45)
h_levels <- c(1, 2) # water levels
mean_roughness(cs, h_levels)
```

par_fill

Partial Filling Flow Diagram

Description

Function to generate a plot of partial-filling diagram of circular pipe with discharge and flow velocity

Usage

```
par_fill(object,J,method="Strickler")
```

Arguments

object A CSCircle object.
J Bottom slope [-].
method Method to calculate the roughness. Allowed are "Strickler" (equal roughness) and "Prandtl-Coolebrook-White".

Value

Plots of a partial filling diagram of a circular pipe with discharge and flow velocity

Examples

```
csC <- CSCircle(Di = 0.7, ks = 1.5, kSt = 75)
par_fill(csC,J=0.04)
```

pressflow	<i>Flow Under Pressure (Bernoulli)</i>
-----------	--

Description

Calculates the flow in a pipe or a rectangle under pressure (Bernoulli). The outlet is not submerged, e.g., the exit loss equals 0.

Usage

```
pressflow(z0, z1, h0, Di=NULL, h = NULL, b = NULL, L, ks=NULL, kst,
          xi_e = 0.5, nu = 1.14e-6, calc_lam = "kst")
```

Arguments

z0	Absolute height of upper gate – upstream of the inlet [m.a.s.l].
z1	Absolute height of the pipe/rectangle vertical middle axis at lower gate [m.a.s.l].
h0	Water depth upstream of the gate – upstream of the inlet [m].
Di	Diameter of pipe [m]. If Di is specified, h and b must be NULL.
h	Height of rectangle [m]. If h is specified, Di must be NULL.
b	Width of rectangle [m]. If b is specified, Di must be NULL.
L	Length of pipe [m].
ks	Equivalent sand roughness [m].
kst	Roughness [$m^{1/3}/s$].
xi_e	Entrance loss [-]. Default = 0.5.
nu	Kinematic viscosity [m^2/s]. Default = 1.14e-6.
calc_lam	Defines if lambda should be calculated with ks or kst.

Value

Pressflow returns the flow under pressure:

Q Discharge [m^3/s].

v Flow velocity [m/s].

Examples

```
# Calculate flow in a pipe under pressure with ks value
pressflow(z0 = 415, z1 = 413, h0 = 3, L = 20, Di = 1, ks = 0.01,
          calc_lam = "ks")

# Calculate flow in rectangle under pressure with kst value
pressflow(z0 = 415, z1 = 413, h0 = 3, L = 20, b = 2, h = 1, kst = 60,
          calc_lam = "kst")
```

pressflow_depth	<i>Backwater Height Upstream A Inlet Under Pressure (Bernoulli)</i>
-----------------	---

Description

Calculates the backwater height upstream of an inlet (pipe or rectangle) under pressure (Bernoulli). The outlet is not submerged, e.g., the exit loss equals 0.

Usage

```
pressflow_depth(
  z0, z1, Q, Di = NULL, h = NULL, b = NULL, L, ks = NULL, kst,
  xi_e = 0.5, nu = 1.14e-6, calc_lam = "kst"
)
```

Arguments

z0	Absolute height of upper gate – upstream of the inlet [m.a.s.l].
z1	Absolute height of the pipe/rectangle vertical middle axis at lower gate [m.a.s.l].
Q	Flow [m ³ /s].
Di	Diameter of pipe [m]. If Di is specified, h and b must be NULL.
h	Height of rectangle [m]. If h is specified, Di must be NULL.
b	Width of rectangle [m]. If b is specified, Di must be NULL.
L	Length of pipe [m].
ks	Equivalent sand roughness [m].
kst	Roughness [m ^(1/3) /s].
xi_e	Entrance loss [-]. Default = 0.5.
nu	Kinematic viscosity [m ² /s]. Default = 1.14e-6.
calc_lam	Defines if lambda should be calculated with ks or kst.

Value

Returns the backwater height upstream the inlet:

h0 Water depth upstream the inlet [m].

v Flow velocity [m/s].

Examples

```
# Flow in a pipe under pressure with ks value
pressflow_depth(z0 = 415, z1 = 413, Q = 5.18, L = 20, Di = 1,
  ks = 0.01, calc_lam = "ks")

# Flow in a rectangle under pressure with kst value
pressflow_depth(z0 = 415, z1 = 413, Q = 13.7, L = 20, b = 2, h = 1,
  kst = 60, calc_lam = "kst")
```

pressflow_depth_sub *Backwater Height Upstream A Inlet Under Pressure (Bernoulli)*

Description

Calculates the backwater height upstream of an inlet (pipe or rectangle) under pressure (Bernoulli). The outlet is submerged; hence, an exit loss (xi_a) has to be specified.

Usage

```
pressflow_depth_sub(
    z0, z1, Q, h1, v1, Di = NULL, h = NULL, b = NULL, L, ks = NULL, kst, xi_a,
    xi_e = 0.5, nu = 1.14e-6, calc_lam = "kst"
)
```

Arguments

z0	Absolute height of upper gate – upstream of the inlet [m.a.s.l].
z1	Absolute height of the pipe/rectangle vertical middle axis at lower gate [m.a.s.l].
Q	Flow [m ³ /s].
h1	Water depth downstream the outlet [m].
v1	Velocity downstream the outlet [m/s].
Di	Diameter of pipe [m]. If Di is specified, h and b must be NULL.
h	Height of rectangle [m]. If h is specified, Di must be NULL.
b	Width of rectangle [m]. If b is specified, Di must be NULL.
L	Length of pipe [m].
ks	Equivalent sand roughness [m].
kst	Roughness [m ^(1/3) /s].
xi_a	Exit loss, according to Borda-Carnot formula $(1 - A1/A2)^2$ [-].
xi_e	Entrance loss [-]. Default = 0.5.
nu	Kinematic viscosity [m ² /s]. Default = 1.14e-6.
calc_lam	Defines if lambda should be calculated with ks or kst.

Value

Returns the backwater height upstream the inlet:

h0 Water depth upstream the inlet [m].

v Flow velocity [m/s].

Examples

```
# Flow in a pipe under pressure with ks value
pressflow_depth_sub(z0=415,z1=413,Q=5.18,h1=2,v1=4,L=20,Di=1,ks=0.01,
  calc_lam="ks",xi_a=0.5)

# Flow in a rectangle under pressure with kst value
pressflow_depth_sub(z0=415,z1=413,Q=13.7,h1=2,v1=4,L=20,b=2,h=1,kst=60,
  calc_lam="kst",xi_a=0.5)
```

scour_curve	<i>Scour depth in a curve</i>
-------------	-------------------------------

Description

Calculate scour depth formed in a curve.

Usage

```
scour_curve(A,v,Fr,h,J,r,rm,d84,d16,dm=NULL,psi=NULL,method="Peter")
```

Arguments

A	wetted area upstream the curve [m ²]
v	flow velocity upstream the curve [m/s]
Fr	Froude number upstream the curve [-]
h	flow depth in the middle of the river upstream the curve [m]
J	bottom slope [-]
r	curve radius from center to the outer bank bottom [m]
rm	curve radius from center to the middle of the river [m]
d84	d84 of grain size distribution [mm]
d16	d16 of grain size distribution [mm]
dm	d50 of grain size distribution [mm]
psi	inner friction angle[°]. Values between 20° and 25° are recommended for flat rivers ($J \sim 0.0003$). For steeper rivers ($0.0035 < J < 0.007$), values between 35° and 40° are recommended (Bezzola 2012).
method	method to calculate scour depth. valid values are "Peter", "Bridge" or "Kikkawa"

Value

T0	water table at maximal scour depth [m]
S	difference between bed elevation at the middle of the river upstream the curve and the maximal scour depth [m]
val	if val = T, the criterion for method "Peter" is fulfilled

References

Bezzola (2012). Vorlesungsmanuskript Flussbau. ETH Zürich.

Examples

```
## calculate scour depth accordint to Peter

# Define parameter
A <- 135.5
Fr <- 0.52
h <- 3.31
J <- 0.0022
r <- 500
rm <- 530
d16 <- 50
d84 <- 200

scour_curve(
  A = A, Fr = Fr, h = h, J = J, rm = rm, r = r,
  d16 = d16, d84 = d84
)

## calculate scour depth accordint to Bridge

# Define parameter
h <- 3.31
r <- 500
rm <- 530
psi <- 20

scour_curve(h = h, rm = rm, r = r, method = "Bridge", psi = psi)

## calculate scour depth according to Kikkawa

# Define parameter
v <- 2.7
h <- 3.31
J <- 0.0022
r <- 500
rm <- 470
dm <- 80

scour_curve(
  v = v, h = h, J = J, rm = rm, r = r,
  dm = dm, method = "Kikkawa"
)
```

Description

Calculate scour depth formed by a groyne

Usage

```
scour_groyne(v,Fr,B,h,J,L,d16,dm,d84,Ks,delta,Kb=NULL,l=NULL, fs=0,
method="Froehlich",bedload=FALSE)
```

Arguments

v	flow velocity upstream the groyne [m/s]
Fr	Froude number upstream the groyne [-]
B	sole width [m]
h	flow depth upstream the groyne [m]
J	bottom slope [-]
L	length of the groyne (perpendicular to the river) [m]
d16	d16 of grain size distribution [mm]
dm	d50 of grain size distribution [mm]
d84	d84 of grain size distribution [mm]
Ks	shape value according to "Froehlich". values between 0.55 and 1 are recommended.[-]
delta	horizontal angle of the groyne in respect to the river [°]
Kb	shape value according to "Hoffmanns" [-]
l	length of the groyne (parallel to the river)[m]
fs	safety factor [-]
method	method to calculate scour depth. valid values are "Froehlich"
bedload	Consider bedload transportation if bedload =TRUE

Value

T0	water table at maximal scour depth [m]
S	difference between bed elevation at the middle of the river and the maximal scour depth [m]

References

Bezzola (2012). Vorlesungsmanuskript Flussbau. ETH Zürich.

Examples

```
## calculate scour depth accordint to Froehlich without bedload
```

```
v <- 2.7
Fr <- 0.52
h <- 3.31
J <- 0.0022
L <- 5
d16 <- 50
dm <- 80
d84 <- 200
Ks <- 0.82
delta <- 60
```

```
scour_groyne(
  v = v, Fr = Fr, h = h, J = J, L = L,
  d16 = d16, dm = dm, d84 = d84,
  Ks = Ks, delta = delta
)
```

```
## calculate scour depth accordint to Froehlich with bedload
```

```
v <- 2.7
Fr <- 0.52
h <- 3.31
J <- 0.0022
L <- 5
Ks <- 0.82
delta <- 60
```

```
scour_groyne(
  v = v, Fr = Fr, h = h, J = J, L = L,
  d16 = d16, dm = dm, d84 = d84,
  Ks = Ks, delta = delta, bedload = TRUE
)
```

scour_horz

Scour depth and length (horizontal jet)

Description

Calculate scour depth and position (length) formed by horizontal jet

Usage

```
scour_horz(Q,B,h,h_u,d90,W=NULL,a=NULL,mu=NULL,l0=NULL,
method="Eggenberger")
```

Arguments

Q	flow [m ³ /s]
B	channel width [m]
h	difference between upstream and downstream water table [m]
h_u	downstream water table [m]
d90	d90 of grain size distribution [mm]
W	shape value. For free waved jet $w = 15.4$ and for covered waved jet $w = 10.35$. If the parameters a and μ are known, W is calculated in the function and must not be specified
a	gate opening height [m]
μ	contraction value. Values between 0.6 (orthogonal gates) and 0.8 (inclined gates) are recommended [-]
l0	length of fix sole protection downstream the gate [m] (for method Shalash)
method	method to calculate scour depth. valid values are "Eggenberger" or "Shalash". Independet of the chosen method, the position of the scour is calculated according to "Eggenberger".

Value

T0	water table at maximal scour depth [m]
S	maximal scour depth [m]
l1	horizontal distance of maximal scour depth to overfall crest [m]
l2	total horizontal distance of scour depth from overfall crest [m]

References

Bezzola (2012). Vorlesungsmanuskript Flussbau. ETH Zürich.

Examples

```
## calculate scour depth accordint to Eggenberger returing all results
scour_horz(Q = 4, B = 1, h = 5, h_u = 1.76, d90 = 150, a = 1, mu = 0.6)

## calculate scour depth accordint to Eggenberger with given W value
scour_horz(Q = 4, B = 1, h = 5, h_u = 1.76, d90 = 150, W = 15.4)

## calculate scour depth accordint to Shalash with l0=5
scour_horz(
  Q = 4, B = 1, h = 5, h_u = 1.76, d90 = 150,
  method = "Shalash", l0 = 5, a = 1
)
```

scour_vert	<i>Scour depth and length (vertical jet)</i>
------------	--

Description

Calculate scour depth and position (length) formed by vertical jet

Usage

```
scour_vert(
  Q, B, h, h_u, d90, d95, ful_ov, method = "Kolatus", bedload = FALSE
)
```

Arguments

Q	flow [m ³ /s]
B	width of the overfall section [m]
h	difference between upstream and downstream water table [m]
h_u	downstream water table [m]
d90	d90 of grain size distribution [mm]
d95	d95 of grain size distribution [mm]
ful_ov	defines if the overfall is complete or incomplete. TRUE and FALSE are valid values [logical]
method	method to calculate scour depth. valid values are "Kolatus" or "Tschopp". Independent of the chosen method, the position of the scour is calculated according to "Kolatus" and the scour depth considering bedload is calculated according to "Tschopp".
bedload	Consider bedload transportation. If bedload = TRUE, the scour depth "TG" and "SG" are calculated additionally which consider bedload transport.

Value

T0	water table at maximal scour depth [m]
S	maximal scour depth [m]
TG	water table at maximal scour depth considering bedload transport [m]
SG	maximal scour depth considering bedload transport [m]
l1	horizontal distance of maximal scour depth to overfall crest [m]
l2	total horizontal distance of scour depth from overfall crest [m]

References

Bezzola (2012). Vorlesungsmanuskript Flussbau. ETH Zürich.

Examples

```
## calculate scour depth according to Kolatus returning all results
scour_vert(
  Q = 4, B = 1, h = 3, h_u = 1.76, d90 = 150, d95 = 200, ful_ov = TRUE
)

## calculate scour depth according to Tschopp
scour_vert(
  Q = 4, B = 1, h = 3, h_u = 1.76, d90 = 150, d95 = 200,
  method = "Tschopp", ful_ov = TRUE
)$S

## calculate scour depth according to Tschopp considering bedload transport
scour_vert(
  Q = 4, B = 1, h = 3, h_u = 1.76, d90 = 150, d95 = 200,
  method = "Tschopp", bedload = TRUE, ful_ov = TRUE
)$SG
```

shear_str

*Shear stress, shear velocity, and dimensionless shear stress***Description**

Calculates shear stress, shear velocity, and dimensionless shear stress based on water depth, slope, and grain size.

Usage

```
shear_str(h0, J, dm = NULL, h = NULL, rho = 1000)
```

Arguments

h0	Numeric. Total water depth [m].
J	Numeric. Bottom slope [-].
dm	Numeric or NULL. Median grain size (d50) of sediment [mm].
h	Numeric or NULL. Local water depth at the point of interest [m]. If NULL, considered equal to h0.
rho	Numeric. Density of water [kg/m3], default is 1000.

Value

A named list with components:

tau	Shear stress [N/m2].
U	Shear velocity [m/s].
tau_st	Dimensionless shear stress [-], if dm is provided, otherwise NA.

References

Bezzola (2012). Flussbau, Vorlesungsmanuskript, ETH Zuerich

Examples

```
# Calculate shear stress at bank bottom
shear_str(h0 = 3.31, J = 0.0022)$tau

# Calculate shear stress at bank middle
shear_str(h0 = 3.31, J = 0.0022, h = 1.6)$tau

# Calculate dimensionless shear stress
shear_str(h0 = 3.31, J = 0.0022, dm = 100)$tau_st
```

wetted_area	<i>Wetted Area</i>
-------------	--------------------

Description

Calculates the wetted area of a CSarbitrary or CScircle object for given water levels.

Usage

```
wetted_area(object, h, ret = "A")
```

Arguments

object	An object of class CSarbitrary or CScircle.
h	A numeric vector of water levels (m). For CScircle, only a single numeric value is allowed.
ret	A character string. If 'A', returns total wetted area. If 'Aii', returns wetted area by segment.

Value

A numeric vector or matrix of wetted areas based on the 'ret' argument.

Examples

```
# Example for CSarbitrary object
x <- c(0, 4, 9, 13)
z <- c(2, 0, 0, 2)
cs <- CSarbitrary(x = x, z = z, xb_l = 4, xb_r = 9, kSt_B = 35,
                 kSt_l = 45, kSt_r = 45)

# Calculate total wetted area at water levels 1 m and 2 m
h <- c(1, 2)
wetted_area(cs, h, ret = "A")
```

```
# Calculate wetted area for each segment at the same water levels
wetted_area(cs, h, ret = "Aii")

# Example for CScircle object
csC <- CScircle(Di = 1, kSt = 75)

# Calculate total wetted area at water level 1 m
h <- 1
wetted_area(csC, h)
```

wetted_perimeter	<i>Wetted Perimeter</i>
------------------	-------------------------

Description

Calculates the wetted perimeter of a CSarbitrary or CScircle object for given water levels.

Usage

```
wetted_perimeter(object, h, ret = "P")
```

Arguments

object	An object of class CSarbitrary or CScircle.
h	A numeric vector of water levels (m). For CScircle, only a single numeric value is allowed.
ret	A character string. If 'P', returns total wetted perimeter. If 'Pii', returns wetted perimeter by segment.

Value

A numeric vector or matrix of wetted perimeter based on the 'ret' argument.

Examples

```
# Example for CSarbitrary object
x <- c(0, 4, 9, 13)
z <- c(2, 0, 0, 2)
cs <- CSarbitrary(x = x, z = z, xb_l = 4, xb_r = 9, kSt_B = 35,
                 kSt_l = 45, kSt_r = 45)

# Calculate total wetted perimeter at water levels 1 m and 2 m
h <- c(1, 2)
wetted_perimeter(cs, h, ret = "P")

# Calculate wetted perimeter for each segment at the same water levels
wetted_perimeter(cs, h, ret = "Pii")
```

```
# Example for CScircle object
csC <- CScircle(Di = 1, kSt = 75)

# Calculate total wetted perimeter at water level 1 m
h <- 1
wetted_perimeter(csC, h)
```

wt_sup

Superelevation of water table in curve

Description

Calculates the superelevation of the water table in a river curve.

Usage

```
wt_sup(w, rm, v, S = 1.5)
```

Arguments

w	Numeric. Horizontal sole width [m].
rm	Numeric. Curve radius from center to the middle of the river [m].
v	Numeric. Flow velocity [m/s].
S	Numeric. Safety factor, default is 1.5.

Value

Numeric. The difference between mean water level and superelevation [m].

References

Bezzola (2012). Flussbau, Vorlesungsmanuskript, ETH Zuerich

Examples

```
# Calculate superelevation
wt_sup(w = 30, rm = 200, v = 5)
```

Index

bedload_MPM, [2](#)
bedload_SJ, [3](#)
block_size, [4](#)

CSarbitrary (CSarbitrary-class), [6](#)
CSarbitrary-class, [6](#)
CScircle (CScircle-class), [6](#)
CScircle-class, [6](#)

d_aequiv, [7](#)

filterlayer, [7](#)
flow, [8](#)
flow, CSarbitrary-method (flow), [8](#)
flow, CScircle-method (flow), [8](#)
flow_depth, [9](#)
flow_depth, CSarbitrary-method (flow_depth), [9](#)
flow_depth, CScircle-method (flow_depth), [9](#)
flow_depth_gate, [10](#)
flow_depth_weir, [11](#)
flow_gate, [12](#)
flow_max, [13](#)
flow_max, CSarbitrary-method (flow_max), [13](#)
flow_max, CScircle-method (flow_max), [13](#)
flow_max_freeboard, [14](#)
flow_max_freeboard, CSarbitrary-method (flow_max_freeboard), [14](#)
flow_velocity, [15](#)
flow_velocity, CSarbitrary-method (flow_velocity), [15](#)
flow_velocity, CScircle-method (flow_velocity), [15](#)
flow_weir, [16](#)
freeboard, [17](#)
froude_number, [18](#)
froude_number, CSarbitrary-method (froude_number), [18](#)
froude_number, CScircle-method (froude_number), [18](#)
mean_roughness, [18](#)
mean_roughness, CSarbitrary-method (mean_roughness), [18](#)
par_fill, [19](#)
par_fill, CScircle-method (par_fill), [19](#)
pressflow, [20](#)
pressflow_depth, [21](#)
pressflow_depth_sub, [22](#)
scour_curve, [23](#)
scour_groyne, [24](#)
scour_horz, [26](#)
scour_vert, [28](#)
shear_str, [29](#)
wetted_area, [30](#)
wetted_area, CSarbitrary-method (wetted_area), [30](#)
wetted_area, CScircle-method (wetted_area), [30](#)
wetted_perimeter, [31](#)
wetted_perimeter, CSarbitrary-method (wetted_perimeter), [31](#)
wetted_perimeter, CScircle-method (wetted_perimeter), [31](#)
wt_sup, [32](#)