

Package ‘lolog’

October 13, 2022

Maintainer Ian E. Fellows <ian@fellstat.com>

License MIT + file LICENCE

Title Latent Order Logistic Graph Models

LinkingTo Rcpp, BH

Type Package

LazyLoad yes

Description Estimation of Latent Order Logistic (LOLOG) Models for Networks.

LOLOGs are a flexible and fully general class of statistical graph models.

This package provides functions for performing MOM, GMM and variational inference. Visual diagnostics and goodness of fit metrics are provided.

See Fellows (2018) <[arXiv:1804.04583](https://arxiv.org/abs/1804.04583)> for a detailed description of the methods.

Version 1.3

Depends R (>= 4.0.0), methods, Rcpp (>= 0.9.4)

Imports network, parallel, ggplot2, reshape2, intergraph, Matrix

Suggests testthat, inline, knitr, rmarkdown, ergm, BH, igraph

URL <https://github.com/statnet/lolog>

RcppModules lolog

RoxygenNote 7.1.1

VignetteBuilder knitr

NeedsCompilation yes

Author Ian E. Fellows [aut, cre],

Mark S. Handcock [ctb]

Repository CRAN

Date/Publication 2021-07-01 07:50:06 UTC

R topics documented:

as.BinaryNet	...	2
as.BinaryNet.default	...	3

as.network	4
as.network.Rcpp_DirectedNet	4
as.network.Rcpp_UndirectedNet	5
BinaryNet	6
calculateStatistics	6
call-symbols	6
coef.lolog	7
createCppModel	7
createLatentOrderLikelihood	8
gofit	9
gofit.lolog	9
inlineLologPlugin	10
LatentOrderLikelihood	11
lazega	12
lolog	12
lolog-terms	16
LologModels	16
lologPackageSkeleton	16
lologVariational	17
plot.gofit	19
plot.lologGmm	21
plot.Rcpp_DirectedNet	22
plot.Rcpp_UndirectedNet	22
print.gofit	23
print.lolog	23
print.lologVariationalFit	24
registerDirectedStatistic	24
simulate.lolog	24
summary.lolog	25
ukFaculty	26
[.	26

Index**28**

as.BinaryNet*Convert to either an UndirectedNet or DirectedNet object*

Description

Convert to either an UndirectedNet or DirectedNet object

Usage`as.BinaryNet(x, ...)`

Arguments

- x the object
- ... unused

Details

Converts network objects to BinaryNets. This function also converts other graph formats, such as igraph and tidygraph, utilizing intergraph::asNetwork.

Value

either an Rcpp_UndirectedNet or Rcpp_DirectedNet object

Examples

```
data(ukFaculty)
net <- as.BinaryNet(ukFaculty)
net
```

as.BinaryNet.default *Convert to either an UndirectedNet or DirectedNet object*

Description

Convert to either an UndirectedNet or DirectedNet object

Usage

```
## Default S3 method:
as.BinaryNet(x, ...)
```

Arguments

- x the object
- ... unused

Details

Converts network objects to BinaryNets. This function also converts other graph formats, such as igraph and tidygraph, utilizing intergraph::asNetwork.

Value

either an Rcpp_UndirectedNet or Rcpp_DirectedNet object

Examples

```
data(ukFaculty)
net <- as.BinaryNet(ukFaculty)
net
```

`as.network`

Network conversion

Description

Network conversion

Arguments

<code>x</code>	The object
<code>...</code>	Additional parameters

`as.network.Rcpp_DirectedNet`

Convert a DirectedNet to a network object

Description

Convert a DirectedNet to a network object

Usage

```
## S3 method for class 'Rcpp_DirectedNet'
as.network(x, ...)
```

Arguments

<code>x</code>	the object
<code>...</code>	unused

Value

A network object

See Also

[DirectedNet](#)

Examples

```
el <- matrix(c(1,2),ncol=2)

#make an UndirectedNet with one edge and 5 nodes
net <- new(UndirectedNet, el, 5L)

nw <- as.network(net)
nw
```

as.network.Rcpp_UndirectedNet

Convert a UndirectedNet to a network object

Description

Convert a UndirectedNet to a network object

Usage

```
## S3 method for class 'Rcpp_UndirectedNet'
as.network(x, ...)
```

Arguments

x	the object
...	unused

Value

A network object

See Also

[UndirectedNet](#)

Examples

```
el <- matrix(c(1,2),ncol=2)

#make an UndirectedNet with one edge and 5 nodes
net <- new(UndirectedNet, el, 5L)
net[1:5,1:5]

nw <- as.network(net)
nw
```

BinaryNet

*BinaryNet***Description**

BinaryNet

Details

Rcpp_DirectedNet and Rcpp_UndirectedNet are the native network classes for the lolog package. They are designed for algorithmic performance, and are thin wrappers for an underlying C++ object. These network objects can be passed back and forth between R and C++ with little overhead. Because they are pointers to C++ objects, serialization via 'save' or 'dput' are not supported

calculateStatistics

*Calculate network statistics from a formula***Description**

Calculate network statistics from a formula

Usage

calculateStatistics(formula)

Argumentsformula A lolog formula (See [lolog](#)).**Examples**

```
data(ukFaculty)
calculateStatistics(ukFaculty ~ edges + mutual + triangles)
```

call-symbols

*Internal Symbols***Description**

Internal symbols used to access compiles code.

coef.lolog	<i>Extracts estimated model coefficients.</i>
------------	---

Description

Extracts estimated model coefficients.

Usage

```
## S3 method for class 'lolog'  
coef(object, ...)
```

Arguments

object	A 'lolog' object.
...	unused

Examples

```
# Extract parameter estimates as a numeric vector:  
data(ukFaculty)  
fit <- lolog(ukFaculty ~ edges)  
coef(fit)
```

createCppModel	<i>Creates a model</i>
----------------	------------------------

Description

Creates a model

Usage

```
createCppModel(formula, cloneNet = TRUE, theta = NULL)
```

Arguments

formula	the model formula
cloneNet	create a deep copy of the network within the model object
theta	the model parameters.

Details

Creates a C++ Model object. In general this isn't needed by most users of the package.

Examples

```
data(ukFaculty)
model <- createCppModel(ukFaculty ~ edges)
model$calculate()
model$statistics()
```

createLatentOrderLikelihood

Creates a probability model for a latent ordered network model

Description

Creates a probability model for a latent ordered network model

Usage

```
createLatentOrderLikelihood(formula, theta = NULL)
```

Arguments

- | | |
|---------|--|
| formula | A LOLOG formula. See link{lolog} |
| theta | Parameter values. |

Value

An Rcpp object representing the likelihood model

Examples

```
# See the methods of the objects returned by this function
UndirectedLatentOrderLikelihood
DirectedLatentOrderLikelihood

# A Barabasi-Albert type graph model with 1000 vertices
el <- matrix(0, nrow=0, ncol=2)
net <- new(UndirectedNet, el, 1000L)
lolik <- createLatentOrderLikelihood(net ~ preferentialAttachment(), theta=1)
banet <- lolik$generateNetwork()$network # generate a random network from the model
degrees <- banet$degree(1:1000)
hist(degrees, breaks=100) # plot the degree distribution
order <- banet[["__order__"]] # The vertex inclusion order

# Earlier nodes have higher degrees
library(ggplot2)
qplot(order, degrees, alpha=I(.25)) + geom_smooth(method="loess")
```

gofit*Conduct goodness of fit diagnostics*

Description

Conduct goodness of fit diagnostics

Usage

```
gofit(object, ...)
```

Arguments

object	the object to evaluate
...	additional parameters

Details

see [gofit.lolog](#)

gofit.lolog*Goodness of Fit Diagnostics for a LOLOG fit*

Description

Goodness of Fit Diagnostics for a LOLOG fit

Usage

```
## S3 method for class 'lolog'  
gofit(object, formula, nsim = 100, ...)
```

Arguments

object	the object to evaluate
formula	A formula specifying the statistics on which to evaluate the fit
nsim	The number of simulated statistics
...	additional parameters

Examples

```

library(network)
data(ukFaculty)

# Delete vertices missing group
delete.vertices(ukFaculty, which(is.na(ukFaculty %v% "Group")))

# A dyad independent model
fitind <- lolog(ukFaculty ~ edges() + nodeMatch("GroupC") + nodeCov("GroupC"))
summary(fitind)

# Check gof on degree distribution (bad!)
gind <- gofit(fitind, ukFaculty ~ degree(0:50))
gind
plot(gind)

#check gof on esp distribution (bad!)
gind <- gofit(fitind, ukFaculty ~ esp(0:25))
gind
plot(gind)

## Not run:

#include triangles and 2-stars (in and out)
fitdep <- lolog(ukFaculty ~ edges() + nodeMatch("GroupC") + nodeCov("GroupC") +
    triangles + star(2, direction="in") + star(2, direction="out"), nsamp=1500)
summary(fitdep)

# Check gof on (in + out) degree distribution (good!)
gdep <- gofit(fitdep, ukFaculty ~ degree(0:50))
gdep
plot(gdep)

#check gof on esp distribution (good!)
gdep <- gofit(fitdep, ukFaculty ~ esp(0:25))
gdep
plot(gdep)

## End(Not run)

```

Description

An lolog plug-in for easy C++ prototyping and access
The inline plug-in for lolog

Usage

```
inlineLologPlugin( . . . )
inlineLologPlugin
```

Arguments

...	plug-in arguments
-----	-------------------

Details

The lolog Rcpp plugin allows for the rapid prototyping of compiled code. new functions can be registered and exposed using [cppFunction](#) and new statistics can be compiled and registered using [sourceCpp](#).

See Also

[cppFunction](#), [sourceCpp](#), [cppFunction](#)

Examples

```
## Not run:
# This creates a function in C++ to create an empty network of size n
# and expose it to R.
src <- "
lolog::BinaryNet<lolog::Directed> makeEmptyNetwork(const int n){
Rcpp::IntegerMatrix tmp(0,2);
lolog::BinaryNet<lolog::Directed> net(tmp, n);
return net;
}"
Rcpp::registerPlugin("lolog",inlineLologPlugin)
emptyNetwork <- cppFunction(src,plugin="lolog")
net <- emptyNetwork(10L)
net[1:10,1:10]

## End(Not run)
```

Description

LatentOrderLikelihood

lazega*Collaboration Relationships Among Partners at a New England Law Firm*

Description

This data set comes from a network study of corporate law partnership that was carried out in a Northeastern US corporate law firm, referred to as SG&R, 1988-1991 in New England.

Usage

```
data(lazega)
```

Licenses and Citation

CC BY 4.0. When publishing results obtained using this data set, the original authors (Lazega, 2001) should be cited, along with this R package.

Copyright

Creative Commons Attribution-Share Alike 4.0 International License, see <https://creativecommons.org/licenses/by/4.0/> for details.

Source

See http://elazega.fr/?page_id=609 and https://www.stats.ox.ac.uk/~snijders/siena/Lazega_lawyers_data.htm

References

Lazega, Emmanuel (2001), The Collegial Phenomenon: The Social Mechanisms of Cooperation among Peers in a Corporate Law Partnership, Oxford: Oxford University Press

lolog*Fits a LOLOG model via Monte Carlo Generalized Method of Moments*

Description

lolog is used to fit Latent Order Logistic Graph (LOLOG) models. LOLOG models are motivated by the idea of network growth where the network begins empty, and edge variables are sequentially 'added' to the network with an either unobserved, or partially observed order s . Conditional upon the inclusion order, the probability of an edge has a logistic relationship with the change in network statistics.

Usage

```

lolog(
  formula,
  auxFormula = NULL,
  theta = NULL,
  nsamp = 1000,
  includeOrderIndependent = TRUE,
  targetStats = NULL,
  weights = "full",
  tol = 0.1,
  nHalfSteps = 10,
  maxIter = 100,
  minIter = 2,
  startingStepSize = 0.1,
  maxStepSize = 0.5,
  cluster = NULL,
  verbose = TRUE
)

```

Arguments

<code>formula</code>	A lolog formula for the sufficient statistics (see details).
<code>auxFormula</code>	A lolog formula of statistics to use for moment matching.
<code>theta</code>	Initial parameters values. Estimated via lologVariational if NULL.
<code>nsamp</code>	The number of sample networks to draw at each iteration.
<code>includeOrderIndependent</code>	If TRUE, all order independent terms in formula are used for moment matching.
<code>targetStats</code>	A vector of network statistics to use as the target for the moment equations. If NULL, the observed statistics for the network are used.
<code>weights</code>	The type of weights to use in the GMM objective. Either 'full' for the inverse of the full covariance matrix or 'diagonal' for the inverse of the diagonal of the covariance matrix.
<code>tol</code>	The Hotelling's T^2 p-value tolerance for convergence for the transformed moment conditions.
<code>nHalfSteps</code>	The maximum number of half steps to take when the objective is not improved in an iteration.
<code>maxIter</code>	The maximum number of iterations.
<code>minIter</code>	The minimum number of iterations.
<code>startingStepSize</code>	The starting dampening of the parameter update.
<code>maxStepSize</code>	The largest allowed value for dampening.
<code>cluster</code>	A parallel cluster to use for graph simulation.
<code>verbose</code>	Level of verbosity 0-3.

Details

LOLOG represents the probability of a tie, given the network grown up to a time point as

$$\text{logit}(p(y_{s_t} = 1 | \eta, y^{t-1}, s_{\leq t})) = \theta \cdot c(y_{s_t} = 1 | y^{t-1}, s_{\leq t})$$

where $s_{\leq t}$ is the growth order of the network up to time t , y^{t-1} is the state of the graph at time $t - 1$. $c(y_{s_t} | y^{t-1}, s_{\leq t})$ is a vector representing the change in graph statistics from time $t - 1$ to t if an edge is present, and θ is a vector of parameters.

The motivating growth order proceeds 'by vertex.' The network begins 'empty' and then vertices are 'added' to the network sequentially. The order of vertex inclusion may be random or fixed. When a vertex 'enters' the network, each of the edge variables connecting it and vertices already in the network are considered for edge creation in a completely random order.

LOLOG formulas contain a network, DirectedNet or UndirectedNet object on the left hand side. the right hand side contains the model terms used. for example,

`net ~ edges`

represents an Erdos-Renyi model and

`net ~ edges + preferentialAttachment()`

represents a Barabasi-Albert model. See [lolog-terms](#) for a list of allowed model statistics

Conditioning on (partial) vertex order can be done by placing an ordering variable on the right hand side of the '| operator, as in

`net ~ edges + preferentialAttachment() | order`

'order' should be a numeric vector with as many elements as there are vertices in the network. Ties are allowed. Vertices with higher order values will always be included later. Those with the same values will be included in a random order in each simulated network.

offsets and constraints are specified by wrapping them with either `offset()` or `constraint()`, for example, the following specifies an Erdos-Renyi model with the constraint that degrees must be less than 10

`net ~ edges + constraint(boundedDegree(0L, 10L))`

If the model contains any order dependent statistics, additional moment constraints must be specified in `auxFormula`. Ideally these should be chosen to capture the features modeled by the order dependent statistics. For example, `preferentialAttachment` models the degree structure, so we might choose two-stars as a moment constraint.

`lolog(net ~ edges + preferentialAttachment(), net ~ star(2))`

will fit a Barabasi-Albert model with the number of edges and number of two-stars as moment constraints.

Value

An object of class 'lolog'. If the model is dyad independent, the returned object will also be of class "lologVariational" (see [lologVariational](#), otherwise it will also be a "lologGmm" object.

`lologGmm` objects contain:

<code>method</code>	"Method of Moments" for order independent models, otherwise "Generalized Method of Moments"
---------------------	---

formula	The model formula
auxFormula	The formula containing additional moment conditions
theta	The parameter estimates
stats	The statistics for each network in the last iteration
estats	The expected stats ($G(y,s)$) for each network in the last iteration
obsStats	The observed $h(y)$ network statistics
targetStats	The target network statistics
obsModelStats	The observed $g(y,s)$ network statistics
net	A network simulated from the fit model
grad	The gradient of the moment conditions (D)
vcov	The asymptotic covariance matrix of the parameter estimates
likelihoodModel	An object of class *LatentOrderLikelihood at the fit parameters

Examples

```

library(network)
set.seed(1)
data(flo)
flomarriage <- network(flo,directed=FALSE)
flomarriage %v% "wealth" <- c(10,36,27,146,55,44,20,8,42,103,48,49,10,48,32,3)

# A dyad independent model
fit <- lolog(fломарriage ~ edges + nodeCov("wealth"))
summary(fit)

# A dyad dependent model with 2-stars and triangles
fit2 <- lolog(fломарriage ~ edges + nodeCov("wealth") + star(2) + triangles, verbose=FALSE)
summary(fit2)

## Not run:

# An order dependent model
fit3 <- lolog(fломарriage ~ edges + nodeCov("wealth") + preferentialAttachment(),
             flомарriage ~ star(2:3), verbose=FALSE)
summary(fit3)

# Try something a bit more real
data(ukFaculty)

# Delete vertices missing group
delete.vertices(ukFaculty, which(is.na(ukFaculty %v% "Group")))

fituk <- lolog(ukFaculty ~ edges() + nodeMatch("GroupC") + nodeCov("GroupC") + triangles + star(2))
summary(fituk)
plot(fituk$net, vertex.col= ukFaculty %v% "Group" + 2)

```

```
## End(Not run)
```

lolog-terms*LOLOG Model Terms***Description**

LOLOG Model Terms

NA

- `boundedDegree(lower,upper)` (order-independent) (undirected) Adds a constraint that the degrees for the network must be between lower and upper.

Constraint Descriptions

- `boundedDegree(lower,upper)` (order-independent) (undirected) Adds a constraint that the degrees for the network must be between lower and upper.

LologModels*Models***Description**

Models

lologPackageSkeleton

Create a skeleton for a package extending lolog

Description

Create a skeleton for a package extending lolog

Usage

```
lologPackageSkeleton(path = ".")
```

Arguments

path	where to create the package
------	-----------------------------

Details

lolog is a modular package, and can be extended at both the R and C++ level. This function will build a package skeleton that can be used as a starting point for development. To create the package in the current directory run:

```
lologPackageSkeleton()
Build and install the package from the command line with
R CMD build LologExtension
R CMD INSTALL LologExtension_1.0.tar.gz
```

See Also

[inlineLologPlugin](#)

Examples

```
## Not run:

#install package
lologPackageSkeleton()
system("R CMD build LologExtension")
system("R CMD INSTALL LologExtension_1.0.tar.gz")

library(LologExtension) #Load package

# Run model with new minDegree statistic
library(network)
m <- matrix(0,20,20)
for(i in 1:19) for(j in (i+1):20) m[i,j] <- m[j,i] <- rbinom(1,1,.1)
g <- network(m, directed=FALSE)
fit <- lologVariational(g ~ edges() + minDegree(1L))
summary(fit)

## End(Not run)
```

lologVariational

Fits a latent ordered network model using Monte Carlo variational inference

Description

Fits a latent ordered network model using Monte Carlo variational inference

Usage

```
lologVariational(
  formula,
  nReplicates = 5L,
  dyadInclusionRate = NULL,
  edgeInclusionRate = NULL,
  targetFrameSize = 5e+05
)
```

Arguments

<code>formula</code>	A lolog formula. See link{lolog}
<code>nReplicates</code>	An integer controlling how many dyad ordering to perform.
<code>dyadInclusionRate</code>	Controls what proportion of non-edges in each ordering should be dropped.
<code>edgeInclusionRate</code>	Controls what proportion of edges in each ordering should be dropped.
<code>targetFrameSize</code>	Sets dyadInclusionRate so that the model frame for the logistic regression will have on average this amount of observations.

Details

This function approximates the maximum likelihood solution via a variational inference on the graph (y) over the latent edge variable inclusion order (s). Specifically, it replaces the conditional probability $p(s | y)$ by $p(s)$. If the LOLOG model contains only dyad independent terms, then these two probabilities are identical, and thus variational inference is exactly maximum likelihood inference. The objective function is

$$E_{p(s)} \left(\log p(y|S, \theta) \right)$$

This can be approximated by drawing samples from $p(s)$ to approximate the expectation. The number of samples is controlled by the `nReplicates` parameter. The memory required is on the order of `nReplicates` * (# of dyads). For large networks this can be impractical, so adjusting `dyadInclusionRate` and `edgeInclusionRate` allows one to down sample the # of dyads in each replicate. By default these are set attempting to achieve as equal a number of edges and non-edges as possible while targeting a model frame with `targetFrameSize` number of rows.

If the model is dyad independent, replicates are redundant, and so `nReplicates` is set to 1 with a note.

The functional form of the objective function is equivalent to logistic regression, and so the `glm` function is used to maximize it. The asymptotic covariance of the parameter estimates is calculated using the methods of Westling (2015).

Value

An object of class c('lologVariationalFit','lolog','list') consisting of the following items:

formula	The model formula
method	"variational"
theta	The fit parameter values
vcov	The asymptotic covariance matrix for the parameter values.
nReplicates	The number of replicates
dyadInclusionRate	The rate at which non-edges are included
edgeInclusionRate	The rate at which edges are included
allDyadIndependent	Logical indicating model dyad independence
likelihoodModel	An object of class *LatentOrderLikelihood at the fit parameters
outcome	The outcome vector for the logistic regression
predictors	The change statistic predictor matrix for the logistic regression

References

Westling, T., & McCormick, T. H. (2015). Beyond prediction: A framework for inference with variational approximations in mixture models. arXiv preprint arXiv:1510.08151.

Examples

```
library(network)
data(ukFaculty)

# Delete vertices missing group
delete.vertices(ukFaculty, which(is.na(ukFaculty %v% "Group")))

fit <- lologVariational(ukFaculty ~ edges() + nodeMatch("GroupC"),
                        nReplicates=1L, dyadInclusionRate=1)
summary(fit)
```

plot.gofit

*Plots a gofit object***Description**

Plots a gofit object

Usage

```
## S3 method for class 'gofit'
plot(
  x,
  y,
  type = c("line", "box"),
  scaling = c("none", "std", "sqrt"),
  lineAlpha = 0.06,
  lineSize = 1,
  ...
)
```

Arguments

x	the gofit object
y	unused
type	type of plot, boxplot or lineplot
scaling	type of scaling of the network statistics. If "std", network statistics are scaling by subtracting off the observed statistics and scaling by the standard deviation. If "sqrt", network statistics are plotted on the square root scale (The square root is the variance stabilizing transformation for a Poisson random variable). The default is "none", where the network statistics are not scaled.
lineAlpha	The transparency of the simulated statistics lines
lineSize	The width of the lines
...	passed to either boxplot or geom_line

Examples

```
library(network)
data(ukFaculty)

# Delete vertices missing group
delete.vertices(ukFaculty, which(is.na(ukFaculty %v% "Group")))

# A dyad independent model
fitind <- lolog(ukFaculty ~ edges() + nodeMatch("GroupC") + nodeCov("GroupC"))
summary(fitind)

# Check gof on degree distribution (bad!)
gind <- gofit(fitind, ukFaculty ~ degree(0:50))
plot(gind)
plot(gind, type="box")
```

plot.lologGmm*Conduct Monte Carlo diagnostics on a lolog model fit*

Description

This function creates simple diagnostic plots for MC sampled statistics produced from a lolog fit.

Usage

```
## S3 method for class 'lologGmm'  
plot(x, type = c("histograms", "target", "model"), ...)
```

Arguments

- x A model fit object to be diagnosed.
- type The type of diagnostic plot. "histograms", the default, produces histograms of the sampled output statistic values with the observed statistics represented by vertical lines. "target" produces a pairs plot of the target output statistic values with the pairs of observed target statistics represented by red squares. output statistic values with the observed statistics represented by vertical lines. "model" produces a pairs plot of the sampled output statistic values with the pairs of observed statistics represented by red squares.
- ... Additional parameters. Passed to [geom_histogram](#) if type="histogram" and [pairs](#) otherwise.

Details

Plots are produced that represent the distributions of the output sampled statistic values or the target statistics values. The values of the observed target statistics for the networks are also represented for comparison with the sampled statistics.

Examples

```
library(network)  
set.seed(1)  
data(flo)  
flomarriage <- network(flo,directed=FALSE)  
flomarriage %v% "wealth" <- c(10,36,27,146,55,44,20,8,42,103,48,49,10,48,32,3)  
  
# An order dependent model  
fit3 <- lolog(fломарriage ~ edges + nodeCov("wealth") + preferentialAttachment(),  
               flомарriage ~ star(2:3), verbose=FALSE)  
plot(fit3)  
plot(fit3, "target")  
plot(fit3, "model")
```

`plot.Rcpp_DirectedNet` *plot an DirectedNet object*

Description

plot an DirectedNet object

Usage

```
## S3 method for class 'Rcpp_DirectedNet'
plot(x, ...)
```

Arguments

x	the Rcpp_DirectedNet object
...	additional parameters for plot.network

Details

This is a thin wrapper around [plot.network](#).

Examples

```
data(ukFaculty)
net <- as.BinaryNet(ukFaculty)
plot(net, vertex.col=net[["Group"]]+1)
```

`plot.Rcpp_UndirectedNet`
Plot an UndirectedNet object

Description

Plot an UndirectedNet object

Usage

```
## S3 method for class 'Rcpp_UndirectedNet'
plot(x, ...)
```

Arguments

x	the object
...	additional parameters for plot.network

Details

This is a thin wrapper around [plot.network](#).

Examples

```
el <- matrix(c(1,2),ncol=2)
net <- new(UndirectedNet, el, 5L)
net[1,5] <- 1
net[2,5] <- 1
plot(net)
```

print.gofit *prints a gofit object*

Description

prints a gofit object

Usage

```
## S3 method for class 'gofit'
print(x, ...)
```

Arguments

x	The object
...	passed to print.data.frame

print.lolog *Print a ‘lolog’ object*

Description

Print a ‘lolog’ object

Usage

```
## S3 method for class 'lolog'
print(x, ...)
```

Arguments

x	the object
...	additional parameters (unused)

`print.lologVariationalFit`

Print of a lologVariationalFit object

Description

Print of a lologVariationalFit object

Usage

```
## S3 method for class 'lologVariationalFit'
print(x, ...)
```

Arguments

<code>x</code>	the object
<code>...</code>	additional parameters (unused)

`registerDirectedStatistic`

Register Statistics

Description

Register Statistics

Usage

```
registerDirectedStatistic
```

`simulate.lolog`

Generates BinaryNetworks from a fit lolog object

Description

Generates BinaryNetworks from a fit lolog object

Usage

```
## S3 method for class 'lolog'
simulate(object, nsim = 1, seed = NULL, convert = FALSE, ...)
```

Arguments

object	A ‘lolog’ object.
nsim	The number of simulated networks
seed	Either NULL or an integer that will be used in a call to set.seed before simulating
convert	convert to a network object#‘
...	unused

Value

A list of BinaryNet (or network if convert=TRUE) objects. Networks contain an additional vertex covariate “__order__” that indicates the sequence order in which the vertex was ‘added’ into the network.

Examples

```
library(network)
data(flo)
flobmarriage <- network(flo,directed=FALSE)
flobmarriage %v% "wealth" <- c(10,36,27,146,55,44,20,8,42,103,48,49,10,48,32,3)
fit <- lolog(flobmarriage ~ edges + nodeCov("wealth"))
net <- simulate(fit)[[1]]
plot(net)
```

summary.lolog

*Summary of a ‘lolog’ object***Description**

Summary of a ‘lolog’ object

Usage

```
## S3 method for class 'lolog'
summary(object, ...)
```

Arguments

object	the object
...	additional parameters (unused)

Examples

```
data(lazega)
fit <- lologVariational(lazega ~ edges() + nodeMatch("office") + triangles,
                        nReplicates=50L, dyadInclusionRate=1)
summary(fit)
```

ukFaculty*Friendship network of a UK university faculty*

Description

The personal friendship network of a faculty of a UK university, consisting of 81 vertices (individuals) and 817 directed and weighted connections. The school affiliation of each individual is stored as a vertex attribute. The survey contained missing data for the school of two individuals.

Usage

```
data(ukFaculty)
```

Licenses and Citation

When publishing results obtained using this data set, the original authors (Nepusz T., Petroczi A., Negyessy L., Bazso F. 2008) should be cited, along with this R package.

Copyright

Creative Commons Attribution-Share Alike 2.0 UK: England & Wales License, see <http://creativecommons.org/licenses/by-sa/2.0/uk/> for details.

Source

The data set was originally reported by Nepusz et. al. (2008) and was subsequently processed and included by the igraphdata package. We have simply converted their network from an igraph to a network object.

References

Nepusz T., Petroczi A., Negyessy L., Bazso F.: Fuzzy communities and the concept of bridgeness in complex networks. Physical Review E 77:016107, 2008.

Description

```
indexing
indexing
indexing
indexing
```

Usage

```
## S4 method for signature 'Rcpp_DirectedNet,ANY,ANY,ANY'
x[i, j, ... , maskMissing = TRUE, drop = TRUE]

## S4 method for signature 'Rcpp_UndirectedNet,ANY,ANY,ANY'
x[i, j, ... , maskMissing = TRUE, drop = TRUE]

## S4 replacement method for signature 'Rcpp_DirectedNet,ANY,ANY,ANY'
x[i, j, ... ] <- value

## S4 replacement method for signature 'Rcpp_UndirectedNet,ANY,ANY,ANY'
x[i, j, ... ] <- value
```

Arguments

x	object
i	indices
j	indices
...	unused
maskMissing	should missing values be masked by NA
drop	unused
value	values to assign

Examples

```
data(ukFaculty)
net <- as.BinaryNet(ukFaculty)

#dyad Extraction
net[1:2,1:5]
net$outNeighbors(c(1,2,3))

#dyad assignment
net[1,1:5] <- rep(NA,5)
net[1:2,1:5]
net[1:2,1:5,maskMissing=FALSE] #remove the mask over missing values and see
#nothing was really changed

#node variables
net$variableNames()
net[["Group"]]
net[["rnorm"]] <- rnorm(net$size())
net[["rnorm"]]
```

Index

* datasets
 lazega, 12
 ukFaculty, 26
[, 26
[, Rcpp_DirectedNet, ANY, ANY, ANY-method
 [], 26
[, Rcpp_DirectedNet-method (), 26
[, Rcpp_UndirectedNet, ANY, ANY, ANY-method
 [], 26
[, Rcpp_UndirectedNet-method (), 26
[<- (), 26
[<- , Rcpp_DirectedNet, ANY, ANY, ANY-method
 [], 26
[<- , Rcpp_DirectedNet-method (), 26
[<- , Rcpp_UndirectedNet, ANY, ANY, ANY-method
 [], 26
[<- , Rcpp_UndirectedNet-method (), 26
_lolog_initStats (call-symbols), 6
_rcpp_module_boot_lolog (call-symbols),
 6

as.BinaryNet, 2
as.BinaryNet.default, 3
as.network, 4
as.network.Rcpp_DirectedNet, 4
as.network.Rcpp_UndirectedNet, 5

BinaryNet, 6

calculateStatistics, 6
call-symbols, 6
coef.lolog, 7
cppFunction, 11
createCppModel, 7
createLatentOrderLikelihood, 8

DirectedLatentOrderLikelihood
 (LatentOrderLikelihood), 11
DirectedModel (LologModels), 16
DirectedNet, 4

DirectedNet (BinaryNet), 6

geom_histogram, 21
glm, 18
gofit, 9
gofit.lolog, 9, 9

initLologStatistics (call-symbols), 6
inlineLologPlugin, 10, 17

LatentOrderLikelihood, 11
lazega, 12
lolog, 6, 12
lolog-terms, 16
LologModels, 16
lologPackageSkeleton, 16
lologVariational, 13, 14, 17

pairs, 21
plot.gofit, 19
plot.lologGmm, 21
plot.network, 22, 23
plot.Rcpp_DirectedNet, 22
plot.Rcpp_UndirectedNet, 22
print.gofit, 23
print.lolog, 23
print.lologVariationalFit, 24

Rcpp_DirectedLatentOrderLikelihood-class
 (LatentOrderLikelihood), 11
Rcpp_DirectedModel-class (LologModels),
 16
Rcpp_DirectedNet-class (BinaryNet), 6
Rcpp_UndirectedLatentOrderLikelihood-class
 (LatentOrderLikelihood), 11
Rcpp_UndirectedModel-class
 (LologModels), 16
Rcpp_UndirectedNet-class (BinaryNet), 6
registerDirectedOffset
 (registerDirectedStatistic), 24
registerDirectedStatistic, 24

registerUndirectedOffset
 (registerDirectedStatistic), [24](#)
registerUndirectedStatistic
 (registerDirectedStatistic), [24](#)
runLologCppTests (call-symbols), [6](#)

simulate.lolog, [24](#)
sourceCpp, [11](#)
summary.lolog, [25](#)

ukFaculty, [26](#)
UndirectedLatentOrderLikelihood
 (LatentOrderLikelihood), [11](#)
UndirectedModel (LologModels), [16](#)
UndirectedNet, [5](#)
UndirectedNet (BinaryNet), [6](#)